
HD74LV125A

Quad. Bus Buffer Gates with 3-state Outputs

HITACHI

ADE-205-245 (Z)

1st Edition

March 1999

Description

The HD74LV125A features independent line drivers with three state outputs. Each output is disabled when the associated output enable (\overline{OE}) input is high. To ensure the high impedance state during power up or power down, \overline{OE} should be connected to V_{CC} through a pull-down resistor; the minimum value of the resistor is determined by the current sourcing capability of the driver. Low-voltage and high-speed operation is suitable for the battery-powered products (e.g., notebook computers), and the low-power consumption extends the battery life.

Features

- $V_{CC} = 2.0\text{ V to }5.5\text{ V}$ operation
- All inputs V_{IH} (Max.) = 5.5 V (@ $V_{CC} = 0\text{ V to }5.5\text{ V}$)
- All outputs V_O (Max.) = 5.5 V (@ $V_{CC} = 0\text{ V}$)
- Typical V_{OL} ground bounce < 0.8 V (@ $V_{CC} = 3.3\text{ V}$, $T_a = 25^\circ\text{C}$)
- Typical V_{OH} undershoot > 2.3 V (@ $V_{CC} = 3.3\text{ V}$, $T_a = 25^\circ\text{C}$)
- Output current $\pm 8\text{ mA}$ (@ $V_{CC} = 3.0\text{ V to }3.6\text{ V}$), $\pm 16\text{ mA}$ (@ $V_{CC} = 4.5\text{ V to }5.5\text{ V}$)

Function Table

Inputs		
\overline{OE}	A	Output Y
L	H	H
L	L	L
H	X	Z

Note: H:High level


L:Low level

X:Immaterial

Z:High impedance

HD74LV125A

Pin Arrangement



Absolute Maximum Ratings

Item	Symbol	Ratings	Unit	Conditions
Supply voltage range	V_{CC}	-0.5 to 7.0	V	
Input voltage range* ¹	V_I	-0.5 to 7.0	V	
Output voltage range* ^{1, 2}	V_O	-0.5 to $V_{CC} + 0.5$ -0.5 to 7.0	V	Output: H or L V_{CC} : OFF or Output: Z
Input clamp current	I_{IK}	-20	mA	$V_I < 0$
Output clamp current	I_{OK}	± 50	mA	$V_O < 0$ or $V_O > V_{CC}$
Continuous output current	I_O	± 35	mA	$V_O = 0$ to V_{CC}
Continuous current through V_{CC} or GND	I_{CC} or I_{GND}	± 70	mA	
Maximum power dissipation at $T_a = 25^\circ\text{C}$ (in still air)* ³	P_T	785 500	mW	SOP TSSOP
Storage temperature	T_{stg}	-65 to 150	$^\circ\text{C}$	

Notes: The absolute maximum ratings are values which must not individually be exceeded, and furthermore, no two of which may be realized at the same time.

1. The input and output voltage ratings may be exceeded if the input and output clamp-current ratings are observed.

2. This value is limited to 5.5 V maximum.


3. The maximum package power dissipation was calculated using a junction temperature of 150 $^\circ\text{C}$.

Recommended Operating Conditions

Item	Symbol	Min	Max	Unit	Conditions
Supply voltage range	V_{CC}	2.0	5.5	V	
Input voltage range	V_I	0	5.5	V	
Output voltage range	V_O	0	V_{CC}	V	H or L
		0	5.5		High impedance state
Output current	I_{OH}	—	-50	μA	$V_{CC} = 2.0 V$
		—	-2	mA	$V_{CC} = 2.3 \text{ to } 2.7 V$
		—	-8		$V_{CC} = 3.0 \text{ to } 3.6 V$
		—	-16		$V_{CC} = 4.5 \text{ to } 5.5 V$
	I_{OL}	—	50	μA	$V_{CC} = 2.0 V$
		—	2	mA	$V_{CC} = 2.3 \text{ to } 2.7 V$
		—	8		$V_{CC} = 3.0 \text{ to } 3.6 V$
		—	16		$V_{CC} = 4.5 \text{ to } 5.5 V$
Input transition rise or fall rate	$\Delta t / \Delta v$	0	200	ns/V	$V_{CC} = 2.3 \text{ to } 2.7 V$
		0	100		$V_{CC} = 3.0 \text{ to } 3.6 V$
		0	20		$V_{CC} = 4.5 \text{ to } 5.5 V$
Operating free-air temperature	T_a	-40	85	$^{\circ}C$	

Note: Unused or floating inputs must be held high or low.

Logic Diagram



DC Electrical Characteristics

- $T_a = -40 \text{ to } 85^{\circ}C$
-

Item	Symbol	$V_{CC} (V)^*$	Min	Typ	Max	Unit	Test Conditions
Input voltage	V_{IH}	2.0	1.5	—	—	V	
		2.3 to 2.7	$V_{CC} \times 0.7$	—	—		
		3.0 to 3.6	$V_{CC} \times 0.7$	—	—		
		4.5 to 5.5	$V_{CC} \times 0.7$	—	—		

HD74LV125A

Item	Symbol	V _{CC} (V)*	Min	Typ	Max	Unit	Test Conditions
	V _{IL}	2.0	—	—	0.5		
		2.3 to 2.7	—	—	V _{CC} × 0.3		
		3.0 to 3.6	—	—	V _{CC} × 0.3		
		4.5 to 5.5	—	—	V _{CC} × 0.3		
Output voltage	V _{OH}	Min to Max	V _{CC} - 0.1	—	—	V	I _{OH} = -50 μA
		2.3	2.0	—	—		I _{OH} = -2 mA
		3.0	2.48	—	—		I _{OH} = -8 mA
		4.5	3.8	—	—		I _{OH} = -16 mA
	V _{OL}	Min to Max	—	—	0.1		I _{OL} = 50 μA
		2.3	—	—	0.4		I _{OL} = 2 mA
		3.0	—	—	0.44		I _{OL} = 8 mA
		4.5	—	—	0.55		I _{OL} = 16 mA
Input current	I _{IN}	0 to 5.5	—	—	±1	μA	V _I = 5.5 V or GND
Off-state output current	I _{OZ}	5.5	—	—	±5	μA	V _O = V _{CC} or GND
Quiescent supply current	I _{CC}	5.5	—	—	20	μA	V _I = V _{CC} or GND, I _O = 0
Output leakage current	I _{OFF}	0	—	—	5	μA	V _I or V _O = 0 V to 5.5 V
Input capacitance	C _{IN}	3.3	—	3.0	—	pF	V _I = V _{CC} or GND

- Note: For conditions shown as Min or Max, use the appropriate values under recommended operating conditions.

Switching Characteristics

- V_{CC} = 2.5 ± 0.2 V

•

Item	Symbol	Ta = 25°C			Ta = -40 to 85°C			Unit	Test Conditions	FROM (Input)	TO (Output)
		Min	Typ	Max	Min	Max	Max				
Propagation delay time	t _{PLH}	—	6.8	13.0	1.0	15.5	ns	C _L = 15 pF C _L = 50 pF	A	Y	
	t _{PHL}	—	8.7	16.5	1.0	18.5					
Enable time	t _{ZH}	—	7.0	13.0	1.0	15.5	ns	C _L = 15 pF C _L = 50 pF	OE	Y	
	t _{ZL}	—	8.8	16.5	1.0	18.5					
Disable time	t _{HZ}	—	5.1	14.7	1.0	17.0	ns	C _L = 15 pF C _L = 50 pF	OE	Y	
	t _{LZ}	—	7.3	18.2	1.0	20.5					

- V_{CC} = 3.3 ± 0.3 V

•

		Ta = 25°C			Ta = -40 to 85°C					FROM (Input)	TO (Output)
Item	Symbol	Min	Typ	Max	Min	Max	Unit	Test Conditions			
Propagation delay time	t _{PLH}	—	4.8	8.0	1.0	9.5	ns	C _L = 15 pF	A	Y	
	t _{PHL}	—	6.1	11.5	1.0	13.0		C _L = 50 pF			
Enable time	t _{ZH}	—	4.8	8.0	1.0	9.5	ns	C _L = 15 pF	$\overline{\text{OE}}$	Y	
	t _{ZL}	—	6.2	11.5	1.0	13.0		C _L = 50 pF			
Disable time	t _{HZ}	—	4.1	9.7	1.0	11.5	ns	C _L = 15 pF	$\overline{\text{OE}}$	Y	
	t _{LZ}	—	5.5	13.2	1.0	15.0		C _L = 50 pF			

Switching Characteristics (cont)

- V_{CC} = 5.0 ± 0.5 V

•

		Ta = 25°C			Ta = -40 to 85°C					FROM (Input)	TO (Output)
Item	Symbol	Min	Typ	Max	Min	Max	Unit	Test Conditions			
Propagation delay time	t _{PLH}	—	3.4	5.5	1.0	6.5	n	C _L = 15 pF	A	Y	
	t _{PHL}	—	4.3	7.5	1.0	8.5	s	C _L = 50 pF			-
Enable time	t _{ZH}	—	3.4	5.1	1.0	6.0	n	C _L = 15 pF	$\overline{\text{OE}}$	Y	
	t _{ZL}	—	4.4	7.1	1.0	8.0	s	C _L = 50 pF			-
Disable time	t _{HZ}	—	3.2	6.8	1.0	8.0	ns	C _L = 15 pF	$\overline{\text{OE}}$	Y	
	t _{LZ}	—	4.0	8.8	1.0	10.0		C _L = 50 pF			-

Output-skew Characteristics

Item	Symbol	V _{CC} = (V)	Ta = 25°C		Ta = -40 to 85°C		Unit
			Min	Max	Min	Max	
Output skew	t _{sk(O)}	2.3 to 2.7	—	2.0	—	2.0	ns
		3.0 to 3.6	—	1.5	—	1.5	
		4.5 to 5.5	—	1.0	—	1.0	

Note: Skew between any outputs of the same package switching in the same direction. This parameter is warranted but not production tested.

HD74LV125A

Operating Characteristics

- $C_L = 50 \text{ pF}$

-

$T_a = 25^\circ\text{C}$

Item	Symbol	$V_{CC} = (\text{V})$	Min	Typ	Max	Unit	Test Conditions
Power dissipation capacitance	C_{PD}	3.3	—	23.2	—	pF	f = 10 MHz
		5.0	—	27.3	—		

Noise Characteristics


- $C_L = 50 \text{ pF}$

-

$T_a = 25^\circ\text{C}$


Item	Symbol	$V_{CC} = (\text{V})$	Min	Typ	Max	Unit	Test Conditions
Quiet output, maximum dynamic V_{OL}	$V_{OL(P)}$	3.3	—	0.3	0.8	V	
Quiet output, minimum dynamic V_{OL}	$V_{OL(V)}$	3.3	—	-0.3	-0.8		
Quiet output, minimum dynamic V_{OH}	$V_{OH(V)}$	3.3	—	3.0	—		
High-level dynamic input voltage	$V_{IH(D)}$	3.3	2.31	—	—	V	
Low-level dynamic input voltage	$V_{IL(D)}$	3.3	—	—	0.99		

Test Circuit




HD74LV125A

• Waveform-1




• Waveform-2





- Notes:
1. $t_r \leq 3 \text{ ns}$, $t_f \leq 3 \text{ ns}$
 2. Input waveform: $\text{PRR} \leq 1 \text{ MHz}$, duty cycle 50%
 3. Waveform-A is for an output with internal conditions such that the output is low except when disabled by the output control.
 4. Waveform-B is for an output with internal conditions such that the output is high except when disabled by the output control.

Package Dimensions



HD74LV125A



Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copy-right, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as in aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safe devices, so that the equipment incorporating the Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

<h1>HITACHI</h1>			
<p>Hitachi, Ltd. Semiconductor & IC Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109</p>			
URL	NorthAmerica	:	http://semiconductor.hitachi.com/
	Europe	:	http://www.hitachi-eu.com/hel/ecg
	Asia (Singapore)	:	http://www.has.hitachi.com.sg/grp3/sicd/index.htm
	Asia (Taiwan)	:	http://www.hitachi.com.tw/E/Product/SICD_Frame.htm
	Asia (HongKong)	:	http://www.hitachi.com.hk/eng/bo/grp3/index.htm
	Japan	:	http://www.hitachi.co.jp/Sicd/indx.htm
<p>For further information write to:</p>			
Hitachi Semiconductor (America) Inc.	Hitachi Europe GmbH	Hitachi Asia Pte. Ltd.	Hitachi Asia (Hong Kong) Ltd.
179 East Tasman Drive, San Jose, CA 95134	Electronic components Group Dornacher Straße 3 D-85622 Feldkirchen, Munich	16 Collyer Quay #20-00 Hitachi Tower Singapore 049318	Group III (Electronic Components) 7/F., North Tower, World Finance Centre, Harbour City, Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong
Tel: <1> (408) 433-1990 Fax: <1> (408) 433-0223	Germany Tel: <49> (89) 9 9180-0 Fax: <49> (89) 9 29 30 00	Tel: 535-2100 Fax: 535-1533	Tel: <852> (2) 735 9218 Fax: <852> (2) 730 0281 Telex: 40815 HITEC HX
	Hitachi Europe Ltd.	Hitachi Asia Ltd.	
	Electronic Components Group. Whitebrook Park Lower Cookham Road Maidenhead	Taipei Branch Office 3F, Hung Kuo Building, No.167, Tun-Hwa North Road, Taipei (105)	
	Berkshire SL6 8YA, United Kingdom Tel: <44> (1628) 585000 Fax: <44> (1628) 778322	Tel: <886> (2) 2718-3666 Fax: <886> (2) 2718-8180	
<p>Copyright © Hitachi, Ltd., 1998. All rights reserved. Printed in Japan.</p>			