

**Dual N-Ch 20V Fast Switching MOSFETs**
**General Description**

The UG2504W is the highest performance trench N-ch MOSFETs with extreme high cell density , which provide excellent RDSON and gate charge for most of the small power switching and load switch applications.

The UG2504W meet the RoHS and Green Product requirement with full function reliability approved.

**Features**

- Advanced high cell density Trench technology
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- Green Device Available

**Absolute Maximum Ratings**

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	20	V
$V_{GS}$	Gate-Source Voltage	$\pm 8$	V
$I_D @ T_A = 25^\circ C$	Continuous Drain Current, $V_{GS} @ 4.5V^1$	5.8	A
$I_D @ T_A = 70^\circ C$	Continuous Drain Current, $V_{GS} @ 4.5V^1$	4.6	A
$I_{DM}$	Pulsed Drain Current <sup>2</sup>	24	A
$P_D @ T_A = 25^\circ C$	Total Power Dissipation <sup>3</sup>	1.1	W
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_J$	Operating Junction Temperature Range	-55 to 150	°C

**Thermal Data**


Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction-ambient <sup>1</sup>	---	110	°C/W
$R_{\theta JC}$	Thermal Resistance Junction-Case <sup>1</sup>	---	70	°C/W

**Product Summary**

$BV_{DSS}$	$R_{DS(ON)}$	ID
20V	22mΩ	5.8A

**Applications**

- Power management in portable and battery operated products
- One cell battery pack protection
- Load Switch

**TSSOP8 Pin Configuration**


**Dual N-Ch 20V Fast Switching MOSFETs**
**Electrical Characteristics ( $T_J=25^\circ\text{C}$ , unless otherwise noted)**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$ , $I_D=250\mu\text{A}$	20	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	BVDSS Temperature Coefficient	Reference to $25^\circ\text{C}$ , $I_D=1\text{mA}$	---	0.028	---	$\text{V}/^\circ\text{C}$
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance <sup>2</sup>	$V_{\text{GS}}=4.5\text{V}$ , $I_D=5\text{A}$	---	17	22	$\text{m}\Omega$
		$V_{\text{GS}}=2.5\text{V}$ , $I_D=4\text{A}$	---	22	28	
		$V_{\text{GS}}=1.8\text{V}$ , $I_D=3\text{A}$	---	35	44	
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$ , $I_D=250\mu\text{A}$	0.3	0.6	1	V
$\Delta V_{\text{GS(th)}}$	$V_{\text{GS(th)}}$ Temperature Coefficient		---	-3.21	---	$\text{mV}/^\circ\text{C}$
$I_{\text{DSS}}$	Drain-Source Leakage Current	$V_{\text{DS}}=16\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=25^\circ\text{C}$	---	---	1	$\text{uA}$
		$V_{\text{DS}}=16\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=55^\circ\text{C}$	---	---	5	
$I_{\text{GSS}}$	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 12\text{V}$ , $V_{\text{DS}}=0\text{V}$	---	---	$\pm 100$	nA
$g_{\text{fs}}$	Forward Transconductance	$V_{\text{DS}}=5\text{V}$ , $I_D=5\text{A}$	---	28	---	S
$R_g$	Gate Resistance	$V_{\text{DS}}=0\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	1.5	3	$\Omega$
$Q_g$	Total Gate Charge (4.5V)	$V_{\text{DS}}=15\text{V}$ , $V_{\text{GS}}=4.5\text{V}$ , $I_D=5\text{A}$	---	14.8	20.7	$\text{nC}$
$Q_{\text{gs}}$	Gate-Source Charge		---	1.44	2.0	
$Q_{\text{gd}}$	Gate-Drain Charge		---	2.8	3.9	
$T_{\text{d(on)}}$	Turn-On Delay Time	$V_{\text{DD}}=10\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $R_G=3.3\Omega$	---	3.2	6.4	$\text{ns}$
$T_r$	Rise Time		---	40	80	
$T_{\text{d(off)}}$	Turn-Off Delay Time		---	40.8	82	
$T_f$	Fall Time		---	9.2	18.4	
$C_{\text{iss}}$	Input Capacitance	$V_{\text{DS}}=15\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $f=1\text{MHz}$	---	952	1333	$\text{pF}$
$C_{\text{oss}}$	Output Capacitance		---	90	126	
$C_{\text{rss}}$	Reverse Transfer Capacitance		---	79	111	


**Diode Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous Source Current <sup>1,4</sup>	$V_G=V_D=0\text{V}$ , Force Current	---	---	5.8	A
$I_{\text{SM}}$	Pulsed Source Current <sup>2,4</sup>		---	---	24	A
$V_{\text{SD}}$	Diode Forward Voltage <sup>2</sup>	$V_{\text{GS}}=0\text{V}$ , $I_s=1\text{A}$ , $T_J=25^\circ\text{C}$	---	---	1.2	V
$t_{\text{rr}}$	Reverse Recovery Time	$I_F=5\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$ , $T_J=25^\circ\text{C}$	---	8.9	---	nS
$Q_{\text{rr}}$	Reverse Recovery Charge		---	2.9	---	nC


Note :

- 1.The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width  $\leq 300\mu\text{s}$  , duty cycle  $\leq 2\%$
- 3.The power dissipation is limited by  $150^\circ\text{C}$  junction temperature
- 4.The data is theoretically the same as  $I_D$  and  $I_{\text{DM}}$  , in real applications , should be limited by total power dissipation.


**Typical Characteristics**



**Fig.1 Typical Output Characteristics**




**Fig.3 Forward Characteristics of reverse**




**Fig.5  $V_{GS(th)}$  vs.  $T_J$**


**Dual N-Ch 20V Fast Switching MOSFETs**



**Fig.2 On-Resistance vs. Gate-Source**




**Fig.4 Gate-Charge Characteristics**




**Fig.6 Normalized  $R_{DS(on)}$  vs.  $T_J$**


**Dual N-Ch 20V Fast Switching MOSFETs**




**Fig.7 Capacitance**




**Fig.8 Safe Operating Area**



**Fig.9 Normalized Maximum Transient Thermal Impedance**



**Fig.10 Switching Time Waveform**



**Fig.11 Gate Charge Waveform**