



REVISIONS	
ISSUE	CHANGES
0	ER 35803 KH 09/14/94
1	CN 36939 A KH 04/23/96
2	CN 37437 A VLS 09/09/98
D	ER 34758 COL 09/05/11

1201-22-9

CUSTOMER  
SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICES, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

USED ON

CAGE CODE:91836

JACK, PANEL, N

DRAWN KH	DATE 04/27/94
DESIGN JT	DATE 04/28/94
APPR.	DATE

**WINCHESTER ELECTRONICS CORPORATION**  
 Winchester Electronics  
 62 Berran Industrial  
 Road North  
 Wellingford, CT 06492  
 B SIZE

1201-22-9

- NOTES:
1. FOR USE WITH BOEING BMS13-65 OF & ADAMS RUSSELL FC14Z CABLES.
  2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
  3. FOR CRIMPING USE DIE KTH-2211.
  4. INTERFACE PER MIL-STD-348, FIG. 304-2.
  5. FOR USE WITH .22 MAX PANEL.
  6. CENTER CONTACT (1-534-69MA9) SUPPLIED UNASSEMBLED.
  7. MARK PACKAGE: KINGS 1201-22-9 YRWK (DATE CODE)
  8. MATERIALS:  
 INSULATOR: TEFLON, ASTM-D-1710  
 K-GRIP SLEEVE: CQM, BRONZE, ASTM-B135  
 CENTER CONTACT: BER, COP, ASTM-B196  
 ALL OTHER PARTS: BRASS, ASTM-B16
  9. FINISHES:  
 CENTER CONTACTS: .000050 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290(RH(S))  
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PLATE PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734(RH(S))
  10. ELECTRICAL CHARACTERISTICS:  
 NOMINAL IMPEDANCE: 50 OHMS  
 VOLTAGE RATING: 1000 VRMS  
 FREQUENCY RANGE: DC TO 11 GHz
  11. WEIGHT: 38.6 GRAMS(.85 POUNDS)