

Connection honeycomb - W 80/ 80-FS/FS(12-2,8-0,8) - 0611017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Connection honeycomb, Connection type: Screw mounting, Number of positions: 80, Color: green

Product description

Connection honeycomb, Connection type: Screw mounting, Number of positions: 80, Color: green

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 350 (CL-2005)
GTIN	 4 017918 003104
Weight per piece (including packing)	0.0 GRM
Weight per Piece (excluding packing)	541.98 GRM
Country of origin	GERMANY

Technical data

General

Number of connections	80
Color	green
Insulating material	PA/F
Inflammability class according to UL 94	HB

Dimensions

Width	146 mm
Length	164 mm
Height	38 mm

Technical data

Maximum load current	16 A
Rated surge voltage	8 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I

Connection honeycomb - W 80/ 80-FS/FS(12-2,8-0,8) - 0611017

Technical data

Technical data

Nominal current I _N	16 A (current data for slip-on connections in acc. with EN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)
Nominal voltage U _N	1000 V (voltage data for slip-on connections in acc. with EN 61210 are also dependent on nominal size, material, insulation of the sleeve and conductor cross section.)

Connection data

Slip-on connection	6.3/2.8 x 0.8 mm
--------------------	------------------

Classifications

eclass

eClass 4.0	27141124
eClass 4.1	27141124
eClass 5.0	27141124
eClass 5.1	27141124
eClass 6.0	27141124

etim

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC000897

unspsc

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410

Approvals

Certificates

Certification

GOST

Certification EX

Certification submitted

Connection honeycomb - W 80/ 80-FS/FS(12-2,8-0,8) - 0611017

Approvals

Approval details

GOST

Accessories

Accessories

Assembly

Equipotential busbar - S-FS (2,8X0,8) - 3191699



Potential busbar, with slotted 6.3/2.8 mm flat connectors, max. 40 A, brass, tin-plated, length: 1 m