




MBR830-MBR8100

Schottky Barrier Rectifiers

VOLTAGE RANGE: 30 - 100 V

CURRENT: 8.0 A

TO-220AC



Dimensions in millimeters

Features

- ◇ High surge capacity.
- ◇ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.
- ◇ Metal silicon junction, majority carrier conduction.
- ◇ High current capacity, low forward voltage drop.
- ◇ The plastic material carries U/L recognition 94V-0

Mechanical Data

- ◇ Case: JEDEC TO-220AC, molded plastic body
- ◇ Polarity: As marked
- ◇ Position: Any
- ◇ Weight: 0.064 ounces, 1.81 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

		MBR 830	MBR 835	MBR 840	MBR 845	MBR 850	MBR 860	MBR 880	MBR 8100	UNITS						
Maximum recurrent peak reverse voltage	V_{RRM}	30	35	40	45	50	60	80	100	V						
Maximum RMS Voltage	V_{RMS}	21	25	28	32	35	42	56	70	V						
Maximum DC blocking voltage	V_{DC}	30	35	40	45	50	60	80	100	V						
Maximum average forward total device rectified current @ $T_c = 125^\circ C$	$I_{F(AV)}$	8.0								A						
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	150								A						
Maximum forward voltage (I _F =8.0A, $T_c=125^\circ C$) (I _F =8.0A, $T_c=25^\circ C$) (Note 1) (I _F =16A, $T_c=25^\circ C$)	V_F	0.57		0.70		-		0.85		V						
Maximum reverse current @ $T_c=25^\circ C$ at rated DC blocking voltage @ $T_c=125^\circ C$	I_R	0.1		15		0.5		50		m A						
Maximum thermal resistance (Note 2)	$R_{\theta JC}$	3.0								K/W						
Operating junction temperature range	T_J	-55 ---- + 150								°C						
Storage temperature range	T_{STG}	-55 ---- + 150								°C						

NOTE: 1. Pulse test: 300μs pulse width, 1% duty cycle.

2. Thermal resistance from junction to case.

Ratings AND Characteristic Curves

FIG.1 – FORWARD CURRENT DERATING CURVE




FIG.2 – MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PERLEG






FIG.3 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC PERLEG



INSTANTANEOUS FORWARD VOLTAGE, VOLTS

FIG.4 – TYPICAL REVERSE CHARACTERISTICS



PERCENT OF RATED PEAK REVERSE VOLTAGE, %