


塑封快恢复整流二极管
反向电压 400 --- 1000V
正向电流 1.5 A

Plastic Fast Recover Rectifier
Reverse Voltage 400 to 1000V
Forward Current 1.5A



特征 Features

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力较强 High forward surge capability
- 高温焊接保证 High temperature soldering guaranteed:
260°C/10 秒, 0.375" (9.5mm)引线长度。
260°C/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线和管体皆符合RoHS标准。
Lead and body according with RoHS standard

机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25°C 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	RU3	RU3M	RU3A	RU3AM	RU3C	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	400	400	600	600	1000	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	280	280	420	420	700	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	400	400	600	600	1000	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}			1.5			A
峰值正向浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}			20			A
典型热阻 Typical thermal resistance	R _{θJA}			45			°C/W
工作结温和存储温度 Operating junction and storage temperature range	T _j , T _{TSG}			-55 --- +150			°C

电特性 TA = 25°C 除非另有规定。

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	RU3	RU3M	RU3A	RU3AM	RU3C	单位 Unit
最大正向电压 Maximum forward voltage	I _F = 1.5A	V _F	1.5	1.1	1.5	1.1	2.5
最大反向电流 Maximum reverse current	TA= 25°C TA=100°C	I _R		5.0 50			µA
最大反向恢复时间 MAX. Reverse Recovery Time	I _F =0.5A I _R =1.0A I _{RR} =0.25A	trr		100			nS
典型结电容 Type junction capacitance	V _R = 4.0V, f = 1MHz	C _j		25			pF

特性曲线 Characteristic Curves

