

GLBCP69

PNP SILICON EPITAXIAL TRANSISTOR



Description

The GLBCP69 is designed for use in low voltage and medium power applications.

Features

- $V_{CE0} : -20V$
- $I_C : 1A$

Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	6.70	7.30	B	13° TYP.	
C	2.90	3.10	J	2.30 REF.	
D	0.02	0.10	1	6.30	6.70
E	0°	10°	2	6.30	6.70
I	0.60	0.80	3	3.30	3.70
H	0.25	0.35	4	3.30	3.70
			5	1.40	1.80

Absolute Maximum Ratings at $T_a = 25^\circ C$





Parameter	Symbol	Ratings	Unit
Junction Temperature	T_j	+150	$^\circ C$
Storage Temperature	T_{stg}	-65~+150	$^\circ C$
Collector to Base Voltage	V_{CB0}	-25	V
Collector to Emitter Voltage	V_{CE0}	-20	V
Emitter to Base Voltage	V_{EB0}	-5	V
Collector Current	I_C	-1	A
Total Power Dissipation	P_D	1.5	W

Electrical Characteristics ($T_a = 25^\circ C$, unless otherwise noted)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV_{CB0}	-25	-	-	V	$I_C = -100\mu A, I_E = 0$
BV_{CE0}	-20	-	-	V	$I_C = -1mA, I_B = 0$
BV_{EB0}	-5	-	-	V	$I_E = -10\mu A, I_C = 0$
I_{CB0}	-	-	-10	μA	$V_{CB} = -25V, I_E = 0$
I_{EB0}	-	-	-10	μA	$V_{EB} = -5V, I_C = 0$
* $V_{CE(sat)1}$	-	-	-500	mV	$I_C = -1A, I_B = -100mA$
* $V_{BE(on)}$	-	-	-1.0	V	$V_{CE} = -1V, I_C = -1A$
* h_{FE1}	50	-	-		$V_{CE} = -10V, I_C = -5mA$
* h_{FE2}	85	-	375		$V_{CE} = -1V, I_C = -500mA$
* h_{FE3}	60	-	-		$V_{CE} = -1V, I_C = -1A$
fT	-	60	-	MHz	$V_{CE} = -5V, I_C = -10mA$

*Pulse Test: Pulse Width $\leq 380\mu s$, Duty Cycle $\leq 2\%$

Characteristics Curve



Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

Head Office And Factory:

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165