


## DPS-180KB-4 Series

85 (W) x 65 (H) x 175 (L) mm



BSMI

CB



UL US



### FEATURES

- Complies with TFX12V
- Remote On/Off
- High Reliability
- Low Acoustic Noise
- Built-in EMI Filter
- Meets IEC 60950: 1999/UL 60950 3<sup>rd</sup> Edition
- TTL Compatible Power Good Signal
- All Outputs SELV (Safety Extra Low Voltage)
- Fan Speed Control Function Inside
- Optional PFC Circuit

### ENVIRONMENTAL

- MTBF: >100,000 hours at Max. Load, 115Vac and 25°C ambient conditions
- Dielectric Withstand: Input to Output: 1800Vac for 1 sec  
Input to Frame Ground: 1800Vac for 1 sec
- ESD: IEC 61000-4-2
- Surge: IEC 61000-4-5
- Harmonic: IEC 61000-3-2 Class D

### ELECTRICAL SPECIFICATIONS

#### Input

- Input Range 90-135/180-265Vac, Switch-Select
- Frequency 47-63Hz
- Input Current 6A @ 115Vac; 3A @ 230Vac
- Efficiency >68% @ Max. Load, Nominal Line
- EMI/RFI FCC Part 15 Class B  
CISPR 22 Class B

#### Output

- Maximum Power 180 Watts
- Holdup Time >17mS @ Max. Load, Nominal Line
- Rise Time 0.2mS ~ 20mS
- Leakage Current <0.75mA @ 250Vac
- Overvoltage Protection: +3.3V, +5V, +12V, -12V
- Overcurrent Protection: <240VA
- Short-Circuit Protection: Latch off all main outputs reset by cycling On/Off control or AC power.
- Power Good Signal: TTL/CMOS compatible on delay 100mS to 500mS, off delay 1mS minimum.

Output	Voltage	Regulation	Minimum Load	Maximum Load	Peak Load	Ripple & Noise Vp-p
V1	+3.3V	+/-5%	0.5A	16.7A	-	50mV
V2	+5V	+/-5%	0.3A	12.0A	-	50mV
V3	+12V	+/-5%	2.0A	10.0A	13.0A	120mV
V4	-12V	+/-10%	0A	0.3A	-	120mV
V5	+5Vsb	+/-5%	0A	2.0A	-	50mV

- Peak-to-peak with 20MHz bandwidth and 10  $\mu$ F in parallel with a 0.1  $\mu$ F capacitor.
- Total combined power on +3.3V & +5V rails are 61W maximum.

All specifications are subject to change without prior notice.

**DELTA ELECTRONICS, INC.**  
3, TUNG YUAN ROAD,  
CHUNGLI INDUSTRIAL ZONE  
TAOYUAN SHIEN, TAIWAN, R.O.C.  
TEL : 886-3-4526107  
FAX : 886-3-4527314  
mail: powersales@delta.com.tw

**DELTA PRODUCTS CORPORATION**  
4405 CUSHING PARKWAY  
FREMONT, CA 94538, U.S.A.  
TEL : 1-510-668-5100  
FAX : 1-510-668-0680

**DELTA ELECTRONICS (JAPAN) INC.**  
DELTA SHIBADAIMON BLDG.  
2-1-14 SHIBADAIMON, MINATO-KU,  
TOKYO, 105-0012, JAPAN  
TEL : 81-3-5733-1111  
FAX : 81-3-5733-1211

**DELTA ELECTRONICS EUROPE LTD.**  
2 YOUNG PLACE  
KELVIN INDUSTRIAL ESTATE  
EAST KILBRIDE, GLASGOW G75 0TD, U.K.  
TEL : 44-1355-588888  
FAX : 44-1355-588889