

## 1.0kV 2.5A HIGH VOLTAGE DIODE

HVRWx is high reliability resin molded type high voltage diode in small size package which is sealed a multilayed mesa type silicon chip by epoxy resin.

**■ Features**


- High speed switching
- High Current
- High surge resistivity for CRT discharge
- High reliability design
- High Voltage

**■ Applications**

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power

**■ Maximum Ratings and Characteristics**

- Absolute Maximum Ratings

**■ Outline Drawings : mm****■ Cathode Mark**

Type	Mark
HVRW1	

Items	Symbols	Condition	HVRW1	Units
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>		1.0	kV
Average Output Current	I <sub>o</sub>	T <sub>a</sub> =25°C, Resistive Load	2.5	A <sub>peak</sub>
Surge Current	I <sub>FSM</sub>		100	A <sub>peak</sub>
Junction Temperature	T <sub>j</sub>		155	°C
Allowable Operation Case Temperature	T <sub>c</sub>		125	°C
Storage Temperature	T <sub>stg</sub>		-40 to +155	°C

- Electrical Characteristics (T<sub>a</sub>=25°C Unless otherwise specified )

Items	Symbols	Conditions	HVRW1	Units
Maximum Forward Voltage Drop	V <sub>F</sub>	at 25°C, I <sub>F</sub> = I <sub>F(AV)</sub>	2.0	V
Maximum Reverse Current	I <sub>R1</sub>	at 25°C, V <sub>R</sub> = V <sub>RRM</sub>	50	uA
	I <sub>R2</sub>	at 100°C, V <sub>R</sub> = V <sub>RRM</sub>	500	uA
Maximum Reverse Recovery Time	T <sub>rr</sub>	at 25°C	150	nS
Junction Capacitance	C <sub>j</sub>	at 25°C, V <sub>R</sub> =0V, f=1MHz	--	pF