

SSMB Plug to BNC Male Adapter



TECHNICAL DATA SHEET

PE9393

SSMB Plug to BNC Male Adapter

C_{Δ}	nfia	ura	tion
CU	m	ula	LIOII

Connector 1SSMB PlugImpedance 150 OhmsConnector 2BNC MaleImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +165

Size

Length, in [mm] 1.2 [30.48] Width/Dia., in [mm] 0.57 [14.48]

Connector 1

Type SSMB Plug Inner Conductor Material and Plating Gold Inner Conductor Plating Specification MIL-G-45204 Body Material and Plating Brass, Nickel Dielectric Type Teflon

Connector 2

Type BNC Male
Inner Conductor Material and Plating Gold
Inner Conductor Plating Specification MIL-G-45204
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/ssmb-plug-bnc-male-straight-adapter-pe9393-p.aspx

SSMB Plug to BNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9393 CAD Drawing

SSMB Plug to BNC Male Adapter

