



注)
NOTE.

- 適合ハウジング: 5379-N
USE WITH 5379-N HOUSING.
- 当該端子の推奨基板穴径は $\phi 0.8 \pm 0.05$ とする。
RECOMMENDED P.C.B. HOLE DIM: $\phi 0.8 \pm 0.05$

39-00-0030	5378TL	バラ状 LOOSE
39-00-0029	5378T	連鎖状 CHAIN
EDP.NO.	ENG.NO.	形状 FORM

DO NOT SCALE DRAWING	04 NO. DRAWN: CH'K: APPR:	03 NO. DRAWN: CH'K: APPR:	02 NO. DRAWN: CH'K: APPR:	01 NO. DRAWN: CH'K: APPR:	REDRAWN 00 NO. JC2000-0629 DRAWN: K.KOHAMA W/2/8 CH'K: T.YAMAGUCHI W/2/8 APPR: M.FUKUSHIMA W/2/8	MATERIAL 材料 黄銅、銅下地 錫メッキ BRASS, TIN OVER COPPER PLATING.	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	SCALE 10:1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	<input checked="" type="checkbox"/> THIRD ANGLE PROJECTION	DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY	SHT REV	
	WIRE RANGE 適用電線範囲 AWG #24-#28 $0.08-0.22\text{mm}^2$						FINISH 仕上げ	10 UNDER 未満	10 OVER 以上	30 UNDER 未満	TITLE: 2.0 BOARD IN CONN. CRIMP PIN		
	INS. RANGE 被覆外径 $\phi 1.5$ MAX.						ANGLE 角度	30 OVER 以上	30 UNDER 未満	30 OVER 以上	MOLEX MOLEX INCORPORATED		
	CAD FILENAME S5378.S01						MATERIAL NO. 5378*	DRAWING NO. SD-5378*	APPROVED BY & DATE M.FUKUSHIMA '00/ 3/30		SHEET NO. 1		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.