



NOTES:

1. INTERFACE PER MIL-STD-348, FIG. 301-1.
2. SAME AS UG-911 A/U EXCEPT FOR FINISH.
3. MATERIALS:
 INSULATOR: TEFLON, ASTM-D-1457
 GASKET: SILICONE RUBBER, ZZ-R-765
 CENTER CONTACT: BER. COP., ASTM-B-196
 LOCKWASHER: PHOS. BRONZE, QQ-B-750
 ALL OTHER METAL PARTS: BRASS, ASTM-B16
4. FINISHES:
 CENTER CONTACT: SILVER PLATE PER QQ-S-365
 GLASS SEAL: TIN DIPPED
 ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT FINISH (TR-5)
5. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 500 VRMS
 FREQUENCY RANGE: DC TO 4
6. ENVIRONMENTAL:
 LEAKAGE RATE SHALL NOT EXCEED 1×10^{-7} cc/sec OF
 TRACER GAS AT ATMOSPHERIC PRESSURE.

SDKC-79-74

REVISIONS	
ISSUE	CHANGES
0	ER 6183 JM 07/22/68
1	CN 6188 A JM 07/23/68
2	CN 18605 C MA 09/22/78
3	CN 37587 C REDRAWN TML 10/13/99
E	REVISED PER ER23475 GGR 04/23/2010

KC7974S

CUSTOMER SALES DRAWING

SCALE 4:1	
APPROX SURFACE AREA	
USED ON	
REF:	
RECEPTACLE, BULKHEAD, HERMETIC SEAL, BNC	
DRAWN MZB	DATE 11/03/88
DESIGN MJB	DATE 11/15/88
APPR.	DATE

KINGS
by WINCHESTER ELECTRONICS

Winchester Electronics
62 Barnes Industrial
Road North
Wallingford, CT 06492

SDKC-79-74