

15x15x2 Ceramic Patch Antenna (Standard)

1. Explanation of Product Number

H	2	P	1	3	F	A	C	A	F	0	1	0	0
				(1)	(2)	(3)	(4)	(5)	(6)				



Product Code:

(1) Product Categories:

3: ceramic patch antenna

(2) Dimensions and Polarization:

FA: 15x15x02 (mm)/right hand circular polarization

(3) Material:

C: MA-FL

(4) Working Frequency:

A: 1575.42MHz

(5) Ground Plane Dimensions:

F: 30x30(mm)

(6) Antenna Series:

01: serial number

Tolerances (Unless otherwise specified) X : ± 1 X.X : ± 0.1 X.XX : ± 0.01 Angle : ± Hole Dia. : ±		 Unictron Technologies Corporation Website: www.unictron.com	
Scale :	Unit : mm	2010-08-04	
Prepared By : Meiping	Checked By : Chinling	THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION	
Designed By : Chinling	Approved By : Herbert		
TITLE : 15*15*2 Ceramic Patch Antenna (Standard)		DOCUMENT NO.	H2P13FACAF0100
		REV. A	

2. Features

- *Stable and reliable in performances
- *Low temperature coefficient of frequency
- *Compact size
- *RoHS compliance

3. Applications

- *Navigation systems or position tracking systems
- *Hand-held devices when GPS function is needed, e.g., PDA, Smart phone, PND.

4. Description

Unictron's patch antenna series are ceramic antennas specially designed for GPS application. This ceramic patch antenna has excellent stability and sensitivity through the use of high performance proprietary ceramic materials and processes.

5. Electrical Specifications (30x30(mm) ground plane)

Characteristics		Specifications	Unit
Outline Dimensions		15×15×2	mm
Ground Plane		30×30	mm
Center Frequency*		1575.42±2	MHz
Bandwidth (under -10dB return loss)		5 min.	MHz
VSWR		2 max.	
Impedance		50	Ω
Polarization		RHCP	
Gain	@Zenith	0.8 (typical)	dBic
	@10° Elevation	-7.9 (typical)	
Temperature Coefficient of Frequency		0±20 max (@ -20°C~80°C)	ppm/°C

*Center frequency will be offset to working frequency according to the conditions of user's ground plane and radome.

Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : ± Hole Dia. : ±



Unictron Technologies Corporation
Website: www.unictron.com

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Chinling Approved By : Herbert

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION


**TITLE : 15*15*2 Ceramic Patch Antenna
(Standard)**

**DOCUMENT
NO.**

H2P13FACAF0100

**REV.
A**

6. Antenna Dimensions (unit: mm)





front side

back side

7. Electrical Characteristics (30x30(mm) ground plane)

Return Loss(S_{11})

Smith Chart



Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : \pm Hole Dia. : \pm



Unictron Technologies Corporation
Website: www.unictron.com


Scale :	Unit : mm
Prepared By : Meiping	Checked By : Chinling
Designed By : Chinling	Approved By : Herbert

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION


TITLE : 15*15*2 Ceramic Patch Antenna (Standard)	DOCUMENT NO.	H2P13FACAF0100	REV.
			A

8. Radiation Pattern (30x30(mm) ground plane)

0°



90°



Right hand circular polarized signal $f_0=1575.42\text{MHz}$

Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : \pm Hole Dia. : \pm



Unictron Technologies Corporation
Website: www.unictron.com

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Chinling Approved By : Herbert

2010-08-04

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE : 15*15*2 Ceramic Patch Antenna (Standard)

DOCUMENT NO.

H2P13FACAF0100

REV.

A