

### Linear Systems replaces discontinued Siliconix J511

The Linear Systems LSJ511 is a  $\pm 20\%$  range current regulator

The LSJ511 is a  $\pm 20\%$  range current regulator designed for demanding applications in test equipment and instrumentation. The LSJ511 utilizes JFET techniques to produce a single two-leaded device which is extremely simple to operate.

- Two-Lead Plastic Package
- Guaranteed  $\pm 20\%$  Tolerance
- Operation up to 50V
- Excellent Temperature Stability
- Simple Series Circuitry, No Separate Voltage Source
- Tight Guaranteed Circuit Performance
- Excellent Performance in Low-Voltage/Battery Circuits and High-Voltage Spike Protection
- High Circuit Stability vs. Temperature

#### LSJ511 Applications:

- Constant-Current Supply
- Current-Limiting
- Timing Circuits

#### FEATURES

REPLACEMENT SOURCE FOR SILICONIX J511

WIDE CURRENT RANGE 4.70mA  $\pm 20\%$

BIASING NOT REQUIRED  $V_{GS} = 0V$

#### ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

@ 25 °C (unless otherwise stated)

#### Maximum Temperatures

Storage Temperature -55 to 150°C

Junction Operating Temperature -55 to 135°C

#### Maximum Power Dissipation

Continuous Power Dissipation @125°C 350mW

#### Maximum Currents

Forward Current 20mA

Reverse Current 50mA

#### Maximum Voltages

Peak Operating Voltage  $P_{OV} = 45V$


#### ELECTRICAL CHARACTERISTICS @ 25 °C (unless otherwise stated)

SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	CONDITIONS
$P_{OV}$	Peak Operating Voltage <sup>2</sup>	50			V	$I_F = 1.1I_{F(max)}$
$V_R$	Reverse Voltage		0.8		V	$I_R = 1mA$
$C_F$	Forward Capacitance		2.2		pF	$V_F = 25V, f = 1MHz$

#### SPECIFIC ELECTRICAL CHARACTERISTICS @ 25 °C (unless otherwise stated)

PART	Forward Current <sup>3</sup> $I_F$			Dynamic Impedance <sup>4</sup> $Z_d$		Knee Impedance $Z_k$	Limiting Voltage <sup>5</sup> $V_L$	
	$V_F = 25V$			$V_F = 25V$		$V_F = 6V$	$I_F = 0.8I_{F(min)}$	
	MIN	NOM	MAX	MIN	TYP	TYP	TYP	MAX
LSJ511	3.800	4.70	5.600	0.12	0.3	0.05	4.2	2.1

#### V-I CHARACTERISTICS CURRENT REGULATING DIODE




#### Notes:


1. Absolute maximum ratings are limiting values above which serviceability may be impaired.
2. Pulsed,  $t = 2ms$ . Maximum  $V_F$  where  $I_F < 1.1I_{F(max)}$ .
3. Pulsed,  $t = 2ms$ . Continuous currents may vary.
4. Pulsed,  $t = 2ms$ . Continuous impedances may vary.
5. Min  $V_F$  required to ensure  $I_F = 0.8I_{F(min)}$ .

#### LSJ511 Availability:

SOT-23  
Bare die



Short Pins 2 & 3  
via PCB trace.



Please contact Micross for full package and die dimensions