



**NOTES:**

1. FOR USE WITH BOEING BMS13-65 OF & ADAMS RUSSELL FC14Z CABLES.
2. FOR CABLING INSTRUCTIONS SEE 3-546-1.
3. FOR CRIMPING USE DIE KTH-2161.
4. INTERFACE PER MIL-STD-348, FIG. 313-2.
5. MARK PACKAGE: KINGS 123-22-5 (DATE CODE)
6. CENTER CONTACT, 1-570-26MA9, TO BE SUPPLIED UNASSEMBLED.
7. MATERIALS:  
 INSULATOR: TEFLON, ASTM-D-1710  
 CENTER CONTACT: BER. COP., ASTM-B-196  
 K-GRIP SLEEVE: COM. BRONZE, ALLOY ASTM B135  
 ALL OTHER PARTS: BRASS, ASTM-B16
8. FINISHES:  
 CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM-B-488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)  
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-N290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:  
 NOMINAL IMPEDANCE: 50 OHMS  
 VOLTAGE RATING: 500 VRMS  
 FREQUENCY RANGE: DC TO 11 GHz
10. WEIGHT: 11.5 GRAMS

123-22-5

**REVISIONS**

ISSUE	CHANGES
0	ER 34692 JCA 06/10/93
1	CN 35536 A KVH 04/26/94
2	CN 37818 C TML 05/12/99
D	REVISED PER DMF304 & ER33954 CY 07/18/11

**CUSTOMER SALES DRAWING**

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE	4:1
APPROX SURFACE AREA	
CAGE CODE:	91836
REF:	BOEING
<b>JACK, TNC</b>	
DRAWN	JCA
DATE	02/03/93
DESIGN	MJB
DATE	02/03/93
APPR.	JT
DATE	06/16/93
<b>KINGS</b> by WINCHESTER ELECTRONICS	Winchester Electronics 82 Barnes Industrial Road North Wallingford, CT 06492
	<b>B</b> SIZE

123-22-5