


Features

- Schottky Barrier Chip
- Guard Ring Die Construction for Transient Protection
- Low Power Loss, High Efficiency
- High Surge Capability
- High Current Capability and Low Forward Voltage Drop
- For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Polarity Protection Application

Mechanical Data

- Case: Molded Plastic
- Plastic Material: UL Flammability Classification Rating 94V-0
- Moisture sensitivity: Level 1 per J-STD-020A
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Body
- Marking: Type Number
- Weight: 5.6 grams (approx.)



TO-3P		
Dim	Min	Max
A	1.88	2.08
B	4.68	5.36
C	20.63	22.38
D	18.5	21.5
E	2.1	2.4
G	0.51	0.76
H	15.38	16.25
J	1.90	2.70
K	2.9Ø	3.65Ø
L	3.78	4.50
M	5.2	5.7
N	0.89	1.53
P	1.82	2.46
Q	2.92	3.23
R	11.70	12.84
S	—	6.10

All Dimensions in mm

Maximum Ratings and Electrical Characteristics

@ $T_A = 25^\circ\text{C}$ unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	MBR 6030PT	MBR 6035PT	MBR 6040PT	MBR 6045PT	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	30	35	40	45	V
RMS Reverse Voltage	$V_{R(RMS)}$	21	25	28	32	V
Average Rectified Output Current @ $T_C = 125^\circ\text{C}$ (Note 1)	I_O			60		A
Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}			500		A
Forward Voltage Drop @ $I_F = 30\text{A}$, $T_C = 25^\circ\text{C}$ @ $I_F = 30\text{A}$, $T_C = 125^\circ\text{C}$ @ $I_F = 60\text{A}$, $T_C = 25^\circ\text{C}$	V_{FM}			0.62 0.55 0.75		V
Peak Reverse Current @ $T_C = 25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_C = 100^\circ\text{C}$	I_{RM}			1.0 50		mA
Typical Total Capacitance (Note 2)	C_T			650		pF
Typical Thermal Resistance Junction to Case (Note 1)	$R_{\theta JC}$			1.0		°C/W
Operating and Storage Temperature Range	T_j, T_{STG}			-55 to +150		°C

Notes: 1. Thermal resistance junction to case mounted on heatsink.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Max Non-Repetitive Surge Current




Fig. 4 Typical Total Capacitance per Element




Fig. 5 Typical Reverse Characteristics