



ACE3400

N-Channel Enhancement Mode MOSFET

Description

The ACE3400 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

Features

- 30V/5.4A, $R_{DS(ON)}=38m\Omega@V_{GS}=10V$
- 30V/4.6A, $R_{DS(ON)}=42m\Omega@V_{GS}=4.5V$
- 30V/3.8A, $R_{DS(ON)}=55m\Omega@V_{GS}=2.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability

Application

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

Absolute Maximum Ratings


Parameter	Symbol	Max	Unit
Drain-Source Voltage	V_{DSS}	30	V
Gate-Source Voltage	V_{GSS}	± 12	V
Continuous Drain Current ($T_J=150^{\circ}C$)	I_D	4.5	A
		3.5	
Pulsed Drain Current	I_{DM}	25	A
Continuous Source Current (Diode Conduction)	I_S	1.7	A
Power Dissipation	P_D	2.0	W
		1.3	
Operating Junction Temperature	T_J	150	$^{\circ}C$
Storage Temperature Range	T_{STG}	-55/150	$^{\circ}C$
Thermal Resistance-Junction to Ambient	$R_{\theta JA}$	90	$^{\circ}C/W$




ACE3400

N-Channel Enhancement Mode MOSFET

Packaging Type




SOT-23-3L	Description
1	Gate
2	Source
3	Drain



Ordering information

ACE3400 XX + H



Electrical Characteristics

$T_A=25^{\circ}\text{C}$, unless otherwise noted

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\text{ uA}$	30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_D=V_{GS}, I_D=250\text{uA}$	0.8		1.6	
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 12V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=24V, V_{GS}=1.0V$			1	uA
		$V_{DS}=24V, V_{GS}=0V, T_J=55^{\circ}\text{C}$			10	
On-State Drain Current	$I_{D(ON)}$	$V_{DS} \geq 4.5V, V_{GS}=4.5V$	10			A
Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=5.4A$		0.030	0.038	Ω
		$V_{GS}=4.5V, I_D=4.6A$		0.034	0.042	
		$V_{GS}=2.5V, I_D=3.8A$		0.040	0.055	
Forward Transconductance	G_{fs}	$V_{DS}=4.5V, I_D=5.4A$		12		S
Diode Forward Voltage	V_{SD}	$I_S=1.7A, V_{GS}=0V$		0.8	1.2	V
Dynamic						
Total Gate Charge	Q_g	$V_{DS}=15V, V_{GS}=10V, I_D=6.7A$		10	18	nC
Gate-Source Charge	Q_{gs}			1.6		
Gate-Drain Charge	Q_{gd}			3.2		
Input Capacitance	C_{iss}	$V_{DS}=15, V_{GS}=0V, f=1\text{MHz}$		450		pF
Output Capacitance	C_{oss}			240		




N-Channel Enhancement Mode MOSFET


Reverse Transfer Capacitance	Crss			38		
Turn-On Time	td(on)	V _{DD} =15V, R _L =15, I _D =1.0A, V _{GEN} =10V, R _G =6Ω		7	15	nS
	tr			10	20	
Turn-Off Time	td(off)			20	40	
	tf			11	20	

Typical Performance Characteristics


Output Characteristics




Transfer Characteristics



On-Resistance vs. Drain Current




Capacitance






Typical Performance Characteristics


Gate Charge




On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage






ACE3400

N-Channel Enhancement Mode MOSFET


Typical Performance Characteristics





Packing Information

SOT-23-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.400	0.012	0.016
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.700REF		0.028REF	
L1	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°



ACE3400

N-Channel Enhancement Mode MOSFET

Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Electronics Co., LTD. As sued herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ACE Technology Co., LTD.
<http://www.ace-ele.com/>