


HSB-440I

STPC® Atlas System-on-Chip

02

Half-size SBCs - ISA



Features

- Onboard STPC® Atlas System-on-Chip
- Onboard 64MB SDRAM
- 18-bit TTL TFT LCD
- 10/100 Base-TX Ethernet Port x 1 (Optional)
- PC/104 Slot
- COM Port x 4/ USB Port x 2/ Digital I/O
- Type II CompactFlash™ and DiskOnChip® Memory
- +5V Only Operation



Specifications

System	
Form Factor	ISA, Half-size SBC
Processor	Onboard STPC® Atlas 133MHz System-on-Chip
System Memory	Onboard 64MB SDRAM
Chipset	STPC® Atlas System-on-Chip
Ethernet	Realtek 8139DL/8100BL, 10/100Base-TX RJ-45 connector x 1
BIOS	AWARD 256KB FLASH ROM
IDE Interface	ATA-100/66/33
SSD	Type II CompactFlash™ slot x 1, DiskOnChip® up to 1GB
Expansion Interface	ISA interface, PC/104 socket x 1
Watchdog Timer	Generates a time-out system reset
RTC	Internal RTC
Battery	Lithium battery
Power Requirement	+5V/ AT
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Board Size	7.3"(L) x 4.8"(W) (185mm x 122mm)
Gross Weight	0.7 lb (0.3kg)
MTBF (Hours)	209,494
Power Consumption (Typical)	6W, Onboard STPC® Atlas System-on-Chip
Display	
VGA Controller	STPC® Atlas System-on-Chip
Memory	Shared system memory up to 4MB
Resolutions	Up to 1024x768@16bpp colors for CRT Up to 800x600@18bpp colors for LCD
LCD Interface	Up to 18-bit TTL TFT LCD
I/O	
Serial Port	Winbond W83977F COM port x 4: (Internal Pin Header, External D-sub x 2) COM 1, 3, 4: RS-232 COM 2: RS-232/422/485
Parallel Port	Supports SPP/ EPP/ ECP mode x 1
Universal Serial Bus	5x2-pin header x 1, supports USB 1.0 Port x 2
Floppy Drive Interface	Standard Floppy Disk Drive x 1
Keyboard and Mouse	Mini-DIN PS/2 K/B and Mouse connector x 1
IrDA	IrDA TX/Rx header x 1

Packing List

- 1701400601
IDE Cable
- 1701340700
Floppy Disk Drive Cable
- 170110030A
Serial Port Cable
- 1701010302
Parallel + Serial Port Cable
- 1700060192
Keyboard and Mouse Cable
- Quick Installation Guide
- Utility CD
- HSB-440I

Ordering Information

- TF-HSB-440I-A10
Half-size ISA CPU Card, STPC Atlas, with TFT LCD, Onboard 64MB, LAN, CF, DOC, 4 COM, Rev.A1.0
- TF-HSB-440I-A10-01
Half-size ISA CPU Card, STPC Atlas, with TFT LCD, Onboard 64MB, DOC, 4 COM, Rev.A1.0

Optional Accessories

- OS-CE-420-440I
Windows® CE.NET(Rev.4.2) SDK for HSB-440I, English Version
- CFC-032
32MB CompactFlash™ Card, 3.3/5V, suggested for Windows® CE.NET image

