High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#:

ATS-55310W-C1-R0

Description:

High Performance X-CUT - Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type: Cross-Cut Heat Sink Attachment: Equivalent Part Number: ATS-55310W-C2-R0

THERMAL TAPE

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Designed specifically for BGAs and other surface mount packages
- Comes pre-assembled with high performance thermal interface material ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.04 °C/W	3.13 °C/W	2.74 °C/W	2.48 °C/W	2.29 °C/W	2.15 °C/W	2.03 °C/W
	Ducted Flow	n/a						

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	31.0 mm	31.0 mm	24.5 mm	mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	 Dimension ATS-5531 (Saint Go Thermal p applicatio ATS resent performant ATS certition 	IOW-C2-R0 is the ex bain C675). performance data ar n. rves the right to upd nce. fies that this heat sir	height from the botto kact heat sink assen e provided for refere ate or change its pro	ence only. Actual pe oducts without notice S-6 and REACH cor	ent thermano	al interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA