BGA Heat Sink (High Aspect Ratio Ext.) **Slant Fin**





ATS Part#:

Description:

ATS031031022-MF-10U

31.00 x 31.00 x 22.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Slant Fin

Heat Sink Type: Slant Fin Heat Sink Attachment: N/A Equivalent Part Number: N/A

*Image above is for illustration purpose only.

Features & Benefits

- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	2.92 °C/W	2.2 °C/W	1.8 °C/W	1.6 °C/W	1.5 °C/W	1.4 °C/W	1.3 °C/W
	Ducted Flow	1.9	1.6	1.4	1.3	1.2	1.1	1.1

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
	31.00 mm	31.00 mm	22.00 mm	38.08 mm	N/A	BLACK-ANODIZED
	 Dimension Dimension Thermal p application ATS resent performant ATS certifier 	n D is fin tip to fin tip performance data are n. rves the right to upda nce.	e provided for refere ate or change its pro k assembly is RoHS	m of the base to the nce only. Actual perf ducts without notice i-6 and REACH com ble.	formanc to impr	e may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA