


P & N-Channel 30-V (D-S) MOSFET

These miniature surface mount MOSFETs utilize High Cell Density process. Low $r_{DS(on)}$ assures minimal power loss and conserves energy, making this device ideal for use in power management circuitry. Typical applications are PWMDC-DC converters, power management in portable and battery-powered products such as computers, printers, battery charger, telecommunication power system, and telephones power system.

- Low $r_{DS(on)}$ Provides Higher Efficiency and Extends Battery Life
- Miniature SO-8 Surface Mount Package Saves Board Space
- High power and current handling capability
- Low side high current DC-DC Converter applications

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ m(Ω)	I_D (A)
30	40 @ $V_{GS} = 4.5V$	6.0
	31 @ $V_{GS} = 10V$	6.9
-30	80 @ $V_{GS} = -4.5V$	-4.2
	52 @ $V_{GS} = -10V$	-5.2



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ UNLESS OTHERWISE NOTED)				
Parameter	Symbol	N-Channel	P-Channel	Units
Drain-Source Voltage	V_{DS}	30	-30	V
Gate-Source Voltage	V_{GS}	± 20	± 20	
Continuous Drain Current ^a	$T_A=25^\circ C$	I_D	6.9	A
	$T_A=70^\circ C$	I_D	5.4	
Pulsed Drain Current ^b	I_{DM}	20	-20	
Continuous Source Current (Diode Conduction) ^a	I_S	1.3	-1.3	A
Power Dissipation ^a	$T_A=25^\circ C$	P_D	2.1	W
	$T_A=70^\circ C$	P_D	1.3	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150		°C

THERMAL RESISTANCE RATINGS				
Parameter	Symbol	Maximum	Units	
Maximum Junction-to-Case ^a	$R_{\theta JC}$	40	°C/W	
Maximum Junction-to-Ambient ^a	$R_{\theta JA}$	60	°C/W	

Notes

- Surface Mounted on 1" x 1" FR4 Board.
- Pulse width limited by maximum junction temperature

SPECIFICATIONS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Limits				Unit
			Ch	Min	Typ	Max	
Static							
Gate-Threshold Voltage	$V_{GS(\text{th})}$	$V_{GS} = V_{DS}, I_D = 250 \mu\text{A}$	N	1			V
		$V_{GS} = V_{DS}, I_D = -250 \mu\text{A}$	P	-1.0			
Gate-Body Leakage	I_{GSS}	$V_{GS} = -20 \text{ V}, V_{DS} = 0 \text{ V}$	P			± 100	nA
		$V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$	N			± 100	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -24 \text{ V}, V_{GS} = 0 \text{ V}$	P			-1	uA
		$V_{DS} = 24 \text{ V}, V_{GS} = 0 \text{ V}$	N			1	
On-State Drain Current ^A	$I_{D(\text{on})}$	$V_{DS} = 5 \text{ V}, V_{GS} = 10 \text{ V}$	N	20			A
		$V_{DS} = -5 \text{ V}, V_{GS} = -10 \text{ V}$	P	-20			
Drain-Source On-Resistance ^A	$r_{DS(\text{on})}$	$V_{GS} = 10 \text{ V}, I_D = 6.9 \text{ A}$	N			31	mΩ
		$V_{GS} = 4.5 \text{ V}, I_D = 6 \text{ A}$				40	
		$V_{GS} = -10 \text{ V}, I_D = -5.2 \text{ A}$	P			52	
		$V_{GS} = -4.5 \text{ V}, I_D = -4.2 \text{ A}$				80	
Forward Transconductance ^A	g_{fs}	$V_{DS} = 15 \text{ V}, I_D = 6.9 \text{ A}$	N		25		S
		$V_{DS} = -15 \text{ V}, I_D = -5.2 \text{ A}$	P		10		
Dynamic							
Total Gate Charge	Q_g	N-Channel $V_{DS}=15\text{V}, V_{GS}=10\text{V}, I_D=6.9\text{A}$ P-Channel $V_{DS}=-15\text{V}, V_{GS}=-10\text{V}, I_D=-5.2\text{A}$	N		4.0		nC
Gate-Source Charge	Q_{gs}		P		10		
Gate-Drain Charge	Q_{gd}		N		1.1		
Turn-On Delay Time	$t_{d(\text{on})}$		P		2.2		
Rise Time	t_r		N		1.4		
Turn-Off Delay Time	$t_{d(\text{off})}$		P		1.7		
Fall-Time	t_f	N-Chanel $V_{DD}=15\text{V}, V_{GS}=10\text{V}, I_D=1\text{A}$, $R_{GEN}=6\Omega$, P-Channel $V_{DD}=-15\text{V}, V_{GS}=-10\text{V}, I_D=-1\text{A}$ $R_{GEN}=6\Omega$	N		8		nS
			P		10		
			N		5		
			P		2.8		
			N		23		
			P		53.6		
			N		3		
			P		46		

Notes

- a. Pulse test: PW <= 300us duty cycle <= 2%.
- b. Guaranteed by design, not subject to production testing.

FREESCALE reserves the right to make changes without further notice to any products herein. FREESCALE makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does freescal assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in freescal data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. freescal does not convey any license under its patent rights nor the rights of others. freescal products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the freescal product could create a situation where personal injury or death may occur. Should Buyer purchase or use freescal products for any such unintended or unauthorized application, Buyer shall indemnify and hold freescal and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that freescal was negligent regarding the design or manufacture of the part. freescal is an Equal Opportunity/Affirmative Action Employer.

Typical Electrical Characteristics (N-Channel)




Figure 1. On-Region Characteristics




Figure 2. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 3. On Resistance Vs Vgs Voltage




Figure 4. Capacitance Characteristics




Figure 5. Gate Charge Characteristics




Figure 6. On-Resistance Variation with Temperature

Typical Electrical Characteristics (N-Channel)




Figure 7. Transfer Characteristics




Figure 8. On-Resistance with Gate to Source Voltage




Figure 9. V_{th} Gate to Source Voltage Vs Temperature




Figure 10. Single Pulse Maximum Power Dissipation




Figure 11. Transient Thermal Response Curve

Typical Electrical Characteristics (P-Channel)




Figure 1. On-Region Characteristics




Figure 2. Body Diode Forward Voltage Variation with Source Current and Temperature




Figure 3. On Resistance Vs Vgs Voltage




Figure 4. Capacitance Characteristics




Figure 5. Gate Charge Characteristics




Figure 6. On-Resistance Variation with Temperature

Typical Electrical Characteristics (P-Channel)




Figure 7. Transfer Characteristics




Figure 8. On-Resistance with Gate to Source Voltage




Figure 9. V_{th} Gate to Source Voltage Vs Temperature




Figure 10. Single Pulse Maximum Power Dissipation

Normalized Thermal Transient Junction to Ambient







Figure 11. Transient Thermal Response Curve

Package Information

SO-8: 8LEAD



Dim	MILLIMETERS		INCHES	
	Min	Max	Min	Max
A	1.35	1.75	0.053	0.069
A ₁	0.10	0.20	0.004	0.008
B	0.35	0.51	0.014	0.020
C	0.19	0.25	0.0075	0.010
D	4.80	5.00	0.189	0.196
E	3.80	4.00	0.150	0.157
e	1.27 BSC		0.050 BSC	
H	5.80	6.20	0.228	0.244
h	0.25	0.50	0.010	0.020
L	0.50	0.93	0.020	0.037
q	0°	8°	0°	8°

Ordering information

- AM4512C-T1-XX
 - A: Analog Power
 - M: MOSFET
 - 4512: Part number
 - C: Complementary
 - T1: Tape & reel
 - XX:

Blank:	Standard
PF:	Leadfree