



75 Ohm Flexible RG6-CATV Coax Cable Triple Shielded with Black PVC (NC) Jacket

TECHNICAL DATA SHEET

RG6-CATV

75 Ohm Flexible RG6-CATV Coax Cable Triple Shielded with Black PVC (NC) Jacket

Configuration

Inner Conductor Material and Plating

Dielectric Type

Copper
PE (F)

Shield Materials Aluminum Foil, Aluminum Braid

Jacket Material and Color PVC (NC), Black

Electrical Specifications

Impedance, Ohms 75
Velocity of Propagation, % 85
Maximum Operating Frequency, GHz 3
RF Shielding, dB 70

Capacitance, pF/ft [pF/m] 16.2 [53.15]

Electrical Specifications by Frequency

Frequency 1

Frequency, MHz 5
Attenuation, dB/100ft [dB/100m] 0.5

Attenuation, dB/100ft [dB/100m] 0.58 [1.9]

Frequency 2

Frequency, MHz 250 Attenuation, dB/100ft [dB/100m] 3.3 [10.83

Frequency 3

Frequency, MHz 550 Attenuation, dB/100ft [dB/100m] 4.9 [16.08]

Frequency 4

Frequency, MHz 1000

Attenuation, dB/100ft [dB/100m] 6.55 [21.49]

Frequency 5

Frequency, GHz 1.45 Attenuation, dB/100ft [dB/100m] 7.9 [25.92]

Frequency 6

Frequency, GHz 1.75

Attenuation, dB/100ft [dB/100m] 8.75 [28.71]

Frequency 7

Frequency, GHz 2.15

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm Flexible RG6-CATV Coax Cable Triple Shielded with Black PVC (NC) Jacket RG6-CATV

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



RG6-CATV CAD Drawing

75 Ohm Flexible RG6-CATV Coax Cable Triple Shielded with Black PVC (NC) Jacket

