



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- 1. BRASS PER QQ-B-626
 - 2. BRASS PER QQ-B-613
 - 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - 4. BERYLLIUM COPPER PER QQ-C-530
 - 5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - 6. TEFLON MIL-P-19468

1. MAX. PANEL THICKNESS=8mm

						DIMENSIONS ARE IN MILLIMETERS				PART NO. SMA6351B1-003-3GT50G-50		<h1 style="text-align: center;">Amphenol</h1> <p style="text-align: center;">TITLE SMA BULKHEAD RECEPT. JACK- FRONT MOUNT BLUNT POST TERMINAL</p> <p style="text-align: center;">DRAWING NO. KJ-SMA6351B1-003-3GT50G-50</p> <p style="text-align: center;">ITEM NO.</p>			
						UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED				DATE	
										CHECKED				DATE	
										DRAWN				DATE	
NO	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	5/1	ISSUE	A	FILE NO.					
6	HEX NUT	NOTE 1	NOTE 3	1	HN8-1/4-36X16						10-11-01'				
5	LOCK WASHER	NOTE 2	NOTE 3	1	LW-102/65X05						10-11-01'				
4	INSULATOR	NOTE 6	NATURAL	1	SMA7301-4T-50						10-11-01'				
3	CONTACT PIN	NOTE 4	NOTE 5	1	SMA6351B1-003-3						10-11-01'				
2	INSULATOR	NOTE 6	NATURAL	1	SMA6351B1-003-2						10-11-01'				
1	BODY	NOTE 1	NOTE 3	1	SMA6351B1-003-1						10-11-01'				