



1K x 8 Dual-Port
Static RAM

2
SRAMS

Features

- 0.8-micron CMOS for optimum speed/power
- Automatic power-down
- TTL compatible
- Capable of withstanding greater than 2001V electrostatic discharge
- Fully asynchronous operation
- Master CY7C130/CY7C131 easily expands data bus width to 16 or more bits using SLAVE CY7C140/CY7C141
- **BUSY** output flag on CY7C130/CY7C131; **BUSY** input on CY7C140/CY7C141
- **INT** flag for port-to-port communication


Functional Description

The CY7C130/CY7C131/CY7C140/CY7C141 are high-speed CMOS 1K by 8 dual-port static RAMs. Two ports are provided permitting independent access to any location in memory. The CY7C130/CY7C131 can be utilized as either a standalone 8-bit dual-port static RAM or as a master dual-port RAM in conjunction with the CY7C140/CY7C141 slave dual-port device in systems requiring 16-bit or greater word widths. It is the solution to applications requiring shared or buffered data, such as cache memory for DSP, bit-slice, or multiprocessor designs.


Each port has independent control pins; chip enable (**CE**), write enable (**R/W**), and output enable (**OE**). Two flags are provided on each port, **BUSY** and **INT**. **BUSY** signals that the port is trying to access the same location currently being accessed by the other port. **INT** is an interrupt flag indicating that data has been placed in a unique location (3FF for the left port and 3FE for the right port). An automatic power-down feature is controlled independently on each port by the chip enable (**CE**) pins.

The CY7C130 and CY7C140 are available in both 48-pin DIP and 48-pin LCC. The CY7C131 and CY7C141 are available in both 52-pin LCC and PLCC.

Logic Block Diagram



Pin Configurations



C130-1


C130-2

Notes:

1. CY7C130/CY7C131 (Master): **BUSY** is open drain output and requires pull-up resistor. CY7C140/CY7C141 (Slave): **BUSY** is input.
2. Open drain outputs: pull-up resistor required.


Pin Configurations (continued)

52-Pin LCC/PLCC
Top View



C130-3

48-Pin LCC/QFP
Top View



C130-4

Selection Guide

		7C130-25 ^[3] 7C131-25 7C140-25 7C141-25	7C130-30 7C131-30 7C140-30 7C141-30	7C130-35 7C131-35 7C140-35 7C141-35	7C130-45 7C131-45 7C140-45 7C141-45	7C130-55 7C131-55 7C140-55 7C141-55
Maximum Access Time (ns)		25	30	35	45	55
Maximum Operating Current (mA)	Com'l/Ind	170	170	120	90	90
	Military			170	120	120
Maximum Standby Current (mA)	Com'l/Ind	65	65	45	35	35
	Military			65	45	45

Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature - 65°C to +150 °C

Ambient Temperature with

Power Applied - 55°C to +125°C

Supply Voltage to Ground Potential
(Pin 48 to Pin 24) - 0.5V to +7.0V

DC Voltage Applied to Outputs
in High Z State - 0.5V to +7.0V

DC Input Voltage - 3.5V to +7.0V

Output Current into Outputs (LOW) 20 mA

Static Discharge Voltage >2001V
(per MIL-STD-883, Method 3015)

Latch-Up Current >200 mA

Operating Range

Range	Ambient Temperature	V _{CC}
Commercial	0°C to +70°C	5V ± 10%
Industrial	- 40°C to +85°C	5V ± 10%
Military ^[4]	- 55°C to +125°C	5V ± 10%

Notes:

3. 25-ns version available only in PLCC/LCC packages.

4. T_A is the "instant on" case temperature

Electrical Characteristics Over the Operating Range^[5]

Parameter	Description	Test Conditions	7C130-25, 30 ^[3] 7C131-25,30 7C140-25,30 7C141-25,30		7C130-35 7C131-35 7C140-35 7C141-35		7C130-45,55 7C131-45,55 7C140-45,55 7C141-45,55		Unit
			Min.	Max.	Min.	Max.	Min.	Max.	
V _{OH}	Output HIGH Voltage	V _{CC} = Min., I _{OH} = - 4.0 mA	2.4		2.4		2.4		V
V _{OL}	Output LOW Voltage	I _{OL} = 4.0 mA		0.4		0.4		0.4	V
		I _{OL} = 16.0 mA ^[6]		0.5		0.5		0.5	
V _{IH}	Input HIGH Voltage		2.2		2.2		2.2		V
V _{IL}	Input LOW Voltage			0.8		0.8		0.8	V
I _{Ix}	Input Leakage Current	GND ≤ V _I ≤ V _{CC}	- 5	+ 5	- 5	+ 5	- 5	+ 5	μA
I _{OZ}	Output Leakage Current	GND ≤ V _O ≤ V _{CC} , Output Disabled	- 5	+ 5	- 5	+ 5	- 5	+ 5	μA
I _{OS}	Output Short Circuit Current ^[7, 8]	V _{CC} = Max., V _{OUT} = GND		- 350		- 350		- 350	mA
I _{CC}	V _{CC} Operating Supply Current	V _{CE} = V _{IL} , Outputs Open, f = f _{MAX} ^[9]	Com'l	170		120		90	mA
			Mil			170		120	
I _{SB1}	Standby Current Both Ports, TTL Inputs	V _{CEL} and V _{CEr} ≥ V _{IH} , f = f _{MAX} ^[9]	Com'l	65		45		35	mA
			Mil			65		45	
I _{SB2}	Standby Current One Port, TTL Inputs	V _{CEL} or V _{CEr} ≥ V _{IH} , Active Port Outputs Open, f = f _{MAX} ^[9]	Com'l	115		90		75	mA
			Mil			115		90	
I _{SB3}	Standby Current Both Ports, CMOS Inputs	Both Ports V _{CEL} and V _{CEr} ≥ V _{CC} - 0.2V, V _{IN} ≥ V _{CC} - 0.2V or V _{IN} ≤ 0.2V, f = 0	Com'l	15		15		15	mA
			Mil			15		15	
I _{SB4}	Standby Current One Port, CMOS Inputs	One Port V _{CEL} or V _{CEr} ≥ V _{CC} - 0.2V, V _{IN} ≥ V _{CC} - 0.2V or V _{IN} ≤ 0.2V, Active Port Outputs Open, f = f _{MAX} ^[9]	Com'l	105		85		70	mA
			Mil			105		85	




Capacitance^[8]

Parameter	Description	Test Conditions	Max.	Unit
C _{IN}	Input Capacitance	T _A = 25°C, f = 1 MHz, V _{CC} = 5.0V	15	pF
C _{OUT}	Output Capacitance		10	pF

Notes:


- See the last page of this specification for Group A subgroup testing information.
- BUSY and INT pins only.
- Duration of the short circuit should not exceed 30 seconds.
- Tested initially and after any design or process changes that may affect these parameters.
- At f = f_{MAX}, address and data inputs are cycling at the maximum frequency of read cycle of 1/t_{RC} and using AC Test Waveforms input levels of GND to 3V.
- AC Test conditions use V_{OH} = 1.6V and V_{OL} = 1.4V.
- Test conditions assume signal transition times of 5 ns or less, timing reference levels of 1.5V, input pulse levels of 0 to 3.0V and output loading of the specified I_{OL}/I_{OH}, and 30-pF load capacitance.
- AC Test Conditions use V_{OH} = 1.6V and V_{OL} = 1.4V.
- At any given temperature and voltage condition for any given device, t_{HZCE} is less than t_{LZCE} and t_{HZOE} is less than t_{LZOE}.
- t_{LZCE}, t_{LZWE}, t_{HZOE}, t_{LZOE}, t_{HZCE} and t_{HZWE} are tested with C_L = 5pF as in part (b) of AC Test Loads. Transition is measured ±500 mV from steady state voltage.
- The internal write time of the memory is defined by the overlap of \overline{CS} LOW and R/W LOW. Both signals must be low to initiate a write and either signal can terminate a write by going high. The data input set-up and hold timing should be referred to the rising edge of the signal that terminates the write.

AC Test Loads and Waveforms



BUSY Output Load
(CY7C130/CY7C131 ONLY)

Equivalent to: THEVENIN EQUIVALENT
OUTPUT — 250Ω — 1.40V



C130-6

Switching Characteristics Over the Operating Range^[5,11]

Parameter	Description	7C130-25 ^[3] 7C131-25 7C140-25 7C141-25		7C130-30 7C131-30 7C140-30 7C141-30		7C130-35 7C131-35 7C140-35 7C141-35		7C130-45 7C131-45 7C140-45 7C141-45		7C130-55 7C131-55 7C140-55 7C141-55		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
READ CYCLE												
t _{RC}	Read Cycle Time	25		30		35		45		55		ns
t _{AA}	Address to Data Valid ^[12]		25		30		35		45		55	ns
t _{OHA}	Data Hold from Address Change	0		0		0		0		0		ns
t _{ACE}	\overline{CE} LOW to Data Valid ^[12]		25		30		35		45		55	ns
t _{DOE}	\overline{OE} LOW to Data Valid ^[12]		15		20		20		25		25	ns
t _{LZOE}	\overline{OE} LOW to Low Z ^[13]	3		3		3		3		3		ns
t _{HZOE}	\overline{OE} HIGH to High Z ^[13, 14]		15		15		20		20		25	ns
t _{LZCE}	\overline{CE} LOW to Low Z ^[13, 14]	5		5		5		5		5		ns
t _{HZCE}	\overline{CE} HIGH to High Z ^[13, 14]		15		15		20		20		25	ns
t _{PU}	\overline{CE} LOW to Power-Up	0		0		0		0		0		ns
t _{PD}	\overline{CE} HIGH to Power-Down		25		25		35		35		35	ns
WRITE CYCLE^[15]												
t _{WC}	Write Cycle Time	25		30		35		45		55		ns
t _{SCE}	\overline{CE} LOW to Write End	20		25		30		35		40		ns
t _{AW}	Address Set-Up to Write End	20		25		30		35		40		ns
t _{HA}	Address Hold from Write End	2		2		2		2		2		ns
t _{SA}	Address Set-Up to Write Start	0		0		0		0		0		ns
t _{PWE}	R/ \overline{W} Pulse Width	15		25		25		30		30		ns
t _{SD}	Data Set-Up to Write End	15		15		15		20		20		ns
t _{HD}	Data Hold from Write End	0		0		0		0		0		ns
t _{HZWE}	R/ \overline{W} LOW to High Z		15		15		20		20		25	ns
t _{LZWE}	R/ \overline{W} HIGH to Low Z	0		0		0		0		0		ns

Switching Characteristics Over the Operating Range^[5,11] (continued)


Parameter	Description	7C130-25 ^[3]		7C130-30		7C130-35		7C130-45		7C130-55		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
BUSY/INTERRUPT TIMING												
t _{BLA}	BUSY LOW from Address Match		20		20		20		25		30	ns
t _{BHA}	BUSY HIGH from Address Mismatch ^[16]		20		20		20		25		30	ns
t _{BLC}	BUSY LOW from \overline{CE} LOW		20		20		20		25		30	ns
t _{BHC}	BUSY HIGH from \overline{CE} HIGH ^[16]		20		20		20		25		30	ns
t _{PS}	Port Set Up for Priority	5		5		5		5		5		ns
t _{WB} ^[17]	R/W LOW after BUSY LOW	0		0		0		0		0		ns
t _{WH}	R/W HIGH after BUSY HIGH	20		30		30		35		35		ns
t _{BDD}	BUSY HIGH to Valid Data		25		30		35		45		45	ns
t _{DDD}	Write Data Valid to Read Data Valid		Note 18		Note 18		Note 18		Note 18		Note 18	ns
t _{WDD}	Write Pulse to Data Delay		Note 18		Note 18		Note 18		Note 18		Note 18	ns
INTERRUPT TIMING												
t _{WINS}	R/W to INTERRUPT Set Time		25		25		25		35		45	ns
t _{EINS}	\overline{CE} to INTERRUPT Set Time		25		25		25		35		45	ns
t _{INS}	Address to INTERRUPT Set Time		25		25		25		35		45	ns
t _{OINR}	\overline{OE} to INTERRUPT Reset Time ^[16]		25		25		25		35		45	ns
t _{EINR}	\overline{CE} to INTERRUPT Reset Time ^[16]		25		25		25		35		45	ns
t _{INR}	Address to INTERRUPT Reset Time ^[16]		25		25		25		35		45	ns

Notes:

16. These parameters are measured from the input signal changing, until the output pin goes to a high-impedance state.
17. CY7C140/CY7C141 only.
18. A write operation on Port A, where Port A has priority, leaves the data on Port B's outputs undisturbed until one access time after one of the following:
 - A. BUSY on Port B goes HIGH.
 - B. Port B's address is toggled.
 - C. \overline{CE} for Port B is toggled.
 - D. R/W for Port B is toggled during valid read.
19. R/W is HIGH for read cycle.
20. Device is continuously selected, $\overline{CE} = V_{IL}$ and $\overline{OE} = V_{IL}$.
21. Address valid prior to or coincident with \overline{CE} transition LOW.
22. If \overline{OE} is LOW during a R/W controlled write cycle, the write pulse width must be the larger of t_{PWE} or $t_{HZWE} + t_{SD}$ to allow the data I/O pins to enter high impedance and for data to be placed on the bus for the required t_{SD} .
23. If the \overline{CE} LOW transition occurs simultaneously with or after the R/W LOW transition, the outputs remain in the high-impedance state.


Switching Waveforms

Read Cycle No. 1^[19, 20]




Switching Waveforms (continued)


Read Cycle No. 2^[19,21]



Read Cycle No. 3^[20]




Write Cycle No.1 (\overline{OE} Tri-States Data I/Os – Either Port)^[15,22]



Switching Waveforms (continued)


Write Cycle No. 2 (R/W Tri-States Data I/Os – Either Port)^[15,23]



C130-11


Busy Timing Diagram No. 1 (\overline{CE} Arbitration)

\overline{CE}_L Valid First:



C130-12

\overline{CE}_R Valid First:




C130-13

Switching Waveforms (continued)


Busy Timing Diagram No. 2 (Address Arbitration)

Left Address Valid First:



C130-14


Right Address Valid First:



C130-15

Busy Timing Diagram No. 3

Write with $\overline{\text{BUSY}}$ (Slave: CY7C140/CY7C141)




C130-16

Switching Waveforms (continued)


Interrupt Timing Diagrams

Left Side Sets \overline{INT}_R




C130-17

Right Side Clears \overline{INT}_R




C130-18

Right Side Sets \overline{INT}_L












C130-19

Left Side Clears \overline{INT}_L



C130-20

Typical DC and AC Characteristics



Ordering Information

Speed (ns)	Ordering Code	Package Name	Package Type	Operating Range
30	CY7C130-30PC	P25	48-Lead (600-Mil) Molded DIP	Commercial
	CY7C130-30PI	P25	48-Lead (600-Mil) Molded DIP	Industrial
35	CY7C130-35PC	P25	48-Lead (600-Mil) Molded DIP	Industrial
	CY7C130-35PI	P25	48-Lead (600-Mil) Molded DIP	
	CY7C130-35DMB	D26	48-Lead (600-Mil) Sidebrazed DIP	Military
	CY7C130-35FMB	F78	48-Lead Quad Flatpack	
	CY7C130-35LMB	L68	48-Square Leadless Chip Carrier	
45	CY7C130-45PC	P25	48-Lead (600-Mil) Molded DIP	Industrial
	CY7C130-45PI	P25	48-Lead (600-Mil) Molded DIP	
	CY7C130-45DMB	D26	48-Lead (600-Mil) Sidebrazed DIP	Military
	CY7C130-45FMB	F78	48-Lead Quad Flatpack	
	CY7C130-45LMB	L68	48-Square Leadless Chip Carrier	
55	CY7C130-55PC	P25	48-Lead (600-Mil) Molded DIP	Industrial
	CY7C130-55PI	P25	48-Lead (600-Mil) Molded DIP	
	CY7C130-55DMB	D26	48-Lead (600-Mil) Sidebrazed DIP	Military
	CY7C130-55FMB	F78	48-Lead Quad Flatpack	
	CY7C130-55LMB	L68	48-Square Leadless Chip Carrier	

Speed (ns)	Ordering Code	Package Name	Package Type	Operating Range
25	CY7C131-25JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
30	CY7C131-30JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C131-30JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
35	CY7C131-35JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C131-35JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
	CY7C131-35FMB	F78	48-Lead Quad Flatpack	Military
	CY7C131-35LMB	L69	52-Square Leadless Chip Carrier	
45	CY7C131-45JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C131-45JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
	CY7C131-45FMB	F78	48-Lead Quad Flatpack	Military
	CY7C131-45LMB	L69	52-Square Leadless Chip Carrier	
55	CY7C131-55JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C131-55JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
	CY7C131-55FMB	F78	48-Lead Quad Flatpack	Military
	CY7C131-55MB	L69	52-Square Leadless Chip Carrier	

Ordering Information (continued)

Speed (ns)	Ordering Code	Package Name	Package Type	Operating Range
30	CY7C140-30PC	P25	48-Lead (600-Mil) Molded DIP	Commercial
	CY7C140-30PI	P25	48-Lead (600-Mil) Molded DIP	Industrial
35	CY7C140-35PC	P25	48-Lead (600-Mil) Molded DIP	Commercial
	CY7C140-35PI	P25	48-Lead (600-Mil) Molded DIP	Industrial
	CY7C140-35DMB	D26	48-Lead (600-Mil) Sidebraze DIP	Military
	CY7C140-35FMB	F78	48-Lead Quad Flatpack	
	CY7C140-35LMB	L68	48-Square Leadless Chip Carrier	
45	CY7C140-45PC	P25	48-Lead (600-Mil) Molded DIP	Commercial
	CY7C140-45PI	P25	48-Lead (600-Mil) Molded DIP	Industrial
	CY7C140-45DMB	D26	48-Lead (600-Mil) Sidebraze DIP	Military
	CY7C140-45FMB	F78	48-Lead Quad Flatpack	
	CY7C140-45LMB	L68	48-Square Leadless Chip Carrier	
55	CY7C140-55PC	P25	48-Lead (600-Mil) Molded DIP	Commercial
	CY7C140-55PI	P25	48-Lead (600-Mil) Molded DIP	Industrial
	CY7C140-55DMB	D26	48-Lead (600-Mil) Sidebraze DIP	Military
	CY7C140-55FMB	F78	48-Lead Quad Flatpack	
	CY7C140-55LMB	L68	48-Square Leadless Chip Carrier	

Speed (ns)	Ordering Code	Package Name	Package Type	Operating Range
25	CY7C141-25JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
30	CY7C141-30JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C141-30JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
35	CY7C141-35JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C141-35JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
	CY7C141-35FMB	F78	48-Lead Quad Flatpack	Military
	CY7C141-35LMB	L69	52-Square Leadless Chip Carrier	
45	CY7C141-45JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C141-45JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
	CY7C141-45FMB	F78	48-Lead Quad Flatpack	Military
	CY7C141-45LMB	L69	52-Square Leadless Chip Carrier	
55	CY7C141-55JC	J69	52-Lead Plastic Leaded Chip Carrier	Commercial
	CY7C141-55JI	J69	52-Lead Plastic Leaded Chip Carrier	Industrial
	CY7C141-55FMB	F78	48-Lead Quad Flatpack	Military
	CY7C141-55LMB	L69	52-Square Leadless Chip Carrier	

MILITARY SPECIFICATIONS

Group A Subgroup Testing

DC Characteristics

Parameter	Subgroups
V _{OH}	1, 2, 3
V _{OL}	1, 2, 3
V _{IH}	1, 2, 3
V _{IL Max.}	1, 2, 3
I _{IX}	1, 2, 3
I _{OZ}	1, 2, 3
I _{CC}	1, 2, 3
I _{SB1}	1, 2, 3
I _{SB2}	1, 2, 3
I _{SB3}	1, 2, 3
I _{SB4}	1, 2, 3

Switching Characteristics

Parameter	Subgroups
READ CYCLE	
t _{RC}	7, 8, 9, 10, 11
t _{AA}	7, 8, 9, 10, 11
t _{ACE}	7, 8, 9, 10, 11
t _{DOE}	7, 8, 9, 10, 11
WRITE CYCLE	
t _{WC}	7, 8, 9, 10, 11
t _{SCE}	7, 8, 9, 10, 11
t _{AW}	7, 8, 9, 10, 11
t _{HA}	7, 8, 9, 10, 11
t _{SA}	7, 8, 9, 10, 11
t _{PWE}	7, 8, 9, 10, 11
t _{SD}	7, 8, 9, 10, 11
t _{HD}	7, 8, 9, 10, 11

Parameter	Subgroups
BUSY/INTERRUPT TIMING	
t _{BLA}	7, 8, 9, 10, 11
t _{BHA}	7, 8, 9, 10, 11
t _{BLC}	7, 8, 9, 10, 11
t _{BHC}	7, 8, 9, 10, 11
t _{PS}	7, 8, 9, 10, 11
t _{WINS}	7, 8, 9, 10, 11
t _{EINS}	7, 8, 9, 10, 11
t _{INS}	7, 8, 9, 10, 11
t _{OINR}	7, 8, 9, 10, 11
t _{EINR}	7, 8, 9, 10, 11
t _{INR}	7, 8, 9, 10, 11
BUSY TIMING	
t _{WB} ^[24]	7, 8, 9, 10, 11
t _{WH}	7, 8, 9, 10, 11
t _{BDD}	7, 8, 9, 10, 11

Note:

24. CY7C140/CY7C141 only.

Document #: 38-00027-I