



PT07 CE SP07 CE


jam nut receptacle




TERMINATION ASSEMBLIES
"CE" (SR) Strain Relief



PT07CE-XX-XXX
SP07CE-XX-XXX



PT07CE-XX-XXX (SR)
SP07CE-XX-XXX (SR)



PT07CP-XX-XX
SP07CP-XX-XXX

All lock wire holes are .044 Dia. Min.

Shell Size	Receptacle Front View				Receptacle Side View											
	H Hex. +.017 -.016	S ±.016	A Dia. +.001 -.005	J Flat +.000 -.010	Panel Thickness				Class "CE"		Class "CE" (SR)			Class "CP"		
				K ±.016	M ±.005	Min.	Max.	L Max.	N Max.	G Dia.	L Max.	N Max.	L Max.	N Max.	D Dia.	D Dia.
8	.750	.938	.473	.530	.125	.696	.062	.125	.827	.730	.125	1.297	.797	.875	.608	.327
10	.875	1.062	.590	.655	.125	.696	.062	.125	.827	.855	.188	1.297	.859	.875	.734	.444
12	1.062	1.250	.750	.818	.125	.696	.062	.125	.827	.980	.312	1.297	.984	.875	.858	.558
14	1.188	1.375	.875	.942	.125	.696	.062	.125	.827	1.105	.375	1.297	1.109	.875	.984	.683
16	1.312	1.500	1.000	1.066	.125	.696	.062	.125	.827	1.230	.500	1.422	1.172	.875	1.110	.808
18	1.438	1.625	1.125	1.191	.125	.696	.062	.125	.827	1.355	.625	1.422	1.422	.875	1.234	.909
20	1.562	1.812	1.250	1.316	.156	.884	.062	.250	.733	1.511	.625	1.328	1.422	.969	1.360	1.034
22	1.688	1.938	1.375	1.441	.156	.884	.062	.250	.733	1.636	.750	1.328	1.609	.969	1.484	1.159
24	1.812	2.062	1.500	1.566	.156	.917	.062	.250	.762	1.761	.800	1.422	1.703	.969	1.610	1.284

All dimensions for reference only.