

[Home](#) > [Products](#) > [By Type](#) > [Relays](#) > [Product Feature Selector](#) > Product Details

CDD-38-30003 Product Details



CDD-38-30003
(6-1393136-0)

TE Internal Number: 6-1393136-0

 [Active](#)

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- CD Series
- Input Voltage = 24 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 30 VDC or 277 VAC
- Mounting Options = Socket

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [CD CMOS IC Time Delay Relay](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Schematic](#)
- [Wiring Diagram](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Termination Type = 8-Pin Octal Style Plug

Electrical Characteristics:

- Input Voltage (VDC) = 24
- Contact Rating = 10A @ 30 VDC or 277 VAC

Body Related Features:

- [Series](#) = CD

Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = Delay on Operate
- Delay Time = 0.1 seconds to 10 seconds
- Type of Control = Knob
- Repeatability, Max. = ± 1%
- Approved Standards = CSA Certified, UL Recognized
- Contact Base Material = Silver Cadmium Oxide
- Approx. Dimensions (L x W x H) (mm [in]) = 61.10 x 45.20 x 74.60 [2.407 x 1.780 x 2.939]
- Enclosure = Yellow Plastic Case

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process

Conditions for Usage:

- Temperature Range (?C) = -40 – +55

Other:

- Brand = Potter & Brumfield

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)