

Standard Cable Assemblies

- BNC Test Patch Cord Assemblies
- Standard RG 58C/U Cable
- Fast Delivery
- BNC, N, TNC, and SMA Connectors

Midwest Microwave offers these standard cable assemblies for use in the laboratory or the microwave system. These low cost, quick delivery assemblies provide a simple approach to meeting the immediate need for standard cable assemblies. Normally standard MIL-C-17 RG58C/U cable is used with standard off the shelf connectors however other types of cable can be designated by using a selected Midwest cable type No. in the Model No.



BNC Male to BNC Male		
XX = Select Cable Type		
Model No.	Length	
CSY-BMBM-XX-012-IS	12"	
CSY-BMBM-XX-024-IS	24"	
CSY-BMBM-XX-036-IS	36"	
CSY-BMBM-XX-048-IS	48"	
CSY-BMBM-XX-060-IS	60"	
CSY-BMBM-XX-072-IS	72"	
CSY-BMBM-XX-084-IS	84"	
CSY-BMBM-XX-096-IS	96"	

BNC Male to SMA Male		
XX = Select Cable Type		
Model No.	Length	
CSY-BMSM-XX-012-IS	12"	
CSY-BMSM-XX-024-IS	24"	
CSY-BMSM-XX-036-IS	36"	
CSY-BMSM-XX-048-IS	48"	
CSY-BMSM-XX-060-IS	60"	
CSY-BMSM-XX-072-IS	72"	
CSY-BMSM-XX-084-IS	84"	
CSY-BMSM-XX-096-IS	96"	

SMA Male to SMA Male		
XX = Select Cable Type		
Model No.	Length	
CSY-SMSM-XX-012-IS	12"	
CSY-SMSM-XX-024-IS	24"	
CSY-SMSM-XX-036-IS	36"	
CSY-SMSM-XX-048-IS	48"	
CSY-SMSM-XX-060-IS	60"	
CSY-SMSM-XX-072-IS	72"	
CSY-SMSM-XX-084-IS	84"	
CSY-SMSM-XX-096-IS	96"	

BNC Male to BNC Bkhd Female		
XX = Select Cable Type		
Model No.	Length	
CSY-BMBB-XX-012-IS	12"	
CSY-BMBB-XX-024-IS	24"	
CSY-BMBB-XX-036-IS	36"	
CSY-BMBB-XX-048-IS	48"	
CSY-BMBB-XX-060-IS	60"	
CSY-BMBB-XX-072-IS	72"	
CSY-BMBB-XX-084-IS	84"	
CSY-BMBB-XX-096-IS	96"	

N Male to N Male		
XX = Select Cable Type		
Model No.	Length	
CSY-NMNM-XX-012-IS	12"	
CSY-NMNM-XX-024-IS	24"	
CSY-NMNM-XX-036-IS	36"	
CSY-NMNM-XX-048-IS	48"	
CSY-NMNM-XX-060-IS	60"	
CSY-NMNM-XX-072-IS	72"	
CSY-NMNM-XX-084-IS	84"	
CSY-NMNM-XX-096-IS	96"	

N Male to N Bkhd Female		
XX = Select Cable Type		
Model No.	Length	
CSY-NMNB-XX-012-IS	12"	
CSY-NMNB-XX-024-IS	24"	
CSY-NMNB-XX-036-IS	36"	
CSY-NMNB-XX-048-IS	48"	
CSY-NMNB-XX-060-IS	60"	
CSY-NMNB-XX-072-IS	72"	
CSY-NMNB-XX-084-IS	84"	
CSY-NMNB-XX-096-IS	96"	

BNC Male to N Male		
XX = Select Cable Type		
Model No.	Length	
CSY-BMNM-XX-012-IS	12"	
CSY-BMNM-XX-024-IS	24"	
CSY-BMNM-XX-036-IS	36"	
CSY-BMNM-XX-048-IS	48"	
CSY-BMNM-XX-060-IS	60"	
CSY-BMNM-XX-072-IS	72"	
CSY-BMNM-XX-084-IS	84"	
CSY-BMNM-XX-096-IS	96"	

N Male to SMA Male		
XX = Select Cable Type		
Model No.	Length	
CSY-NMSM-XX-012-IS	12"	
CSY-NMSM-XX-024-IS	24"	
CSY-NMSM-XX-036-IS	36"	
CSY-NMSM-XX-048-IS	48"	
CSY-NMSM-XX-060-IS	60"	
CSY-NMSM-XX-072-IS	72"	
CSY-NMSM-XX-084-IS	84"	
CSY-NMSM-XX-096-IS	96"	

TNC Male to TNC BkhdFemale		
XX = Select Cable Type		
Model No.	Length	
CSY-TMTB-XX-012-IS	12"	
CSY-TMTB-XX-024-IS	24"	
CSY-TMTB-XX-036-IS	36"	
CSY-TMTB-XX-048-IS	48"	
CSY-TMTB-XX-060-IS	60"	
CSY-TMTB-XX-072-IS	72"	
CSY-TMTB-XX-084-IS	84"	
CSY-TMTB-XX-096-IS	96"	

Notes: 1. "XX" = "58" for RG58/U. To designate a desired cable type, select a Midwest Cable Type No. and substitute for "XX" in the Model No.
2. If a connector combination other than those shown is required, refer to page 178 and 179 and modify the Model No. as required.