

Material: Copper




Wire Range AWG (mm <sup>2</sup> )	Stud Size S	Maximum Width W	Minimum Clearance C	Krimptite®		Insulkrimp® (PVC Insulation)		Versakrimp™		Avikrimp® (Nylon Insulation)	
				Order No.	Maximum Length L	Order No.	Maximum Length L	Order No.	Maximum Length L	Order No.	Maximum Length L
10-12 (5.00-3.30)	3-4 (2.6)	9.80 (.385)	7.70 (.303)		19.90 (.785)		27.30 (1.076)		19.80 (.785)		27.70 (1.091)
	5-6 (3-3.5)	7.40 (.292)	7.80 (.306)	C-136-06	18.80 (.741)	C-236-06X	26.20 (1.032)	C-336-06	18.80 (.741)	C-836-06*	27.00 (1.047)
		9.80 (.385)	7.70 (.303)	C-128-06	19.90 (.785)	C-228-06X	27.30 (1.076)	C-328-06	19.90 (.785)	C-828-06*	27.70 (1.091)
	8 (4)	7.40 (.292)	7.80 (.306)	C-136-08	18.80 (.741)	C-236-08X	26.20 (1.032)	C-336-08	18.80 (.741)	C-836-08*	27.00 (1.047)
		9.80 (.385)	7.70 (.303)	C-128-08	19.90 (.785)	C-228-08X	27.30 (1.076)	C-328-08	19.90 (.785)	C-828-08*	27.70 (1.091)
	10 (-)	9.80 (.385)	7.70 (.303)	C-128-10	19.90 (.785)	C-228-10X	27.30 (1.076)	C-328-10	19.90 (.785)	C-828-10*	27.70 (1.091)
		13.70 (.540)	10.00 (.393)	C-130-10	24.20 (.952)	C-230-10X	31.60 (1.243)	C-330-10	24.20 (.952)	C-830-10*	32.00 (1.258)
	1/4 (6)	15.20 (.598)	14.40 (.566)		26.80 (1.056)	C-240-10X	34.20 (1.347)		26.80 (1.056)	C-840-10*	34.60 (1.362)
		13.70 (.540)	10.00 (.393)	C-130-14	24.20 (.952)	C-230-14X	31.60 (1.243)	C-330-14	24.20 (.952)	C-830-14*	32.00 (1.258)
	5/16 (8)	15.20 (.598)	14.40 (.566)	C-140-14	26.80 (1.056)	C-240-14X	34.20 (1.347)	C-340-14	26.80 (1.056)	C-840-14*	34.60 (1.362)
		13.70 (.540)	10.00 (.393)	C-130-56	24.20 (.952)	C-230-56X	31.60 (1.243)	C-330-56	24.20 (.952)	C-830-56*	32.00 (1.258)
	3/8 (9)	15.20 (.598)	14.40 (.566)	C-140-56	26.80 (1.056)	C-240-56X	34.20 (1.347)	C-340-56	26.80 (1.056)	C-840-56*	34.60 (1.362)
		19.30 (.760)	15.50 (.611)	C-101-38	32.50 (1.280)	C-201-38X	39.90 (1.571)	C-301-38	32.50 (1.280)		40.30 (1.586)
	7/16 (11)	19.30 (.760)	15.50 (.611)	C-101-76	32.50 (1.280)	C-201-76X	39.90 (1.571)	C-301-76	32.50 (1.280)		40.30 (1.586)
1/2 (12)		19.30 (.760)	15.50 (.611)	C-101-12	32.50 (1.280)	C-201-12X	39.90 (1.571)	C-301-12	32.50 (1.280)	C-801-12*	40.30 (1.586)

\* For heavier wire insulation the maximum wire insulation diameter can be expanded to 6.50mm (.255") by adding "X" to the end of the order no.

Note: For terminals on mylar tape, add "T" at the end of loose piece order no.


**METAL STRIP OPEN BARREL STAR RINGS WITH VIBRATION SUPPORT**



Material	Order No.	Wire Size AWG (mm <sup>2</sup> )	Stud Size S	Maximum Width W (in.)	Minimum Clearance C (in.)	Maximum Length L (in.)
Brass	SRZ-0129-06	14-18 (2.00-0.80)	6	.385	.275	.949
Brass	SRZ-0129-08	14-18 (2.00-0.80)	8	.385	.275	.949
Brass	SRZ-0129-10	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Brass	SRZ-4129-06	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Brass	SRZ-4129-08	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Brass	SRZ-4129-10	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	SRZ-S-4129-06	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Steel	SRZ-S-4129-08	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Steel	SRZ-S-4129-10	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	SRZ-S-4130-10	24 (0.20)	10	.480	.386	.965

Note: 14-18 part will accept 12 gauge wire

**METAL STRIP OPEN BARREL RINGS WITH VIBRATION SUPPORT**



Material	Order No.	Wire Size AWG (mm <sup>2</sup> )	Stud Size S	Maximum Width W (in.)	Minimum Clearance C (in.)	Maximum Length L (in.)
Brass	RZ-0129-06	14-18 (2.00-0.80)	6	.385	.275	.949
Brass	RZ-0129-08	14-18 (2.00-0.80)	8	.385	.275	.949
Brass	RZ-0129-10	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Brass	RZ-4129-06	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Brass	RZ-4129-08	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Brass	RZ-4129-10	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	RZ-S-4129-06	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Steel	RZ-S-4129-08	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Steel	RZ-S-4129-10	14-18 (2.00-0.80)	10	.385	.275	.949

Note: 14-18 part will accept 12 gauge wire

