



5 Amp. Glass Passivated Ultrafast Rectifiers

ITO-220AC   PIN 1 PIN 2 CASE Case Positive	Voltage 200 to 600 V Current 5 A
	• High efficiency, Low VF • High current capability • High reliability • High surge current capability • Low power loss • For use in low voltage, high frequency inverter, free wheeling, and polarity protection application MECHANICAL DATA • Case: ITO-220AC Molded plastic • Epoxy: UL 94V-0 rate flame retardant • Terminals: Pure tin plated, Lead free, solderable per MIL-STD-202, Method 208 guaranteed • Polarity: As marked • High temperature soldering guaranteed: 260 °C/10 seconds, 4.06mm from case. • Weight: 2.24 grams

Absolute Maximum Ratings, according to IEC publication No. 134

		SFAF 504G	SFAF 506G	SFAF 508G
V _{RRM}	Maximum Recurrent Peak Reverse Voltage (V)	200	400	600
V _{RMS}	Maximum RMS Voltage (V)	140	280	420
V _{DC}	Maximum DC Blocking Voltage (V)	200	400	600
I _{F(AV)}	Maximum Average Forward Rectified Current 9.5mm Lead Length @ T _C = 100 °C	5.0 A		
I _{FSM}	Peak Forward Surge Current 8.3 ms. single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	125 A		
T _{rr}	Maximum Reverse Recovery Time From I _F = 0.5 A; I _R = 1 A; I _{RR} = 0.25 A	35 nS		
C _j	Typical Junction Capacitance at 1MHz and reverse voltage of 4V _{DC}	70 pF		
T _j , T _{stg}	Operating and Storage Temperature Range	- 65 to + 150 °C		


Electrical Characteristics

		SFAF 504G	SFAF 506G	SFAF 508G
V _F	Maximum Instantaneous Forward Voltage @ 5.0 A	0.975 V	1.3 V	1.7 V
I _R	Maximum DC Reverse Current @ T _A = 25 °C at Rated DC Blocking Voltage @ T _A = 100 °C	10 µA 400 µA		
R _{thj-c}	Typical Thermal Resistance (See Note)	5.0 °C/W		


Note: Thermal Resistance from Junction to Case Mounted on Heatsink Size of 50.8mm x 76.2mm x 6.35mm Al-Plate.

Rating And Characteristic Curves


MAXIMUM FORWARD CURRENT DERATING CURVE




TYPICAL FORWARD CHARACTERISTICS




MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




TYPICAL JUNCTION CAPACITANCE




TYPICAL REVERSE CHARACTERISTICS



REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



PACKAGE MECHANICAL DATA ITO-220AC


REF.	DIMENSIONS		
	Milimeters		
	Min.	Nominal	Max.
A	4.40	-	4.70
B	3.00	-	3.16
C	2.50	-	2.80
D	0.50	-	0.76
E	9.90	-	10.30
F	0.50	-	0.90
F1	1.10	-	1.40
F2	-	-	1.80
G1	2.40	2.55	2.70
L2	13.20	-	13.80
L3	14.80	-	15.50
L4	2.55	-	2.85
L5	3.70	-	4.10
L6	-	-	1.60
L7	6.30	-	6.90
DIA	3.00	-	3.40