

REMEC

Voltage Controlled Oscillator

Microwave Band

6.8 to 8.0 GHz

Electrical Specifications ⁽¹⁾:






Parameter	Specifications
Frequency Range	6.8 to 8.0 GHz
Power Output at 25°C (50 Ohm load)	+10.0 dBm, min.
Power Output Variation vs. Temperature	2.0 dB, typical
Frequency Drift vs. Temperature ⁽²⁾	150 MHz, typical
Frequency Pulling (12 dB Return Loss)	25 MHz, typical
Frequency Pushing	15 MHz/V, typical
Tuning Voltage Limits	0 to +20 VDC
SSB Phase Noise (50 kHz offset)	-87 dBc/Hz, typical
Harmonics ⁽³⁾	-20 dBc, typical
Spurious	-70 dBc, max.
Bias Voltage ⁽⁴⁾	+15 VDC ±1%
Bias Current ⁽⁵⁾	75 mA, typical
Operating Temperature	-30 to +65 °C

HVA103T-2
HVA103SM-22

Notes:

- Specifications guaranteed over the operating temperature range. Those specifications indicated as typical are not guaranteed. Plots exemplify typical performance at +25°C
- Total frequency drift over the full temperature range.
- Worst case harmonics over the frequency range.
- Alternate bias voltages available.
- Lower bias current available.
- Other package available see page 4-45
- Military screening available.

Typical Performance at 25°C



Specifications subject to change without notice.