







#### MODEL TYPE - GENDER #COAX 10-24 25-99

# Premium Multiple Line Coax Cables - Feature Braid and Mylar Shields in 0.3" Dia. Size

These extraordinary low loss coaxials are particularly suitable for transmission of RGB signals over extended distances without worry of signal deterioration or crosstalk. Each individual Slimline coaxial has a typical 75 ohm impedance and a full shield coverage comprised of a copper braid and mylar shield. Color coaxials are typically Red, Green, Blue, Black and Gray. Outer appearance is black including molded strain reliefs.

-	, .				
BNC Maie / BNC Male BNC Male / BNC Male	3 3 3 3 3	5.0 7.5 10.0 15.0 25.0 50.0	21.75 25.15 28.50 35.25 48.75 82.50	20:01 23:14 26:22 32:43 44:85 75:30	18.27 21.13 23.94 29.61 40.95 69.30
BNC Maie / BNC Male BNC Maie / BNC Maie BNC Maie / BNC Maie BNC Maie / BNC Maie BNC Maie / BNC Maie BNC Maie / BNC Maie	4 4 4 4 4	5.0 7.5 10.0 15.0 25.0 50.0	26.50 30.75 35.00 43.50 60.50 103.00	24 38 28 29 32 20 40 02 55 66 94 76	22.26 25.83 29.40 36.54 50.82 86.52
BNC Male / BNC Male BNC Male / BNC Male	5 5 5 5 5 5 5 5	5.0 7.5 10.0 15.0 25.0 50.0	31.50 36.75 42.00 52.50 73.50 126.00	28.98 33.31 38.64 48.30 67.62 115.92	26.46 30.87 35.28 44.10 61.74 105.84
	BNC Maie / BNC Male BNC Male / BNC Male	BNC Maie / BNC Male 3 BNC Maie / BNC Male 3 BNC Maie / BNC Male 3 BNC Male / BNC Male 4 BNC Male / BNC Male 5	BNC Maie / BNC Male 3 7.5 BNC Maie / BNC Male 3 7.5 BNC Maie / BNC Male 3 10.0 BNC Male / BNC Male 3 15.0 BNC Male / BNC Male 3 25.0 BNC Male / BNC Male 3 25.0 BNC Male / BNC Male 4 50.0 BNC Male / BNC Male 4 7.5 BNC Male / BNC Male 4 10.0 BNC Male / BNC Male 4 15.0 BNC Male / BNC Male 4 5.0 BNC Male / BNC Male 4 5.0 BNC Male / BNC Male 4 5.0 BNC Male / BNC Male 5 5.0 BNC Male / BNC Male 5 5.0 BNC Male / BNC Male 5 7.5 BNC Male / BNC Male 5 10.0 BNC Male / BNC Male 5 10.0 BNC Male / BNC Male 5 15.0	BNC Maie / BNC Male 3 5.0 21.75 BNC Maie / BNC Male 3 7.5 25.15 BNC Maie / BNC Male 3 10.0 28.50 BNC Male / BNC Male 3 15.0 35.25 BNC Male / BNC Male 3 25.0 48.75 BNC Male / BNC Male 3 50.0 82.50 BNC Male / BNC Male 4 5.0 26.50 BNC Male / BNC Male 4 7.5 30.75 BNC Male / BNC Male 4 7.5 30.75 BNC Male / BNC Male 4 10.0 35.00 BNC Male / BNC Male 4 15.0 43.50 BNC Male / BNC Male 4 50.0 60.50 BNC Male / BNC Male 4 50.0 103.00 BNC Male / BNC Male 5 5.0 31.50 BNC Male / BNC Male 5 7.5 36.75 BNC Male / BNC Male 5 7.5 36.75 BNC Male / BNC Male 5 10.0 42.00 BNC Male / BNC Male 5 15.0 52.50	BNC Male / BNC Male 3 5.0 21.75 20 01 BNC Male / BNC Male 3 7.5 25.15 23 14 BNC Male / BNC Male 3 10.0 28.50 26 22 BNC Male / BNC Male 3 15.0 35.25 32 43 BNC Male / BNC Male 3 25.0 48.75 44 85 BNC Male / BNC Male 3 50.0 82.50 75 90  BNC Male / BNC Male 4 5.0 26.50 24 38 BNC Male / BNC Male 4 7.5 30.75 28 29 BNC Male / BNC Male 4 10.0 35.00 32 20 BNC Male / BNC Male 4 15.0 43.50 40 02 BNC Male / BNC Male 4 25.0 60.50 55 66 BNC Male / BNC Male 4 25.0 60.50 55 66 BNC Male / BNC Male 4 50.0 103.00 94 76  BNC Male / BNC Male 5 5.0 31.50 28 98 BNC Male / BNC Male 5 7.5 36.75 33 81 BNC Male / BNC Male 5 15.0 52.50 48 30 BNC Male / BNC Male 5 15.0 52.50 48 30 BNC Male / BNC Male 5 15.0 52.50 48 30 BNC Male / BNC Male 5 15.0 52.50 48 30 BNC Male / BNC Male 5 15.0 52.50 48 30 BNC Male / BNC Male 5 15.0 52.50 48 30 BNC Male / BNC Male 5 15.0 52.50 48 30

### 3 Thin-Line Coax Cables - Formed into a Light Weight Cable w/RGB/VGA Color Ident.

Low loss coaxial cables are suitable for transmitting RGB video signals. Light weight and flex bility make these cables ideal for graphic systems connections. Coaxial color identity is: Red, Green, Blue, Black & Grav.

racian racar tor (	grapine systems connections: countai	color lucilei	ty 15, 100	· Orcen, Dr	ac, Diam & Co	JI a y.
CTL3B-5	BNC Male / BNC Male	3	5.0	20.50	18.36	17.22
CTL3B-7.5	BNC Male / BNC Male	3	7.5	23.25	21.39	19.53
CTL3B-10	BNC Male / BNC Male	3	10.0	26.00	23.32	21.84
CTL3B-15	BNC Male / BNC Male	3	15.0	31.50	28.98	26.46
CTL3B-25	BNC Male / BNC Male	3	25.0	42.50	39 0	35.70
	*	1.1 00.00		0		

# 4 Thin-Line Coaxial Cables - Integrated Cable with RGB Colors and Optional Sync

CTL4B-5 CTL4B-7.5 CTL4B-10 CTL4B-15 CTL4B-25	BNC Male / BNC Male BNC Male / BNC Male BNC Male / BNC Male BNC Male / BNC Male BNC Male / BNC Male	4 4 4 4	5.0 7.5 10.0 15.0	25.00 28.50 32.00 39.00	23.00 26.22 29.44 35.88	21.00 23.94 26.88 32.76
CTL4B-15 CTL4B-25 CTL4B-50	BNC Male / BNC Male BNC Male / BNC Male BNC Male / BNC Male	4 4 4	25.0 50.0	53.00 58.00	35 ⊚6 48 76 80.96	32.76 44.52 73.92

## 5 Thin-Line Coaxial Cables - Interconnection Cables for Monitors with 5 BNC

CTL5B-5	BNC Male / BNC Male	5	5.0	29.75	27 37	24.99
CTL5B-7.5	BNC Male / BNC Male	5	7.5	34.15	31. 2	28.69
CTL5B-10	BNC Male / BNC Male	5	10.0	38.50	35 -2	32.34
CTL5B-15	BNC Male / BNC Male	5	15.0	47.25	43 47	39.69
CTL5B-25	BNC Male / BNC Male	5	25.0	64.75	59 57	54.39

#### Thin-Line - 75 ohm (.11" Dia.) Coaxial Cables Replace Heavier Coaxial Type

Substitute our smaller diameter Thin-Line Series cables for your 75 ohm coaxial cables. This coaxial has a spiral tinned copper shield and a proprietary air foamed dielectric. Molded BNCs used throughout

spirai unileu copper	sincid and a proprietary air toaine	a arefective	c. Moiaea	BINGS used	i inrougnout	
CTL1B-1	BNC Male / BNC Male	1	1.0	5.25	4.3	4.41
CTL1B-2.5	BNC Male / BNC Male	1	2.5	6.00	5.52	5.04
CTL1B-5	BNC Male / BNC Male	1	5.0	7.25	6.67	6.09
CTL1B-7.5	BNC Male / BNC Male	1	7.5	8.50	7 2	7.14
CTL1B-10	BNC Male / BNC Male	1	10.0	10.25	9.43	8.61
CTL1B-15	BNC Male / BNC Male	1	15.0	12.25	11.27	10.29
CTL1B-25	BNC Male / BNC Male	1	25.0	17.25	15.87	14.49

#### MODEL DESCRIPTION #GOAX LGT/FT ONE REEL BULK PER FT.

75 ohm Thin-Line Coaxial Cable - 250 and 500 Ft. Bulk Rolls for Do-It-Yourself Projects Our Thin Line 75 ohm cable is available in conventional 250 and 500 foot spools. Note: Coaxial makeup is with spiral shield.

70.00	.40
125.00	.40
195.00	1.20
355.00	1.20
260.00	1.50
435.00	1.50
	125.00 195.00 355.00 260.00

# Premium 75 ohm ThinLine Coaxial Cable in Bulk with Braid and Aluminum Mylar Shield

The ultimate in multi-line (5) Thin 75 ohm coaxial is now available for your own fabricating needs. Features additional overall braid shield as shown.

CTL5B-250	75 ohm Coax Cable,	Copper Braid	i, Mylar/Bik 5	250	420.00	2.00
CTL5B-500	75 ohm Coax Cable,	Copper Braid	i, Mylar/Bik 5	500	625.00	2.00
MODEL		DESCRIPTION	)N		1-9 1	0-24 25-99

### Crimp Coaxial Connectors - Save Time and Money Compared to Soldering

Machined brass connectors are finished in nickel for a long, useful life. Center pin is gold-plated for lowest contact resistance. Connectors are individually packed making it easier to use in the field with little chance of losing small parts. Packaged in boxes of 25.

BAC836B-74	BNC Crimp Plug 50 ohm for RG174	1.85	1.70	1.55
BAC836B-87	BNC Crimp Plug 75 ohm for RG187 and CTL Cables	1.85	1.70	1.55

Order Toll Free: 800-343-1455

Web: http://www.L-com.com

8am - 6pm EASTERN STANDARD TIME



24 Hour Fax Service: 978-689-9484

E-mail: sales@L-com.com PRICES AND SPECIFICATIONS SUBJECT TO CHANGE.