

FEATURES AND SPECIFICATIONS

Features and Benefits

- Snap-in retention locks for secure peg retention
- Sturdy locating pegs provide added stability

Reference Information

Product Specification: PS-8981-4V/4R

Packaging: Tray

UL File No.: E29179

CSA File No.: LR19980A

Mates With: 70156/8981-4P

Designed In: Inches

Electrical

Voltage: 250V AC

Current: 6.5A

Contact Resistance: 15mΩ max.

Dielectric Withstanding Voltage: 1500V AC

Insulation Resistance: 500 MΩ min.

Mechanical

Contact Retention to Housing: 17.79N (4.0 lb) min.

Mating Force: 17.79N (4.0 lb) max.

Unmating Force: 6.67N (1.5 lb) min.

Durability: 50 cycles

Physical

Housing: Natural 6/6 nylon, UL 94V-2

Contact: Phosphor Bronze

Plating: Tin/Lead over Copper


Operating Temperature: -40 to +105°C




5.08mm (.200") Pitch Disk Drive Power Connection System Header

8981

Right Angle



CATALOG DRAWING (FOR REFERENCE ONLY)



ORDERING INFORMATION AND DIMENSIONS

Order No.	PC Tail Length
15-24-4041	3.56 (.140)