

Flachstecker


mit Steckerbreite 2,8 mm
zum Einlöten in Leiterplatten




Tabs

with tab width 2.8 mm
for soldering into PC boards


Typ 1




Typ 2



Typ 3



Typ 4



Typ	Steck- dicke	Steck- breite	b1	b2	L1	L2	L3	Mat- dicke	Form E=Einzel B=Band	Teile-Nr.	Werkstoff	Oberfläche	Fuß- note
1	0,80	2,80	1,40		14,00	6,50		0,80	E E E	17486.123.011 17486.123.041 17486.123.071	CuZn CuZn CuZn	Sn 3 Ag 1 fSn 2	
2	0,50	2,80	0,90		10,50	6,50		0,50	E	17471.123.011	CuZn	Sn 3	*1
2	0,50	2,80	0,90		10,50	6,50		0,50	E E E E	17477.123.003 17477.123.011 17477.123.042 17477.123.071	CuZn CuZn CuZn CuZn	Sn 3 Ag 3 fSn 2	
2	0,80	2,80	0,90		10,50	6,50		0,80	E E E E E E E E E	12610.123.003 12610.123.042 12610.123.051 12610.123.053 12610.123.071 12610.123.072 12610.213.003 12610.213.011 12610.213.042	CuZn CuZn CuZn CuZn CuZn CuZn CuSn CuSn CuSn	Ag 3 Au 0,1 Au 1 fSn 2 Ni 3 Sn 8 Sn 3 Ag 3	
2	0,80	2,80	0,90		11,50	8,10		0,80	E	12625.123.011	CuZn	Sn 3	
3	0,50	2,80	1,30	5,00	13,40	7,10	8,00	0,50	E	17123.123.011	CuZn	Sn 3	
3	0,80	2,80	1,30	5,00	13,40	7,10	8,00	0,80	E E E	17127.123.011 17127.123.071 17127.213.011	CuZn CuZn CuSn	Sn 3 fSn 2 Sn 3	
4	0,80	2,80	1,30	5,00	13,40	7,10	8,00	0,80	E	12124.123.071	CuZn	fSn 2	*1
4	0,80	2,80	1,30	5,00	13,40	7,10	8,00	0,80	E	17124.123.071	CuZn	fSn 2	
*1 Ohne Rastloch													
*1 Without locking hole													

12170.001