




Hutton Close, Crowther Ind Est, Washington, Tyne & Wear NE38 0AH, England
<mailto:sales@isocom.uk.com> - Tel: +44 (0)191 4166546 - Fax: +44 (0)191 4155055

- [Circuit](#)
- [Features](#)
- [Description](#)
- [Absolute Maximum Ratings](#)
- [Electrical Characteristics](#)

- [Similar Optocouplers](#)
- [Home Page](#)

IS610, IS611

Circuit



Features

- 5000V Isolation
- FET Output
- Low Cost Dual-in-line Package

Description

The IS610 and IS611 are optically coupled isolators each consisting of a Gallium Arsenide Infrared Emitting Diode and a symmetrical bilateral silicon photo detector, mounted in a standard 6-pin dual in line package. Surface Mount Option Available.

All electrical parameters are 100% tested. Specifications are guaranteed to a cumulative 0.65% AQL.

Absolute Maximum Ratings (25°C)

Storage Temperature:	-55°C to +150°C
Operating Temperature:	-55°C to +100°C
Lead Soldering:	260°C for 10s, 1.6mm from case
Input to Output Isolation Voltage:	±2500V (IS610) ±5000V (IS611)

Input Diode

Forward DC Current:	60mA
Peak Forward Current:	3A (1µs pw 300pps)
Reverse DC Voltage:	6V
Power Dissipation:	150mW
Derate Linearly:	2.0mW/°C above 25°C

Output Transistor

Breakdown Voltage:	±30V
Output Current:	±100mA
Power Dissipation:	300mW
Derate Linearly:	4.0mW/°C above 25°C

Individual Electrical Characteristics

INPUT	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
V _F	Forward Voltage	I _F =16mA		1.2	1.75	V
I _R	Reverse Current	V _R =6.0V			10	µA
V _R	Reverse Breakdown Voltage	I _R =10µA	6.0			V
OUTPUT						
V _{(BR)46}	Breakdown Voltage	I ₄₆ =10µA; I _F =0	30			V
R ₄₆	Off-State Resistance	V ₄₆ =15V, I _F =0	300			Mohms
I ₄₆	Off-State Dark Current	V ₄₆ =15V, I _F =0, T _A =25°C			50	nA
		V ₄₆ =15V, I _F =0, T _A =100°C			50	µA
C ₄₆	Capacitance	V ₄₆ =0, I _F =0, f=1MHz			15	pF
COUPLED	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
R ₄₆	On-State Resistance					
	IS610	I _F =16mA, I ₄₆ =100µA			200	ohms
	IS611				170	ohms
R _{IO}	Isolation Resistance, Input to Output	V _{IO} =500V, note 1	100			Gohm
C _{IO}	Capacitance, Input to Output	f=1MHz			2.5	pF
t _{ON}	Turn-On Time	I _F =16mA, R _L =50ohm, V ₄₆ =5V			15	µs
t _{OFF}	Turn-Off Time				15	µs

	Isolation Voltage, Input to Output					
	IS610	note 1	2500			V
	IS611		5000			V
	Resistance, Non-Linearity and Asymmetry	$I_F=16\text{mA}$, $I_{46}=25\mu\text{A RMS}$, $f=1\text{KHz}$			0.1	%

Notes

1. Measured with input leads shorted together and output leads shorted together.

Isocom takes great effort to ensure accurate data, but regrettably cannot be held liable for any error on its website. Visit [File Lists](#) to confirm old printouts are up-to-date.

[Contents](#)