



**J-Line Interconnection Systems – Accessories**

30-200/270 Amp, (30-200A Load Breaking) Maximum 600 VAC/250 VDC  
Load Breaking Receptacles, Plugs, Connectors & Inlets

**Replacement Interiors**

For Receptacles, Connectors, Plugs & Male Inlets

 <p><b>Female Interiors: Receptacles &amp; Connectors</b></p>					 <p><b>Male Interiors: Plug &amp; Male Inlets</b></p>			
Poles/Wires	30 Amp	60 Amp	100/150 Amp	200/270 Amp	30 Amp	60 Amp	100/150 Amp	200/270 Amp
+ 2P2W 2P3W	JRU322 JRU323	JRU622 JRU623	JRU1022 JRU1023	JRU2022 JRU2023	JPU322 JPU323	JPU622 JPU623	JPU1022 JPU1023	JPU2022 JPU2023
* 3P3W 3P4W * 4P4W	JRU333 JRU334 JRU344	JRU633 JRU634 JRU644	JRU1033 JRU1034 JRU1044	JRU2033 JRU2034 JRU2044	JPU333 JPU334 JPU344	JPU633 JPU634 JPU644	JPU1033 JPU1034 JPU1044	JPU2033 JPU2034 JPU2044

\*Includes equipment grounding lug for attachment to enclosure.  
+For replacement only – includes equipment grounding lug.  
**Material** – Molded composition with silvered copper contacts.

**Cup Caps**

For Watertight (Series JPS) Plugs – Standard or Reverse Service



Amperes	Cat. No.
30	F30717A
60	F30718A
100	F30814A
200	F30815A

Cup Caps are used:  
\*Where portable equipment is on a standby basis and plugs are not in use.  
\* To effectively protect insulation and contacts from excessive moisture, dirt, dust and corrosion.  
**Material** – cast aluminum, corrosion-resistant copper-free alloy, electrostatic epoxy coated with steel braid cable attached.