

- Bestückung: Reihe a + c
16 + 8*- , 28 + 6*- , 40 + 4*- und 52 + 2*-polige Messerleisten


- UK** **Contact arrangement: row a + c**
16 + 8*, 28 + 6*, 40 + 4* and 52 + 2* contact male connectors

- Ⓕ **Disposition des contacts: rangée a + c**
Connecteurs à 16 + 8*, 28 + 6*, 40 + 4*- et 52 + 2*
contacts mâles


- ① **Disposizione dei contatti: file a + c**
Connettori maschi a 16 + 8*, 28 + 6*, 40 + 4* e 52 + 2* contatti




**Lochbild / Printed circuit layout / Perçage du circuit imprimé /
Dima foratura del circuito stampato**




Polzahl No. of contacts <i>N. de contacts</i> <i>Numero poli</i>	Maße in mm / Dimensions in mm / Dimensions in mm / Dimensioni in mm			
	A	B ₁	B ₂	B ₃
52 + max. 2*	25 × 2,54 = 63,50			
40 + max. 4*	19 × 2,54 = 48,26	3 × 2,54 = 7,62		
28 + max. 6*	13 × 2,54 = 33,02	3 × 2,54 = 7,62	6 × 2,54 = 15,24	
16 + max. 8*	7 × 2,54 = 17,78	3 × 2,54 = 7,62	6 × 2,54 = 15,24	9 × 2,54 = 22,86




16 + 8* -polig / contacts / *contacts* / *contatti*




28 + 6* -poliq / **contacts** / *contacts* / *contatti*



40 + 4* -poliq / **contacts** / *contacts* / *contatti*



52 + 2* -poliq / **contacts** / *contacts* / *contatti*



Bestell-Nummern / Part numbers / Références / Numeri di catalogo

Polzahl No. of contacts <i>Nombre des contacts Numero poli</i>	Bestückung Contact arrangement <i>Disposition des contacts Disposizione dei contatti</i>	Anforderungsstufe ³⁾ Performance level <i>Niveau des exigences de contrôle Classe di prestazione</i>	Anschlußarten / Termination methods / Raccordements / Tipo di terminazione	
				
16 + 8*	Reihe a + c Row a + c <i>Rangées a + c</i> <i>Linee a + c</i>	2	105-216-033	105-216-133
28 + 6*		2	105-228-033	105-228-133
40 + 4*		2	—	105-240-133
52 + 2*		2	105-252-033	105-252-133

* Sonderkontakte

* Special contacts

* *Contacts spéciaux*

* *Contatti speciali*

Ⓓ Bauform M – Serie 105

Ⓕ Type M – Série 105

Ⓔ Type M – Series 105

Ⓘ Tipo M – Serie 105


Ⓓ **Bestückung: Reihe a + c**
16 + 8*, 28 + 6*, 40 + 4*- und 52 + 2*-polige Federleisten

Ⓕ **Disposition des contacts: rangée a + c**
Connecteurs à 16 + 8*, 28 + 6*, 40 + 4*- et 52 + 2* contacts femelles




Ⓔ **Contact arrangement: row a + c**
16 + 8*, 28 + 6*, 40 + 4*- and 52 + 2* contact female connectors


Ⓘ **Disposizione dei contatti: file a + c**
Connettori femmina a 16 + 8*, 28 + 6*, 40 + 4* e 52 + 2* contatti




16 + 8* -polig / contacts / contacts / contatti




28 + 6* -polig / contacts / contacts / contatti




40 + 4* -polig / contacts / contacts / contatti



52 + 2* -polig / contacts / contacts / contatti



Lochbild / Printed circuit layout / Perçage du circuit imprimé / Dima foratura del circuito stampato



Polzahl No. of contacts N. de contacts Numero poli	Maße in mm / Dimensions in mm / Dimensions en mm / Dimensioni in mm			
	A	B ₁	B ₂	B ₃
52 + max. 2*	25 × 2,54 = 63,50			
40 + max. 4*	19 × 2,54 = 48,26	3 × 2,54 = 7,62		
28 + max. 6*	13 × 2,54 = 33,02	3 × 2,54 = 7,62	6 × 2,54 = 15,24	
16 + max. 8*	7 × 2,54 = 17,78	3 × 2,54 = 7,62	6 × 2,54 = 15,24	9 × 2,54 = 22,86

Bestell-Nummern / Part numbers / Références / Numeri di catalogo

Polzahl No. of contacts Nombre de contacts Numero poli	Bestückung Contact arrangement Disposition des contacts Disposizione dei contatti	Anforderungsstufe ³⁾ Performance level Niveau des exigences de contrôle Classe di prestazione	Anschlußarten / Termination methods / Raccordements / Tipo di terminazione					
16 + 8*	Reihe a + c Row a + c Rangées a + c Linee a + c	2	105-216-431	105-216-432	105-216-433	—	105-216-434	105-216-533
28 + 6*		2	—	105-228-432	105-228-433	105-228-439	105-228-434	—
40 + 4*		2	105-240-431	105-240-432	105-240-433	105-240-439	105-240-434	105-240-533
52 + 2*		2	105-252-431	105-252-432	105-252-433	105-252-439	105-252-434	105-252-533

Lötöse
solder eyelet
câillet à souder
occhiello da saldare

* Sonderkontakte

* Special contacts

* Contacts spéciaux

* Contatti speciali

Ⓓ Hinweise siehe Ausklappseite

Ⓔ Notes see fold-out-page

Ⓕ Note voir la page dépliant

Ⓘ Note vedi pagina ripiegata

Ⓓ Bauform M – Serie 105

Ⓕ Type M – Série 105

Ⓖ Type M – Series 105



Ⓖ Tipo M – Serie 105

Ⓓ Bestückung: Reihe a, b + c
24 + 8*, 42 + 6*, 60 + 4*- und 78 + 2*-polige Messerleisten


Ⓖ Contact arrangement: row a, b + c
24 + 8*, 42 + 6*, 60 + 4* and 78 + 2* contact male connectors

Ⓕ Disposition des contacts: rangée a, b + c
Connecteurs à 24 + 8*, 42 + 6*, 60 + 4* et 78 + 2* contacts mâles


Ⓖ Disposizione dei contatti: file a, b + c
Connettori maschi a 24 + 8*, 42 + 6*, 60 + 4* e 78 + 2* contatti




24 + 8* -polig / contacts / contacts / contatti




42 + 6* -polig / contacts / contacts / contatti




60 + 4* -polig / contacts / contacts / contatti



78 + 2* -polig / contacts / contacts / contatti



Lochbild / Printed circuit layout / Perçage du circuit imprimé /
Dima foratura del circuito stampato



Polzahl No. of contacts N. de contacts Numero poli	Maße in mm / Dimensions in mm / Dimensions en mm / Dimensioni in mm			
	A	B ₁	B ₂	B ₃
78 + max. 2*	25 × 2,54 = 63,50			
60 + max. 4*	19 × 2,54 = 48,26	3 × 2,54 = 7,62		
42 + max. 6*	13 × 2,54 = 33,02	3 × 2,54 = 7,62	6 × 2,54 = 15,24	
24 + max. 8*	7 × 2,54 = 17,78	3 × 2,54 = 7,62	6 × 2,54 = 15,24	9 × 2,54 = 22,86

Lötöse
solder eyelet
œillet à souder
occhietto da
saldare

Bestell-Nummern / Part numbers / Références / Numeri di catalogo

Polzahl No. of contacts Nombre de contacts Numero poli	Bestückung Contact arrangement Disposition des contacts Disposizione dei contatti	Anforderungsstufe ³⁾ Performance level Niveau des exigences de contrôle Classe di prestazione	Anschlußarten / Termination methods / Raccordements / Tipo di terminazione			
24 + 8*	Reihe a, b + c Row a, b + c Rangées a, b + c Linee a, b + c	2	105-024-033	105-024-133	—	105-024-134
42 + 6*		2	105-042-033	105-042-133	—	105-042-134
60 + 4*		2	105-060-033	—	—	—
78 + 2*		2	105-078-033	—	105-078-031	105-078-134

* Sonderkontakte

* Special contacts

* Contacts spéciaux

* Contatti speciali

Ⓓ Hinweise siehe Ausklappseite

Ⓖ Notes see fold-out-page

Ⓕ Note voir la page dépliant

Ⓖ Note vedi pagina ripiegata

Ⓓ Bauform M – Serie 105

Ⓕ Type M – Série 105

Ⓖ Type M – Series 105


Ⓖ Tipo M – Serie 105

Ⓓ **Bestückung: Reihe a, b + c**
24 + 8*, 42 + 6*, 60 + 4*- und 78 + 2*-polige Federleisten


Ⓕ **Disposition des contacts: rangée a, b + c**
Connecteurs à 24 + 8*, 42 + 6*, 60 + 4*- et 78 + 2* contacts femelles

Ⓖ **Contact arrangement: row a, b + c**
24 + 8*, 42 + 6*, 60 + 4*- and 78 + 2* contact female connectors


Ⓖ **Disposizione dei contatti: file a, b + c**
Connettori femmina a 24 + 8*, 42 + 6*, 60 + 4* e 78 + 2* contatti




24 + 8* -polig / contacts / contacts / contatti




42 + 6* -polig / contacts / contacts / contatti




60 + 4* -polig / contacts / contacts / contatti



78 + 2* -polig / contacts / contacts / contatti



Lochbild / Printed circuit layout / Perçage du circuit imprimé / Dima foratura del circuito stampato



Polzahl No. of contacts N. de contacts Numero poli	Maße in mm / Dimensions in mm / Dimensions en mm / Dimensioni in mm			
	A	B ₁	B ₂	B ₃
78 + max. 2*	25 × 2,54 = 63,50			
60 + max. 4*	19 × 2,54 = 48,26	3 × 2,54 = 7,62		
42 + max. 6*	13 × 2,54 = 33,02	3 × 2,54 = 7,62	6 × 2,54 = 15,24	
24 + max. 8*	7 × 2,54 = 17,78	3 × 2,54 = 7,62	6 × 2,54 = 15,24	9 × 2,54 = 22,86

Bestell-Nummern / Part numbers / Références / Numeri di catalogo

Polzahl No. of contacts Nombre de contacts Numero poli	Bestückung Contact arrangement Disposition des contacts Disposizione dei contatti	Anforderungsstufe ³⁾ Performance level Niveau des exigences de contrôle Classe di prestazione	Anschlußarten / Termination methods / Raccordements / Tipo di terminazione				
24 + 8*	Reihe a, b, c Row a, b, c Rangées a, b, c Linee a, b, c	2	105-024-431	105-024-432	—	105-024-434	105-024-533
42 + 6*		2	105-042-431	105-042-432	105-042-433	105-042-434	105-042-533
60 + 4*		2	105-060-431	105-060-432	105-060-433	—	105-060-533
78 + 2*		2	105-078-431	105-078-432	—	105-078-434	105-078-533

Lötöse
solder eyelet
câillet à souder
occhiello da saldare

* Sonderkontakte

* Special contacts

* Contacts spéciaux

* Contatti speciali

Ⓓ Hinweise siehe Ausklappseite

Ⓖ Notes see fold-out-page

Ⓕ Note voir la page dépliant

Ⓖ Note vedi pagina ripiegata