




### Features

- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ Plastic material used carries Underwriters Laboratory Classifications 94V-0
- ✧ High Surge current capability
- ✧ Qualified as per AEC-Q101
- ✧ Guard-ring for transient protection
- ✧ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✧ High temperature soldering guaranteed: 260°C / 10 seconds, 0.375"(9.5mm) lead lengths 5 lbs tension
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode

### Mechanical Data

- ✧ Case: ITO-220AB
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in-lbs. Max.
- ✧ Weight: 1.7 grams



### Dimensions in inches and (millimeters)

#### Marking Diagram



- MBRF10LXXCT = Specific Device Code  
 G = Green compound  
 Y = Year  
 WW = Work Week

### Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%

Type Number	Symbol	MBRF10L100CT		Unit
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	100		V
Maximum RMS Voltage	$V_{RMS}$	70		V
Maximum DC blocking voltage	$V_{DC}$	100		V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	10		A
Peak Repetitive Forward Current (Rated VR, Square Wave, 20KHz)	$I_{F(RMS)}$	10		A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	120		A
Peak Repetitive Reverse Surge Current (Note 1)	$I_{RRM}$	1		A
Maximum Instantaneous Forward Voltage at (Note 2) $I_F = 5A, T_A = 25^\circ C$ $I_F = 5A, T_A = 125^\circ C$ $I_F = 10A, T_A = 25^\circ C$ $I_F = 10A, T_A = 125^\circ C$	$V_F$	TYP	MAX	V
		0.73	0.76	
		0.59	0.65	
		0.82	0.85	
		0.66	0.71	
Maximum Reverse Current at Rated DC Blocking Voltage $T_A = 25^\circ C$ $T_A = 125^\circ C$	$I_R$	TYP	MAX	uA mA
		0.3	20	
		0.5	15	
Voltage rate of change (Rated $V_R$ )	dV/dt	10,000		V/uS
Typical Junction Capacitance (Note 3)	$C_j$	185		pF
Maximum Thermal Resistance Per Leg	$R_{\theta JC}$	5.5		°C/W
Operating Temperature Range	$T_J$	-55 to + 150		°C
Storage Temperature Range	$T_{STG}$	-55 to + 150		°C

Note1: 2.0uS Pulse Width, F=1.0KHz, Continues 10 Cycles

Note2: Pulse Test : 300us Pulse Width, 1% Duty cycle

Note3: Measure at 1MHz and Applied Reverse Voltage of 4.0V D.C.

## RATINGS AND CHARACTERISTIC CURVES (MBRF10L100CT)

FIG. 1 MAXIMUM FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE




FIG. 6 TYPICAL TRANSIENT THERMAL IMPEDANCE

