

1. Features

- Typical 1dB bandwidth of 30.2MHz
- High attenuation
- Single Ended Operation
- Dual In-line Package (DIP)

RoHS Compliant


Tested by SGS Testing Korea

2. Electrical Specifications


Source and Load Impedance = 50Ω

Operating Temperature : +25℃		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	260.0	-
Insertion Loss	dB	-	29.0	31.5
1dB Bandwidth	MHz	-	30.2	-
3dB Bandwidth	MHz	30.45	30.52	-
40dB Bandwidth	MHz	-	31.91	32.0
Amplitude Ripple (fo ± 14.85 MHz)	dB	-	0.5	1.2
Group Delay Variation (fo ± 14.85 MHz)	nsec	-	35	70
Absolute Delay	usec	-	2.75	-
Ultimate Rejection	dB	45	50	-
Temperature Coefficient of Frequency	ppm/℃	-	-18	-

D2012 Package Dimension



Matching Schematic



Pin Configuration

Input	1	Ground	2,4
Output	5	Others	Ground

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

3. Typical Performance (at +25°C)

