

[Home](#) > [Products](#) > [By Type](#) > [Relays](#) > [Product Feature Selector](#) > Product Details

V23030C1021A206 Product Details



V23030C1021A206
(6-1393801-4)

TE Internal Number: 6-1393801-4

 [Active](#)

Communications/Signal PC Board Relays

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- V23030 / Card Relay SN Series
- DC Actuating System
- Input Voltage = 24 VDC
- Contact Arrangement = 6 Form C, 6PDT, 6 C/O
- Contact Current Rating = 2 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Termination Type = Through Hole

Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 24
- Contact Current Rating (Amps.) = 2
- [Coil Resistance \(?\)](#) = 730
- Coil Power, Nominal (mW) = 780
- Dielectric Between Coil and Contacts (V rms) = 1000

Body Related Features:

- Series = V23030 / Card Relay SN
- Polarized = No

Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Dust Protected
- [FCC Part 68 Isolation](#) = No
- Approved Standards = None
- Contact Base Material = Hard Gold
- Approx. Dimensions (L x W x H) (mm [in]) = 39.70 x 37.40 x 10.20 [1.564 x 1.473 x .401]
- Contact Type = Bifurcated
- Pin Configuration = Industry Standard

Configuration Related Features:

- [Contact Arrangement](#) = 6 Form C, 6PDT, 6 C/O
- [Coil Magnetic System](#) = Non Polarized, Monostable
- Coil Suppression Diode = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Other:

- Brand = Axicom

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat with Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)