

.150" (3.81mm) ELVT Plug










Download part **DXF** File





Download part DXF File

Top/ Bottom Entry

Product Intro.	Variations
Gold Plating	Locking Ears
Marking	Mating Header

All ELV pluggable terminal blocks incorporate moving vise clamp wire termination and mate with Amphenol Pcd ELVH headers.

ELVT blocks offer wire entry perpendicular to contact-top or bottom entry is available.

SPECIFICATIONS:

Current Rating: 12A Operating Voltage: 300V Insulation Resistance: >103 Megohms Dielectric Withstanding: <1600V Wire Pullout Force: Per UL 486E, Section 14

MATERIALS:

Housing: PPO, UL 94V-0, Black or green Contact: Copper alloy, optional finish Clamp Screw: Steel, nickel finish Wire clamp: Copper alloy, nickel finish

INSTALLATION:

Wire Range: 16-28 AWG Wire Strip Length: .25" (.375" ELVF) Tightening Torque: 2.2 lb-in. (0.25N-m



Pos	Catalog # Black	Catalog # Green	L (In.)
2	ELVT02500	ELVT025G0	.300
3	ELVT03500	ELVT035G0	.450
4	ELVT04500	ELVT045G0	.600
5	ELVT05500	ELVT055G0	.750
6	ELVT06500	ELVT065G0	.900
7	ELVT07500	ELVT075G01	.050
8	ELVT08500	ELVT085G01	.200
9	ELVT09500	ELVT095G01	.350
10	ELVT10500	ELVT105G01	.500
11	ELVT11500	ELVT115G01	.650
12	ELVT12500	ELVT125G01	.800
13	ELVT13500	ELVT135G01	.950
14	ELVT14500	ELVT145G02	2.100
15	ELVT15500	ELVT155G02	2.250
16	ELVT16500	ELVT165G02	2.400
17	ELVT17500	ELVT175G02	2.550
18	ELVT18500	ELVT185G02	2.700
19	ELVT19500	ELVT195G02	2.850
20	ELVT 20500	ELVT205G03	3.000

Back to Home Page

C Amphenol Pcd