


**EVALUATION KIT  
AVAILABLE**

# MAXIM

## Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

**MAX2320/21/22/24/26/27/29**

### General Description

The MAX2320/MAX2321/MAX2322/MAX2324/MAX2326/MAX2327/MAX2329 high-performance SiGe receiver front-end ICs set a new industry standard for low noise and high linearity at a low supply current. This family integrates a variety of unique features such as an LO frequency doubler and divider, dual low-noise amplifier (LNA) gain settings, and a low-current paging mode that extends the handset standby time.

The MAX2320 family includes seven ICs: four operate at both cellular and PCS frequencies, one operates at cellular frequencies, one at PCS frequencies, and one is configured as a dual PCS device (see *Selector Guide*). Each part includes an LNA with a high input third-order intercept point (IIP<sub>3</sub>) to minimize intermodulation and cross-modulation in the presence of large interfering signals. In low-gain mode, the LNA is bypassed to provide higher cascaded IIP<sub>3</sub> at a lower current. For paging, a low-current, high-gain mode is provided.

The CDMA mixers in cellular and PCS bands have high linearity, low noise, and differential IF outputs. The FM mixer is designed for lower current and a single-ended output.

All devices come in a 20-pin TSSOP-EP package with exposed paddle and are specified for the extended temperature range (-40°C to +85°C).

### Applications

CDMA/TDMA/PDC/WCDMA/GSM Cellular Phones

Single/Dual/Triple-Mode Phones

Wireless Local Loop (WLL)

### Selector Guide

PART	DESCRIPTION
MAX2320	Dual-band, dual VCO inputs, and dual IF outputs
MAX2321	MAX2320 with LO doubler
MAX2322	PCS band, single mode with optional frequency doubler
MAX2324	Cellular band, dual IF outputs
MAX2326	MAX2320 with LO divider
MAX2327	Dual-band, dual VCO inputs, and separately controlled VCO buffers
MAX2329	PCS band with dual inputs, half-band PCS filter compatible

*Typical Application Circuits appear at end of data sheet.*

### Features


- ♦ Ultra-High Linearity at Ultra-Low Current and Noise
- ♦ +2.7V to +3.6V Operation
- ♦ Pin-Selectable Low-Gain Mode Reduces Gain by 15dB and Current by 3mA
- ♦ Pin-Selectable Paging Mode Reduces Current Draw by 6mA when Transmitter is Not in Use
- ♦ LO Output Buffers
- ♦ LO Frequency Doubler (MAX2321)
- ♦ LO Frequency Divider (MAX2326)
- ♦ 0.1µA Shutdown Current
- ♦ 20-Pin TSSOP-EP Package

### Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
<b>MAX2320EUP</b>	-40°C to +85°C	20 TSSOP-EP
<b>MAX2321EUP</b>	-40°C to +85°C	20 TSSOP-EP
<b>MAX2322EUP</b>	-40°C to +85°C	20 TSSOP-EP
<b>MAX2324EUP</b>	-40°C to +85°C	20 TSSOP-EP
<b>MAX2326EUP</b>	-40°C to +85°C	20 TSSOP-EP
<b>MAX2327EUP</b>	-40°C to +85°C	20 TSSOP-EP
<b>MAX2329EUP*</b>	-40°C to +85°C	20 TSSOP-EP

\* Future product—contact factory for availability.

### Pin Configurations



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## ABSOLUTE MAXIMUM RATINGS

V <sub>CC</sub> to GND .....	-0.3V to +4.3V
Digital Input Voltage to GND .....	-0.3V to (V <sub>CC</sub> + 0.3V)
RF Input Signals .....	1.0V peak
Continuous Power Dissipation (T <sub>A</sub> = +70°C) 20-Pin TSSOP-EP (derate 80mW/°C above +70°C).....	6.4W
Operating Temperature Range .....	-40°C to +85°C

Junction Temperature .....	+150°C
Storage Temperature Range .....	-65°C to +150°C
Lead Temperature (soldering, 10sec) .....	+300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## DC ELECTRICAL CHARACTERISTICS—MAX2320/MAX2321/MAX2326

(V<sub>CC</sub> = +2.7V to +3.6V, R<sub>RBIAS</sub> = R<sub>RLNA</sub> = 20kΩ, no RF signals applied, BUFFEN = 0.6V, LO buffer outputs connected to V<sub>CC</sub> through 100Ω resistors, all other RF and IF outputs connected to V<sub>CC</sub>, T<sub>A</sub> = -40°C to +85°C, unless otherwise noted. Typical values are at V<sub>CC</sub> = +2.75V and T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS	
Supply Voltage	V <sub>CC</sub>			+2.7	+3.6		V	
Operating Supply Current (Note 1)	I <sub>CC</sub>	High-gain, high-linearity modes	PCS band	MAX2320/6	20	27.5	mA	
				MAX2321	22	29.5		
			Cellular band	MAX2320/1	19.5	24.5		
				MAX2326	20.5	25.5		
		High-gain, low-linearity paging modes	PCS band	MAX2320/6	14.5	22		
				MAX2321	16.5	24		
			Cellular band	MAX2320/1	14	18		
				MAX2326	15	19		
		Low-gain, high-linearity modes	PCS band	MAX2320/6	17	23		
				MAX2321	19	25		
			Cellular band	MAX2320/1	16	19.5		
				MAX2326	17	20.5		
FM mode					14	18		
LO Buffer Supply Current	I <sub>LOBUF</sub>	Additional current for BUFFEN = V <sub>CC</sub>		4.5	6.5		mA	
Shutdown Supply Current	I <sub>SHDN</sub>	(Note 1)		0.1	20		µA	
Digital Input Logic High	V <sub>IH</sub>			2.0			V	
Digital Input Logic Low	V <sub>IL</sub>				0.6		V	
Digital Input Current High	I <sub>IH</sub>				5		µA	
Digital Input Current Low	I <sub>IL</sub>			-25			µA	

# **Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs**

## **DC ELECTRICAL CHARACTERISTICS—MAX2322/MAX2324**

( $V_{CC} = +2.7V$  to  $+3.6V$ ,  $R_{RBIAS} = R_{RLNA} = 20\text{k}\Omega$ , no RF signals applied,  $BUFFEN = 0.6V$ , LO buffer outputs connected to  $V_{CC}$  through  $100\Omega$  resistors, all other RF and IF outputs connected to  $V_{CC}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ , unless otherwise noted. Typical values are at  $V_{CC} = +2.75V$  and  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS			MIN	TYP	MAX	UNITS
Supply Voltage	$V_{CC}$				+2.7		+3.6	V
Operating Supply Current (Note 1)	$I_{CC}$	High-gain, high-linearity modes	PCS band (MAX2322)	LOX2 = GND	20	27.5		mA
				LOX2 = $V_{CC}$	22	29.5		
			Cellular band (MAX2324)		19.5	24.5		
		High-gain, low-linearity paging modes	PCS band (MAX2322)	LOX2 = GND	14.5	22		
				LOX2 = $V_{CC}$	16.5	24		
			Cellular band (MAX2324)		14	18		
		Low-gain, high-linearity modes	PCS band (MAX2322)	LOX2 = GND	17	23		
				LOX2 = $V_{CC}$	19	25		
			Cellular band (MAX2324)		16	19.5		
FM mode (MAX2324 only)					14	18		
LO Buffer Supply Current	$I_{LOBUF}$	Additional current for $BUFFEN = V_{CC}$			4.5	6.5		mA
Shutdown Supply Current	$I_{SHDN}$	(Note 1)			0.1	20		$\mu\text{A}$
Digital Input Logic High	$V_{IH}$				2.0			V
Digital Input Logic Low	$V_{IL}$					0.6		V
Digital Input Current High	$I_{IH}$					5		$\mu\text{A}$
Digital Input Current Low	$I_{IL}$				-25			$\mu\text{A}$
Digital Output Logic High	$V_{OH}$	MAX2324 only			1.7			V
Digital Output Logic Low	$V_{OL}$	MAX2324 only				0.4		V
Digital Output Current High	$I_{OH}$	MAX2324 only			60			$\mu\text{A}$
Digital Output Current Low	$I_{OL}$	MAX2324 only, $V_{MODEOUT} = 2.4V$				-100		$\mu\text{A}$

**MAX2320/21/22/24/26/27/29**

## **DC ELECTRICAL CHARACTERISTICS—MAX2327**

( $V_{CC} = +2.7V$  to  $+3.6V$ ,  $R_{RBIAS} = R_{RLNA} = 20\text{k}\Omega$ , no RF signals applied,  $BUFFEN = 0.6V$ , LO buffer outputs connected to  $V_{CC}$  through  $100\Omega$  resistors, all other RF and IF outputs connected to  $V_{CC}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ , unless otherwise noted. Typical values are at  $V_{CC} = +2.75V$  and  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS			MIN	TYP	MAX	UNITS		
Supply Voltage	$V_{CC}$				+2.7		+3.6	V		
Operating Supply Current (Note 1)	$I_{CC}$	High-gain mode	PCS band		14.5	22		mA		
			Cellular band		14	18				
		FM mode			14	18				
LO Buffer Supply Current	$I_{LOBUF}$	Additional current for $BUFFEN = V_{CC}$			4.5	6.5		mA		
Shutdown Supply Current	$I_{SHDN}$	(Note 1)			0.1	20		$\mu\text{A}$		
Digital Input Logic High	$V_{IH}$				2.0			V		
Digital Input Logic Low	$V_{IL}$					0.6		V		
Digital Input Current High	$I_{IH}$					5		$\mu\text{A}$		
Digital Input Current Low	$I_{IL}$				-25			$\mu\text{A}$		

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## AC ELECTRICAL CHARACTERISTICS—MAX2320/MAX2321/MAX2326

(MAX232\_ evaluation kit (EV kit),  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), for MAX2321  $f_{LOHIN} = 1085\text{MHz}$ , LO input power =  $-7\text{dBm}$ ,  $50\Omega$  system,  $TA = +25^\circ\text{C}$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS		
Low-Band RF Frequency Range (Note 2)				800		1000	MHz		
High-Band RF Frequency Range (Note 2)				1800		2500	MHz		
Low-Band LO Frequency Range (Note 2)				700		1150	MHz		
High-Band LO Frequency Range (Note 2)				1600		2300	MHz		
IF Frequency Range (Note 2)				50		400	MHz		
<b>LNA PERFORMANCE</b>									
<b>HIGH-GAIN, HIGH-LINEARITY MODES</b> (Note 1)									
Gain (Note 3)	TA = $+25^\circ\text{C}$	PCS band		13	14.5	16	dB		
		Cellular band		13.5	15	16			
	TA = $-40^\circ\text{C}$ to $+85^\circ\text{C}$	PCS band		12	14.5	17			
		Cellular band		13	15	16.5			
Gain Variation over Temperature Relative to $+25^\circ\text{C}$ (Note 4)	TA = $-40^\circ\text{C}$ to $+85^\circ\text{C}$	PCS band		$\pm 1$			dB		
		Cellular band		$\pm 1$					
Noise Figure (Note 4)		PCS band			1.6		dB		
		Cellular band			1.4				
Input Third-Order Intercept (Notes 4, 5)		PCS band			+7		dBm		
		Cellular band			+7				
Output 1dB Compression		PCS band			+6.5		dBm		
		Cellular band			+7				
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODES AND FM MODE</b> (Note 1)									
Gain (Note 3)		PCS band			13.5		dB		
		Cellular band			14.5				
Gain Variation over Temperature Relative to $+25^\circ\text{C}$ (Note 4)	TA = $-40^\circ\text{C}$ to $+85^\circ\text{C}$	PCS band		$\pm 1$			dB		
		Cellular band		$\pm 1$					
Noise Figure (Note 4)		PCS band			1.7		dB		
		Cellular band			1.4				
Input Third-Order Intercept (Note 5)		PCS band			+2		dBm		
		Cellular band			+3.5				
<b>LOW-GAIN, HIGH-LINEARITY MODES</b> (Note 1)									
Gain (Note 3)		PCS band			-0.5		dB		
		Cellular band			0				
Gain Variation over Temperature Relative to $+25^\circ\text{C}$ (Note 4)	TA = $-40^\circ\text{C}$ to $+85^\circ\text{C}$	PCS band		$\pm 1$			dB		
		Cellular band		$\pm 1$					
Noise Figure		PCS band			5		dB		
		Cellular band			4				

# **Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs**

## **AC ELECTRICAL CHARACTERISTICS—MAX2320/MAX2321/MAX2326 (continued)**

(MAX232\_ evaluation kit (EV kit), V<sub>CC</sub> = +2.75V, f<sub>LNAINH</sub> = f<sub>MIXINH</sub> = 1960MHz, f<sub>LNAINL</sub> = f<sub>MIXINL</sub> = 881MHz, f<sub>LOHIN</sub> = 1750MHz, f<sub>LOLIN</sub> = 1091MHz (digital modes), f<sub>LOLIN</sub> = 991MHz (FM mode), for MAX2321 f<sub>LOHIN</sub> = 1085MHz, LO input power = -7dBm, 50Ω system, TA = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS		
<b>LNA PERFORMANCE</b>								
<b>LOW-GAIN, HIGH-LINEARITY MODES</b> (Note 1)								
Input Third-Order Intercept (Note 5)		PCS band	+14			dBm		
		Cellular band	+16					
<b>MIXER PERFORMANCE</b>								
<b>HIGH-GAIN, HIGH-LINEARITY, AND LOW-GAIN MODES</b> (Note 1)								
Gain (Note 3)		TA = +25°C, PCS band	MAX2320/6	11	12.5	13.5	dB	
			MAX2321	7.5	11	13		
		TA = -40°C to +85°C, PCS band	MAX2320/6	9	12.5	14.5		
			MAX2321	7	11	13		
		TA = +25°C, cellular band	MAX2320/1	10	12	13		
			MAX2326	10.5	12	13.5		
		TA = -40°C to +85°C, cellular band	MAX2320/1	9.5	12	14		
			MAX2326	9.5	12	14.5		
Gain Variation over Temperature Relative to +25°C (Note 4)		TA = -40°C to +85°C	PCS band	+1.5			dB	
			Cellular band	+1.5				
Noise Figure		PCS band	MAX2320/6	8.5			dB	
			MAX2321 (Note 6)	11.5				
		Cellular band	MAX2320/1	8.5				
			MAX2326	9.5				
Input Third-Order Intercept (Notes 4, 5)		PCS band	MAX2320/6	+4			dBm	
			MAX2321	+4				
		Cellular band	MAX2320/1	+4				
			MAX2326	+3				
Output 1dB Compression		PCS band		+1			dBm	
		Cellular band		+3				
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODES</b> (Note 1)								
Gain (Note 3)		PCS band	MAX2320/6	12			dB	
			MAX2321	11				
		Cellular band	MAX2320/1	11.5				
			MAX2326	11.5				
Gain Variation over Temperature Relative to +25°C (Note 4)		TA = -40°C to +85°C	PCS band	±1.5			dB	
			Cellular band	±1.5				
Noise Figure		PCS band	MAX2320/6	8			dB	
			MAX2321 (Note 6)	10.5				
		Cellular band	MAX2320/1	7.5				
			MAX2326	8.5				

**MAX2320/21/22/24/26/27/29**

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## AC ELECTRICAL CHARACTERISTICS—MAX2320/MAX2321/MAX2326 (continued)

(MAX232\_ evaluation kit (EV kit),  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), for MAX2321  $f_{LOHIN} = 1085\text{MHz}$ , LO input power =  $-7\text{dBm}$ ,  $50\Omega$  system,  $TA = +25^\circ\text{C}$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
MIXER PERFORMANCE						
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODES</b> (Note 1)						
Input Third-Order Intercept (Note 4)	PCS band	MAX2320/6	+1.5			dBm
		MAX2321	+2			
	Cellular band	MAX2320/1	+1.5			
		MAX2326	+1			
Output 1dB Compression		PCS band	0			dBm
		Cellular band	+1			
<b>FM MODE</b> (Note 1)						
Gain (Note 3)		TA = $+25^\circ\text{C}$	8	9.5	11	dB
		TA = $-40^\circ\text{C}$ to $+85^\circ\text{C}$	7	9.5	11.5	
Noise Figure				12.5		dB
Input Third-Order Intercept (Notes 4, 5)				+5.5		dBm

# **Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs**

## **AC ELECTRICAL CHARACTERISTICS—MAX2322**

(MAX2322 EV kit, V<sub>CC</sub> = +2.75V, f<sub>LNAINH</sub> = f<sub>MIXINH</sub> = 1960MHz, f<sub>LOHIN</sub> = 1750MHz (LOX2 = GND), f<sub>LOHIN</sub> = 1085MHz (LOX2 = V<sub>CC</sub>), R<sub>RLNA</sub> = R<sub>RBIAS</sub> = 20kΩ, LO input power = -7dBm, 50Ω system, T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
RF Frequency Range (Note 2)			1800	2500		MHz
LO Frequency (Note 2)		LOX2 = V <sub>CC</sub>	800	1150		MHz
		LOX2 = GND	1600	2300		
IF Frequency Range (Note 2)			50	400		MHz
<b>LNA PERFORMANCE</b>						
<b>HIGH-GAIN, HIGH-LINEARITY MODE PCS BAND (Note 1)</b>						
Gain (Note 3)		T <sub>A</sub> = +25°C	13	14.5	16	dB
		T <sub>A</sub> = -40°C to +85°C	12	14.5	17	
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C		±1		dB
Noise Figure (Note 4)				1.6		dB
Input Third-Order Intercept (Notes 4, 5)				+7		dBm
Output 1dB Compression				+6.5		dBm
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODE PCS BAND (Note 1)</b>						
Gain (Note 3)			13.5			dB
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C		±1		dB
Noise Figure (Note 4)				1.7		dB
Input Third-Order Intercept (Note 5)				+2		dBm
<b>LOW-GAIN MODE PCS BAND (Note 1)</b>						
Gain (Note 3)			-0.5			dB
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C		±1		dB
Noise Figure				5		dB
Input Third-Order Intercept (Note 5)				+14		dBm
<b>MIXER PERFORMANCE</b>						
<b>HIGH-GAIN, HIGH-LINEARITY, AND LOW-GAIN MODES PCS BAND (Note 1)</b>						
Gain (Note 3)		T <sub>A</sub> = +25°C	11	12.5	13.5	dB
		T <sub>A</sub> = -40°C to +85°C	9	12.5	14.5	
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C		±1.5		dB
Noise Figure				8.5		dB
Input Third-Order Intercept (Notes 4, 5)				+4		dBm
Output 1dB Compression				+1		dBm

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## AC ELECTRICAL CHARACTERISTICS—MAX2322 (continued)

(MAX232\_ EV kit, V<sub>CC</sub> = +2.75V, f<sub>LNAINH</sub> = f<sub>MIXINH</sub> = 1960MHz, f<sub>LOHIN</sub> = 1750MHz (LOX2 = GND), f<sub>LOHIN</sub> = 1085MHz (LOX2 = V<sub>CC</sub>), R<sub>RLNA</sub> = R<sub>RBIAS</sub> = 20kΩ, LO input power = -7dBm, 50Ω system, T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODE PCS BAND (Note 1)</b>						
Gain (Note 3)			12			dB
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C		±1.5		dB
Noise Figure (Note 4)			8			dB
Input Third-Order Intercept (Notes 4, 5)				+1.5		dBM
Output 1dB Compression			0			dBM

## AC ELECTRICAL CHARACTERISTICS—MAX2324

(MAX232\_ EV kit, V<sub>CC</sub> = +2.75V, f<sub>LNAINL</sub> = f<sub>MIXINL</sub> = 881MHz, f<sub>LOLIN</sub> = 1091MHz (digital modes), f<sub>LOLIN</sub> = 991MHz (FM mode), R<sub>RLNA</sub> = R<sub>RBIAS</sub> = 20kΩ, LO input power = -7dBm, 50Ω system, T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
RF Frequency Range (Note 2)			800	1000		MHz
LO Frequency (Note 2)			700	1150		MHz
IF Frequency Range (Note 2)			50	400		MHz
<b>LNA PERFORMANCE</b>						
<b>HIGH-GAIN, HIGH-LINEARITY MODE CELLULAR BAND (Note 1)</b>						
Gain (Note 3)		T <sub>A</sub> = +25°C	13.5	15	16	dB
		T <sub>A</sub> = -40°C to +85°C	13	15	16.5	
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C		±1		dB
Noise Figure (Note 4)			1.4			dB
Input Third-Order Intercept (Notes 4, 5)				+7		dBM
Output 1dB Compression			+	7		dBM

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## AC ELECTRICAL CHARACTERISTICS—MAX2324 (continued)

(MAX2324 EV kit, V<sub>CC</sub> = +2.75V, f<sub>LNAINL</sub> = f<sub>MIXINL</sub> = 881MHz, f<sub>LOLIN</sub> = 1091MHz (digital modes), f<sub>LOLIN</sub> = 991MHz (FM mode), R<sub>RLNA</sub> = R<sub>RBIAS</sub> = 20kΩ, LO input power = -7dBm, 50Ω system, T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODE CELLULAR BAND AND FM MODE (Note 1)</b>						
Gain (Note 3)			14.5			dB
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C	±1			dB
Noise Figure (Note 4)			1.4			dB
Input Third-Order Intercept (Note 5)			+3.5			dBm
<b>LOW-GAIN MODE (Note 1)</b>						
Gain (Note 3)			0			dB
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C	±1			dB
Noise Figure			4			dB
Input Third-Order Intercept (Note 5)			+16			dBm
<b>MIXER PERFORMANCE</b>						
<b>HIGH-GAIN, HIGH-LINEARITY, AND LOW-GAIN MODES CELLULAR BAND (Note 1)</b>						
Gain (Note 3)		T <sub>A</sub> = +25°C	10	12	13	dB
		T <sub>A</sub> = -40°C to +85°C	9.5	12	14	
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C	±1.5			dB
Noise Figure			8.5			dB
Input Third-Order Intercept (Notes 4, 5)			+4			dBm
Output 1dB Compression			+3			dBm
<b>HIGH-GAIN, LOW-LINEARITY PAGING MODE CELLULAR BAND (Note 1)</b>						
Gain (Note 3)			12			dB
Gain Variation over Temperature Relative to +25°C (Note 4)		T <sub>A</sub> = -40°C to +85°C	±1.5			dB
Noise Figure			7.5			dB
Input Third-Order Intercept (Notes 4, 5)			+1.5			dBm
Output 1dB Compression			+1			dBm

**MAX2320/21/22/24/26/27/29**

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## AC ELECTRICAL CHARACTERISTICS—MAX2324 (continued)

(MAX232\_EV kit, V<sub>CC</sub> = +2.75V, f<sub>LNAINL</sub> = f<sub>MIXINL</sub> = 881MHz, f<sub>LOLIN</sub> = 1091MHz (digital modes), f<sub>LOLIN</sub> = 991MHz (FM mode), R<sub>RRLNA</sub> = R<sub>RBIA</sub>S = 20kΩ, LO input power = -7dBm, 50Ω system, T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>FM MODE</b> (Note 1)						
Gain (Note 3)		T <sub>A</sub> = +25°C	8	9.5	11	dB
		T <sub>A</sub> = -40°C to +85°C	7	9.5	11.5	
Noise Figure				12.5		dB
Input Third-Order Intercept (Notes 4, 5)				+5.5		dBm

## AC ELECTRICAL CHARACTERISTICS—MAX2327

(MAX232\_EV kit, V<sub>CC</sub> = +2.75V, f<sub>LNAINH</sub> = f<sub>MIXINH</sub> = 1960MHz, f<sub>LNAINL</sub> = f<sub>MIXINL</sub> = 881MHz, f<sub>LOHIN</sub> = 1750MHz, f<sub>LOLIN</sub> = 1091MHz (digital modes), f<sub>LOLIN</sub> = 991MHz (FM mode), R<sub>RRLNA</sub> = R<sub>RBIA</sub>S = 20kΩ, LO input power = -7dBm, 50Ω system, T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Low-Band RF Frequency Range (Note 2)			800		1000	MHz
High-Band RF Frequency Range (Note 2)			1800		2500	MHz
Low-Band LO Frequency Range (Note 2)			700		1150	MHz
High-Band LO Frequency Range (Note 2)			1600		2300	MHz
IF Frequency Range (Note 2)			50		400	MHz

### LNA PERFORMANCE

#### DIGITAL AND FM MODES (Note 1)

Gain (Note 3)	TA = +25°C	PCS band	12	13.5	15.5	dB
		Cellular band	13	14.5	15.5	
	TA = -40°C to +85°C	PCS band	11.5	13.5	16	
		Cellular band	12.5	14.5	16	
Gain Variation over Temperature Relative to +25°C (Note 4)	TA = -40°C to +85°C	PCS band	±1			dB
		Cellular band	±1			
Noise Figure (Note 4)		PCS band		1.7		dB
		Cellular band		1.4		
Input Third-Order Intercept (Note 5)		PCS band		+2		dBm
		Cellular band		+3.5		

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## AC ELECTRICAL CHARACTERISTICS—MAX2327 (continued)

(MAX2327\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXINH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXINL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode),  $R_{RLNA} = R_{RBIA} = 20\text{k}\Omega$ , LO input power = -7dBm,  $50\Omega$  system,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>MIXER PERFORMANCE</b>						
<b>DIGITAL MODES</b> (Note 1)						
Gain (Note 3)		$T_A = +25^\circ\text{C}$	PCS band	10.5	12	13
			Cellular band	9.5	11.5	12.5
		$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	PCS band	9.5	12	14
			Cellular band	9	11.5	13.5
Gain Variation over Temperature Relative to $+25^\circ\text{C}$ (Note 4)		$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$		$\pm 1.5$		dB
Noise Figure		PCS band		8		dB
		Cellular band		7.5		
Input Third-Order Intercept (Notes 4, 5)		PCS band		+1.5		dBm
		Cellular band		+1.5		
Output 1dB Compression		PCS band		0		dBm
		Cellular band		+1		
<b>FM MODE</b> (Note 1)						
Gain (Note 3)		$T_A = +25^\circ\text{C}$	8	9.5	11	dB
		$T_A = -40^\circ\text{C}$ to $+85^\circ\text{C}$	7	9.5	11.5	
Noise Figure				12.5		dB
Input Third-Order Intercept (Notes 4, 5)				+5.5		dBm

## AC ELECTRICAL CHARACTERISTICS—All Devices

(MAX2327\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$ ,  $R_{RLNA} = R_{RBIA} = 20\text{k}\Omega$ , LO input power = -7dBm,  $BUFFEN = V_{CC}$ ,  $50\Omega$  system,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>LO BUFFER PERFORMANCE</b>						
LO Output Level		Load = $100\Omega$ pull-up resistor		-12		dBm
		$BUFFEN = GND$		-44		
LO_OUT Even-Harmonic Distortion				-31		dBc
LO Emissions at LNA Input Port		Interstage filter rejection = 20dB		-50		dBm

**Note 1:** See Tables 1–5 for operational mode selection.

**Note 2:** Operation is characterized for the frequencies specified in the conditions; for other frequencies in the band, see Tables 8–12 for LNA and mixer S parameters.

**Note 3:** Guaranteed by design, characterization, and production functional test.

**Note 4:** Guaranteed by design and characterization.

**Note 5:** For cellular band, RF inputs are -25dBm each tone at 881MHz and 882MHz,  $f_{LO} = 1091\text{MHz}$ . For PCS band, RF inputs are -25dBm each tone at 1960MHz and 1961MHz,  $f_{LO} = 2170\text{MHz}$ . For IIP3 vs ICC trade-off, see *Typical Operating Characteristics*.










**Note 6:** The noise figure of the MAX2321 PCS-band mixer improves by approximately 2dB with LO input power = 0dBm.

**MAX2320/21/22/24/26/27/29**

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Operating Characteristics


(MAX232\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXINH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), LO input power =  $-7\text{dBm}$ ,  $50\Omega$  system, all measurements include matching component losses but not connector and trace losses,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Operating Characteristics (continued)


(MAX232\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), LO input power = -7dBm, 50Ω system, all measurements include matching component losses but not connector and trace losses,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Operating Characteristics (continued)










(MAX232\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), LO input power = -7dBm,  $50\Omega$  system, all measurements include matching component losses but not connector and trace losses,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Operating Characteristics (continued)

(MAX232\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), LO input power =  $-7\text{dBm}$ ,  $50\Omega$  system, all measurements include matching component losses but not connector and trace losses,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs


## Typical Operating Characteristics (continued)

(MAX2320 EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), LO input power =  $-7\text{dBm}$ ,  $50\Omega$  system, all measurements include matching component losses but not connector and trace losses,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)


**CELLULAR-BAND MIXER IIP3  
vs. RF INPUT LEVEL**




**CELLULAR-BAND MIXER IIP3  
vs. LO INPUT LEVEL**




**PCS-BAND HGHL MIXER IIP3  
vs. CURRENT**




**PCS-BAND HGHL MIXER IIP3  
vs. CURRENT**




**PCS-BAND MIXER IIP3  
vs. RF INPUT LEVEL**




**PCS-BAND MIXER IIP3  
vs. LO INPUT LEVEL**




**CELLULAR-BAND HGHL MIXER NOISE FIGURE  
vs. LO INPUT LEVEL**



**CELLULAR-BAND HGLL MIXER NOISE FIGURE  
vs. LO INPUT LEVEL**



**CELLULAR-BAND FM MIXER NOISE FIGURE  
vs. LO INPUT LEVEL**




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs


## Typical Operating Characteristics (continued)

(MAX232\_EV kit,  $V_{CC} = +2.75V$ ,  $f_{LNAINH} = f_{MIXNH} = 1960\text{MHz}$ ,  $f_{LNAINL} = f_{MIXNL} = 881\text{MHz}$ ,  $f_{LOHIN} = 1750\text{MHz}$ ,  $f_{LOLIN} = 1091\text{MHz}$  (digital modes),  $f_{LOLIN} = 991\text{MHz}$  (FM mode), LO input power =  $-7\text{dBm}$ ,  $50\Omega$  system, all measurements include matching component losses but not connector and trace losses,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.)


**PCS-BAND HGH1 MIXER NOISE FIGURE  
vs. LO INPUT LEVEL**




**PCS-BAND HGLL MIXER NOISE FIGURE  
vs. LO INPUT LEVEL**




**CELLULAR-BAND LO BUFFER OUTPUT LEVEL  
vs. INPUT LEVEL**




**CELLULAR-BAND 2nd AND 3rd HARMONICS  
vs. LO BUFFER OUTPUT**




**PCS-BAND LO BUFFER OUTPUT LEVEL  
vs. LO INPUT LEVEL**



**PCS-BAND 2nd AND 3rd HARMONICS  
LO BUFFER OUTPUT vs. LO INPUT LEVEL**



**PCS-BAND MIXER  
2x2 SPURIOUS REJECTION**



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Pin Description

PIN					NAME	FUNCTION
MAX2320 MAX2321 MAX2326	MAX2322	MAX2324	MAX2327	MAX2329		
1	1	—	1	1	LNAOUTH	High-Band LNA Output. Connect a pull-up inductor to V <sub>CC</sub> and an external series capacitor as part of the matching network.
—	—	—	—	2	PCSL/H	Logic Input. PCSL/H <+0.6V activates the PCS upper half-band signal path; PCSL/H >+2V activates the PCS lower half-band signal path.
2	—	2	2	3	LNAOUTL	Low-Band LNA Output. Connect a pull-up inductor to V <sub>CC</sub> and an external series capacitor as part of the matching network.
3	3	3	—	5	RLNA	LNA Bias-Setting Resistor Connection. For nominal bias, connect a 20kΩ resistor to ground. The resistor value controls the LNA's linearity in high-gain, high-linearity modes.
4	4	—	4	4	LNAINH	High-Band RF Input. Requires a blocking capacitor and a matching network. The capacitor may be used as part of the matching network.
—	—	4	—	—	MODEOUT	Logic Output. Indicates mode of operation. V <sub>MODEOUT</sub> = high in FM mode.
5	—	5	5	6	LNAINL	Low-Band RF Input. Requires a blocking capacitor and a matching network. The capacitor may be used as part of the matching network.
—	6	6	7	7	SHDN	Shutdown Logic Input. See <i>Detailed Description</i> for control modes.
6	—	—	6	—	BAND	Band-Select Logic Input. See <i>Detailed Description</i> for control modes.
7	7	7	—	8	LIN	Linearity-Select Logic Input. See <i>Detailed Description</i> for control modes.
8	8	8	—	9	GAIN	Gain-Select Logic Input. See <i>Detailed Description</i> for control modes.
—	—	—	8	—	MODE	Cellular-Band Mode Select Logic Input. See <i>Detailed Description</i> for control modes.
9	—	9	9	—	LOLIN	Low-Frequency LO Input. Used in FM mode on all parts and in cellular digital mode for MAX2320/MAX2324.
10	10	—	10	10	LOHIN	High-Frequency LO Input. For MAX2321, used in cellular digital mode and in PCS mode with the doubler active. For MAX2320/MAX2327/MAX2329, used in PCS mode without the doubler. For MAX2322, used with or without the doubler. For MAX2326, used in PCS mode and cellular digital mode with the divide-by-two.

# **Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs**

## **Pin Description (continued)**

<b>PIN</b>					<b>NAME</b>	<b>FUNCTION</b>
<b>MAX2320 MAX2321 MAX2326</b>	<b>MAX2322</b>	<b>MAX2324</b>	<b>MAX2327</b>	<b>MAX2329</b>		
11	11	—	11	11	LOHOUT	High-Frequency LO Buffer Output. Open-collector output requires pull-up inductor or pull-up resistor of 100Ω or less. Reactive match to the load delivers maximum power.
12	—	12	12	—	LOLOUT	Low-Frequency LO Buffer Output. Open-collector output requires pull-up inductor or pull-up resistor of 100Ω or less. Reactive match to the load delivers maximum power.
13	—	13	13	—	FMOUT	FM Mixer Output. Requires a pull-up inductor to VCC and a series capacitor as part of the matching network.
—	13	—	—	13	LOX2	LO Doubler Logic Input. Drive LOX2 high to enable the LO doubler.
14	14	14	14	14	VCC	Power Supply. Bypass with a 1000pF capacitor as close to the pin as possible.
15	15	15	15	12	BUFFEN	LO Output Buffer Enable. The LO buffers are controlled separately from the rest of the IC. Drive BUFFEN high to power up the LO output buffer associated with the selected LO input port.
16, 17	16, 17	16, 17	—	15, 16	CDMA-, CDMA+	CDMA Mixer Differential Outputs. Require pull-up inductors and series capacitors as part of the matching network.
—	—	—	16, 17	—	IFOUT+, IFOUT-	Mixer Differential Outputs. Require pull-up inductors and series capacitors as part of the matching network.
18	18	18	18	17	RBIAS	Bias-Setting Resistor Connection. For nominal bias, connect 20kΩ resistor to ground. The resistor value controls the digital LNA's linearity in low-gain, digital, or FM mode, and controls the mixers in all modes.
19	—	19	19	18	MIXNL	Low-Band Mixer Input. Requires a blocking capacitor and a matching network. The capacitor may be used as part of the matching network.
20	20	—	20	20	MIXNH	High-Band Mixer Input. Requires a blocking capacitor and a matching network. The capacitor may be used as part of the matching network.
—	2, 5, 9, 12, 19	1, 10, 11, 20	3	19	N.C.	No Connection. Do not make any connection to these pins.
Slug	Slug	Slug	Slug	Slug	GND	Ground Reference for RF, DC, and Logic Inputs. Solder the slug evenly to the board ground plane.

**MAX2320/21/22/24/26/27/29**

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Detailed Description

### Low-Noise Amplifier (LNA)

Within its operating bands, each device in the MAX2320 family (except the MAX2327) has three modes of low-noise amplifier (LNA) operation: high gain, high linearity (HGHL); high gain, low linearity (HGLL); and low gain, high linearity (LGHL). The logic inputs control the LNA mode as described in the AC Electrical Characteristics. Use HGHL mode when extra-high LNA linearity is required for cross-modulation suppression. Use HGLL mode when the transmitter is off and cross-modulation is not a concern. When the LNA changes modes, the input VSWR change is minimal. Use LGHL mode for receiving large signals and when high sensitivity is not required. The MAX2327 LNA has only an HGLL mode. Adjust the HGHL mode LNA linearity by changing RRLNA, and adjust linearity of the other modes by changing RRBIAS.

### Downconverter

The downconverters in these devices are double-balanced mixers. The PCS-band mixer and digital cellular-band mixer share the same IF output ports. The cellular band FM mixer has its own IF output to feed a different filter. Adjust the downconverter linearity and current by changing RRBIAS (see *Typical Operating Characteristics*). When the linearity requirement is high, the mode

control inputs increase the current in the downconverter. When the linearity requirement is not high, the current is lower.

### LO Output Buffers

The BUFFEN logic input turns the open-collector LO output buffers on and off. This feature saves current if the buffers are not required.

### Operational Modes

Each device has logic input pins that control the different operational modes listed in Tables 1–5.

### MAX2320/MAX2321/MAX2326 Operation

The MAX2320/MAX2321/MAX2326 are dual-band, triple-mode receivers that amplify and downconvert cellular- and PCS-band signals. They consist of cellular and PCS low-noise amplifiers (LNA); cellular digital, cellular FM, and PCS digital mixers; and cellular and PCS LO buffers. The MAX2321 has a LO frequency doubler on-chip, so a single cellular-band VCO can be used for both the cellular- and PCS-band mixers. Selecting the PCS path activates the LO frequency doubler. The MAX2326 has an LO divide-by-two circuit, so a single PCS-band VCO can be used for both the cellular and PCS mixers. Selecting the cellular path activates the LO divide-by-two circuit. Three logic input pins—BAND, GAIN, and LIN—control eight operational modes of the LNAs and mixers. The modes are summarized in Table 1.

**Table 1. MAX2320/MAX2321/MAX2326 Operational Modes**

DESCRIPTION	BAND	GAIN	LIN
Shutdown. The entire part is shut down except for the LO buffer, which is controlled by BUFFEN.	L	L	L
Low-Gain, High-Linearity (LGHL) PCS Mode. The PCS LNA and mixer are in LGHL mode.	L	L	H
High-Gain, Low-Linearity (HGLL) PCS Mode. The LNA and mixer are in HGLL mode.	L	H	L
High-Gain, High-Linearity (HGHL) PCS Mode. The LNA and mixer are in HGHL mode.	L	H	H
High-Gain, Low-Linearity (HGLL) Cellular FM Mode. The cellular LNA is in HGLL mode. The FM mixer and associated LO buffer are selected.	H	L	L
Low-Gain, High-Linearity (LGHL) Cellular Digital Mode. The cellular LNA and mixer are in LGHL mode.	H	L	H
High-Gain, Low-Linearity (HGLL) Cellular Digital Mode. The cellular LNA and mixer are in HGLL mode.	H	H	L
High-Gain, High-Linearity (HGHL) Cellular Digital Mode. The cellular LNA and mixer are in HGHL mode.	H	H	H

**Note:** L = Logic Low; H = Logic High

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## MAX2322 Operation

The MAX2322 is a lower-cost PCS-only version that can be installed as a drop-in replacement for the dual-band versions. It consists of a PCS LNA, PCS mixer, pin-selectable LO frequency doubler, and LO buffer. Logic input  $\overline{SHDN} = V_{CC}/GND$  turns on/off the entire IC except the LO buffer. The LOX2 logic input controls the LO frequency doubler. LOX2 = GND disables the doubler when using a PCS band VCO, and LOX2 = V<sub>CC</sub> activates the doubler when using a cellular-band VCO. GAIN and LIN logic inputs control the MAX2322's three operational modes, as summarized in Table 2.

## MAX2324 Operation

The MAX2324 is a lower-cost cellular-only version that can be installed as a drop-in replacement for the dual-band versions. It consists of a cellular LNA, cellular digital mixer, cellular FM mixer, and LO buffer. A SHDN logic input turns on/off the entire IC except the LO buffer. GAIN and LIN logic inputs control the MAX2324's three operational modes, as summarized in Table 3.

## MAX2327 Operation

The MAX2327 is similar to the MAX2320 except it only features an HGLL mode, and either LO output buffer is selectable during shutdown. It consists of PCS and cellular LNAs; PCS, cellular digital, and cellular FM mixers; and PCS and cellular LO buffers. A SHDN logic input turns on/off the entire IC except the LO buffer. BAND and MODE logic inputs control the MAX2327's three operational modes, as summarized in Table 4.

## MAX2329 Operation

The MAX2329 is a receiver for the PCS band, featuring two independent signal paths. It is ideal for systems using half-band filters and/or duplexers for superior spurious suppression. It consists of two PCS LNAs, two PCS mixers, and an LO buffer. A SHDN logic input turns on/off the entire IC except the LO buffer. PCSL/H, GAIN, and LIN logic inputs control the MAX2329's six operational modes, as summarized in Table 5.

## Applications Information

### Cascaded LNA/Mixer Performance

The LNA and mixer design aims at optimizing cascaded performance in all gain and linearity modes. In high-gain, high-linearity mode, both the LNA and mixer have a low noise figure, high gain, and high linearity. The LNA has high gain to minimize the noise contribution of the mixer, thus increasing the receiver's sensitivity and extra-high linearity for superior cross-modulation suppression. The high-gain, low-linearity mode is used

**Table 2. MAX2322 Operational Modes**

OPERATIONAL MODE	GAIN	LIN
Not used.	L	L
Low-Gain, High-Linearity (LGHL) PCS Mode. The LNA and mixer are in LGHL mode.	L	H
High-Gain, Low-Linearity (HGLL) PCS Mode. The LNA and mixer are in HGLL mode.	H	L
High-Gain, High-Linearity (HGHL) PCS Mode. The LNA and mixer are in HGHL mode.	H	H

**Note:** L = Logic Low; H = Logic High

**Table 3. MAX2324 Operational Modes**

OPERATIONAL MODE	GAIN	LIN
FM Mode. The LNA is in HGLL mode. The FM mixer and the associated LO buffer are selected.	L	L
Low-Gain, High-Linearity (LGHL) Cellular Mode. The LNA and digital mixer are in LGHL mode.	L	H
High-Gain, Low-Linearity (HGLL) Cellular Mode. The LNA and digital mixer are in HGLL mode.	H	L
High-Gain, High-Linearity (HGHL) Cellular Mode. The LNA and digital mixer are in HGHL mode.	H	H

**Note:** L = Logic Low; H = Logic High

**Table 4. MAX2327 Operational Modes**

OPERATIONAL MODE	BAND	MODE
Not used.	L	L
Digital PCS Mode. The LNA and mixer are in HGLL mode.	L	H
FM Mode. The cellular FM mixer is selected.	H	L
Digital Cellular Mode. The cellular digital mixer is selected.	H	H

**Note:** L = Logic Low; H = Logic High

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

when the transmitter is off and cross-modulation is not a concern. In low-gain, high-linearity mode, the received signal is strong enough that linearity is the primary concern. The LNA gain is reduced for higher system linearity. Tables 6 and 7 summarize the cascaded performance.

## S Parameters

The S parameters are listed in Tables 8–12. An electronic copy is also available at [www.maxim-ic.com/MAX2320/S\\_table/](http://www.maxim-ic.com/MAX2320/S_table/).

## Layout Considerations

Keep RF signal lines as short as possible to minimize losses and radiation. Use high-Q components for the LNA input matching circuit to achieve the lowest possible noise figure. At the digital mixer outputs, keep the differential signal lines together and of equal length to ensure signal balance. For best gain and noise performance, solder the slug evenly to the board ground plane.

**Table 5. MAX2329 Operational Modes**

OPERATIONAL MODE	PCSL/H	GAIN	LIN
Not used	L	L	L
High Half-Band, Low-Gain, High-Linearity (LGHL) Mode	L	L	H
High Half-Band, High-Gain, Low-Linearity (HGLL) Mode	L	H	L
High Half-Band, High-Gain, High-Linearity (HGHL) Mode	L	H	H
Not used	H	L	L
Low Half-Band, Low-Gain, High-Linearity (LGHL) Mode	H	L	H
Low Half-Band, High-Gain, Low-Linearity (HGLL) Mode	H	H	L
Low Half-Band, High-Gain, High-Linearity (HGHL) Mode	H	H	H

**Note:** L = Logic Low; H = Logic High

**Table 6. Typical Cascaded Performance of Cellular-Band Receiver with 3dB Interstage Filter Loss**

PARAMETER	HIGH GAIN, HIGH LINEARITY	HIGH GAIN, LOW LINEARITY	LOW GAIN, HIGH LINEARITY	FM
Conversion Power Gain	24dB	23dB	9dB	24dB
Noise Figure	2.52dB	2.43dB	12dB	3dB
Third-Order Input Intercept	-8dBm	-10dBm	+6dBm	-10dBm

**Table 7. Typical Cascaded Performance of PCS-Band Receiver with 3dB Interstage Filter Loss**

PARAMETER	HIGH GAIN, HIGH LINEARITY	HIGH GAIN, LOW LINEARITY	LOW GAIN
Conversion Power Gain	24dB	23dB	8.8dB
Noise Figure	2.7dB	2.9dB	12.5dB
Third-Order Input Intercept	-8dBm	-9.5dBm	+6.6dBm

# **Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs**

**Table 8. Cellular LNA S Parameters in High-Gain, High-Linearity Mode**

FREQUENCY (MHz)	S11 (mag)	S11 (phase)	S21 (mag)	S21 (phase)	S12 (mag)	S12 (phase)	S22 (mag)	S22 (phase)
700	0.579	-74.8	4.63	92.1	0.085	60.9	0.714	-34.7
750	0.548	-78.4	4.39	87.9	0.089	60.6	0.696	-35.9
800	0.534	-81.2	4.13	84.4	0.0908	60	0.689	-36.6
850	0.52	-83.7	3.88	81.9	0.096	60.1	0.683	-37.6
900	0.51	-86.1	3.7	79.4	0.099	58.8	0.677	-38.3
950	0.503	-88.5	3.5	76.6	0.104	58.3	0.674	-39.3
1000	0.496	-90.6	3.3	74.9	0.109	59.1	0.669	-40.8

**Table 9. PCS LNA S Parameters in High-Gain, High-Linearity Mode**

FREQUENCY (MHz)	S11 (mag)	S11 (phase)	S21 (mag)	S21 (phase)	S12 (mag)	S12 (phase)	S22 (mag)	S22 (phase)
1700	0.46	-112	4.22	86	0.077	77	0.64	-51
1750	0.446	-113	4.07	88	0.082	77	0.64	-52
1800	0.44	-113	4.18	88	0.086	76	0.643	-52
1850	0.439	-113	4.23	84	0.09	77	0.657	-53
1900	0.434	-114	3.9	82	0.093	72	0.68	-55
1950	0.43	-115	3.82	84	0.09	75	0.673	-57
2000	0.423	-116	3.85	83	0.094	76	0.681	-58
2050	0.407	-115	3.82	83	0.098	76	0.69	-59
2100	0.391	-112	3.82	81	0.103	74	0.7	-61
2150	0.405	-106	3.68	79	0.101	71	0.695	-63
2200	0.467	-104	3.56	81	0.093	73	0.677	-64
2250	0.503	-107	3.67	82	0.094	79	0.683	-63
2300	0.525	-110	3.83	81	0.099	82	0.705	-64
2350	0.54	-112	3.88	78	0.1	86	0.727	-66
2400	0.55	-113	3.9	75	0.106	93	0.739	-67
2450	0.571	-113	3.79	73	0.126	99	0.754	-69
2500	0.614	-113	3.78	74	0.158	100	0.769	-71

**MAX2320/21/22/24/26/27/29**

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

**Table 10. Cellular Mixer S11 in High-Gain, High-Linearity Mode**

FREQUENCY (MHz)	S11 (mag)	S11 (phase)
700	0.853	-35.8
750	0.849	-38
800	0.846	-40.2
850	0.844	-42.2
900	0.843	-44.1
950	0.842	-46.3
1000	0.842	-48.5

**Table 11. PCS Mixer S11 in High-Gain High-Linearity Mode**


FREQUENCY (MHz)	S11 (mag)	S11 (phase)
1700	0.865	-62
1750	0.864	-63
1800	0.865	-64
1850	0.867	-64
1900	0.863	-65
1950	0.862	-65
2000	0.861	-66
2050	0.879	-67
2100	0.86	-68
2150	0.858	-68
2200	0.854	-69
2250	0.85	-71
2300	0.845	-72
2350	0.838	-74
2400	0.83	-76
2450	0.825	-78
2500	0.805	-82

**Table 12. Mixer IF port S22**

FREQUENCY (MHz)	DIGITAL MIXER		FREQUENCY (MHz)	FM MIXER	
	S22 (mag)	S22 (phase)		S22 (mag)	S22 (phase)
50	0.999	-1.10	50	0.999	-1.69
100	0.999	-2.26	70	0.998	-2.38
110	0.999	-2.46	85	0.998	-2.92
130	0.998	-2.89	100	0.997	-3.38
150	0.998	-3.35	110	0.997	-3.71
200	0.998	-4.45	150	0.996	-4.97
210	0.998	-4.67	200	0.995	-6.49
250	0.997	-5.48	250	0.995	-7.82
300	0.997	-6.48	300	0.994	-9.06
350	0.996	-7.47	350	0.993	-10.28
400	0.996	-8.36	400	0.992	-11.40


# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Application Circuits




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Application Circuits (continued)




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Application Circuits (continued)




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Application Circuits (continued)




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Application Circuits (continued)



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs


## Typical Application Circuits (continued)



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs


## Typical Application Circuits (continued)

**MAX2329**  
(PCS BAND WITH DUAL INPUTS, HALF-BAND PCS FILTER COMPATIBLE)



# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Typical Application Circuits (continued)




# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs


## ***Pin Configurations (continued)***

**MAX2320/21/22/24/26/27/29**


TOP VIEW




TSSOP



TSSOP



TSSOP




TSSOP

## ***Chip Information***

TRANSISTOR COUNT: 1315

# Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs

## Package Information



S Y B D L	COMMON DIMENSIONS			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	—	1.10	.043	
A <sub>1</sub>	0.05	0.15	.002	.006
A <sub>2</sub>	0.85	0.95	.033	.037
b	0.19	0.30	.007	.012
b <sub>1</sub>	0.19	0.25	.007	.010
c	0.090	0.20	.0035	.008
c <sub>1</sub>	0.090	0.135	.0035	.0053
D SEE VARIATIONS	SEE VARIATIONS			
E	4.30	4.50	.169	.177
e	0.65	BSC	.026	BSC
H	6.25	6.50	.246	.256
L	0.50	0.70	.020	.028
N SEE VARIATIONS	SEE VARIATIONS			
Y	2.85	3.15	.112	.124
α	0°	8°	0°	8°

JEDEC MO-153	N	VARIATIONS			
		MILLIMETERS		INCHES	
		MIN.	MAX.	MIN.	MAX.
AB	14	D	4.90	.510	.193
AC	16	D	4.90	.510	.193
AC-EP	16	D	4.90	.510	.193
	X	2.85	3.15	.112	.124
AD	20	D	6.40	6.60	.252
AD-EP	20	D	6.40	6.60	.252
	X	4.00	4.34	.157	.171
AE	24	D	7.70	7.90	.303
AF	28	D	9.60	9.80	.378
AF-EP	D	9.60	9.80	.378	.386
	X	5.35	5.65	.211	.222

<b>MAXIM</b>	
PROPRIETARY INFORMATION	
TITLE: PACKAGE OUTLINE, TSSOP, 4.40mm BODY, 0.65mm PITCH	
APPROVAL	DOCUMENT CONTROL NO.
21-0066	REV C 1/1

TSSOP.EPS

**Adjustable, High-Linearity,  
SiGe Dual-Band LNA/Mixer ICs**

NOTES

**MAX2320/21/22/24/26/27/29**

# **Adjustable, High-Linearity, SiGe Dual-Band LNA/Mixer ICs**

## **NOTES**

*Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.*

**36** **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 1999 Maxim Integrated Products

Printed USA

**MAXIM** is a registered trademark of Maxim Integrated Products.