

Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz



TECHNICAL DATA SHEET

PE8010

Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz

Configuration	
Bias Type	Zero Biased Detector
Detector Polarity	Negative
Body Style	Straight
RF Input Connector	SMA Male
RF Input Impedance	50 Ohms
Video Output Connector	SMA Female
Electrical Specifications	
Frequency Range, GHz	0.01 to 2
Voltage Sensitivity, mV/mW	500
Tangential Signal Sensitivity	-52
Maximum VSWR	1.2:1
Flatness, dB Maximum Input Power, Watts	0.2 23
Video Capacitance, pF	470
video Capacitance, pr	470
Mechanical Specifications	
Temperature	
Operating Range, deg C	0 to +90
opolaung hango,aog o	0.00.000
Size	
Length, in [mm]	1.21 [30.73]
Width/Dia., in [mm]	0.31 [7.87]
RF Input	
Туре	SMA Male
Video Output	
Туре	SMA Female
Compliance Cartifications (visit www.Destance), can far surrent desurrent)	
Compliance Certifications (visit www.Pasternack.com for or	,
RoHS Compliant	Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz PE8010

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com







Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz



TECHNICAL DATA SHEET

PE8010

Plotted and Other Data Notes:

Values at 25 °C, sea level

Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz PE8010

URL: http://www.pasternack.com/50-ohm-sma-zero-biased-detector-negative-10-mhz-2000-mhz-pe8010-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



ISO 9001 : 2008 Registered

PE8010 CAD Drawing

Zero Biased Detector With 50 Ohm SMA Male to SMA Female Video Out Operating From 10 MHz to 2 GHz

