

3637C150MT Product Details

 [Live Product Chat](#)

Quick Links

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)



3637C150MT
(3-1676951-6)
TE Internal Number: 3-1676951-6
 [Active](#)

Inductors

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Inductor
- Inductor Type = Shielded Power Wirewound
- Lead Type = Surface Mount Terminals
- Wirewound
- Inductance = 15 ?H

[View all Features](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: SHIELDED SMD POWER INDUCTORS SERIES 3637 (PDF, English) Catalog Pages/Data Sheets: Shielded SMD Power Inductor - Type 3637 Series - Tyc... (PDF, English) Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available List all Documents	Additional Information: Product Line Information Related Products: Tooling

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: Product Type = Inductor - Inductor Type = Shielded Power Wirewound Element = Wirewound Shielded = Yes Electrical Characteristics: Inductance (?H) = 15 DC Resistance (?) = 0.05 Current, Maximum (mA) = 4000 Quality Factor = 45 Package Type = Taped and Reeled - Tolerance (%) = 20 Body Related Features: Lead Type = Surface Mount Terminals Series = 3637 Package, Component Size = 13mm Diameter Mount Style = Surface Mount	Industry Standards: RoHS/ELV Compliance = RoHS compliant, ELV compliant Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C - RoHS/ELV Compliance History = Always was RoHS compliant Operation/Application: Application = Power Circuitry Other: - Brand = Sigma Inductors