



General ordering data

Order No.	1815670300
Part designation	SAIL-M12WM12W-3-3.0U
Version	Sensor/Actuator line, Connecting line, LED: No, 3.00 m, PUR/PVC
EAN	4032248403417
Qty.	1 pc(s).

Technical data

Ambient temperature, max.	80 °C
Ambient temperature, min.	-30 °C
Cable diameter, max.	5 mm
Cable diameter, min	4.6 mm
Connection cross-section	0,34
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	M12
Core cross-section	0.34 mm ²
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	250 V DC / 300 V AC
Sheathing colour	black
Wiring diagram	
jumpered	No
No. of poles	3
Version	pin, 90° - socket 90°
Cable length	3 m

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-06-00-00
eClass 5.0	27-06-91-90
eClass 5.1	27-06-91-90

Similar products

Order No.	Part designation	Version
1815670060	SAIL-M12WM12W-3-0.6U	Sensor/Actuator line, Connecting line, LED: No, 0.60 m, PUR/PVC
1815670150	SAIL-M12WM12W-3-1.5U	Sensor/Actuator line, Connecting line, LED: No, 1.50 m, PUR/PVC
1815671000	SAIL-M12WM12W-3-10U	Sensor/Actuator line, Connecting line, LED: No, 10.00 m, PUR/PVC
1815670500	SAIL-M12WM12W-3-5.0U	Sensor/Actuator line, Connecting line, LED: No, 5.00 m, PUR/PVC