

D. Audio Power Amplifier

Device	Package	Vcc (V)	Output Power		Use			Remark
			RL=4 ohm	RL=8 ohm	R/C	Car	Hi-Fi	
KA2201	8 DIP	6		0.5W	*			Vcc=3~14V
		9		1.2W				
KA2206	12 DIP/F	9	2.3W × 2		*			Vcc=4.5~11V
KA22065	12 SIP H/S	9	4.6W × 2		*			Vcc=6~15V
† KA22066	12 DIP/F	9	4.0W × 2		*			Vcc=4.5~11V
KA2214	14 DIP H/S	9		1.2W × 2	*			Vcc=3~16V
KA2209	8 DIP	3	110mW × 2		*			Vcc=1.8~9V
KA22103	17 ZSIP H/S	13.2	19W × 2			*		Vcc=9~18V
KA2212	9 SIP	6		0.5W	*			Vcc=3.5~12V
LM386/S	8 DIP/9 SIP	6		0.325W	*			Vcc=4~12V
KA2213	14 DIP H/S	6	1W		*			Included
KA22130	16 DIP	6	1W		*			Pre-Amp with ALC
KA22131	24 SOP	3	69mW × 2 (RL=16Ω)		*			Vcc=1.8~3.6V Included Auto Reverse Pre-AMP
KA22134	16 DIP	3	27mW × 2 (RL=32Ω)		*			Vcc=1.8~6V Dual PRE + POWER AMP with Volume Control
KA22135	22 SDIP	3	28mW × 2 (RL=32Ω)		*			Vcc=2~7.5V Dual PRE + POWER AMP and DC Motor Speed Controller
KA22136	28 SOP	3	28mW × 2 (RL=32Ω)		*			Vcc=2~5V Dual PRE+POWER AMP with Volume Control and DC Motor Speed Controller

† New Product