



MMBD101/MMBD352/MMBD353/MMBD354/MMBD355

SURFACE MOUNT HIGH FREQUENCY SCHOTTKY DIODE

VOLTAGE 7.0 Volts **POWER** 250mWatts


SOT-23 Unit: inch (mm)

FEATURES

- Low Capacitance, Minimizing Insertion Losses in VHF Applications
- Low V_F : 0.5V (Typ) at $I_F = 10\text{mA}$
- Extremely Fast Switching Speed
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: SOT-23 plastic case.
- Terminals : Solderable per MIL-STD-750, Method 2026
- Weight: approximately 0.008gram



MAXIMUM RATINGS

Parameter	Symbol	MMBD101	MMBD352	MMBD353	MMBD354	MMBD355	Units
Marking Code	-	101	352	353	354	355	-
Reverse Voltage	V_R	7					V
Forward Power Dissipation	P_F	250					mW
Junction Temperature Range	T_J	-55 to +125					°C
Storage Temperature Range	T_{STG}	-55 to +150					°C
Circuit Figure	-	SINGLE	SERIES	SERIES (Rev)	COMMON CATHODE	COMMON ANODE	-

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Units
Thermal Resistance , Junction to Ambient	$R_{\theta JA}$	400	°C/W

NOTE:

1. FR-5 Board = 1.0X0.75X0.062 in.




Fig.14




Fig.17




Fig.33




Fig.16




Fig.15






MMBD101/MMBD352/MMBD353/MMBD354/MMBD355

ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=10\mu\text{A}$	7.0	10	-	V
Reverse Leakage Current	I_R	$V_R=3.0\text{V}$	-	-	0.25	μA
Forward Voltage	V_F	$I_F=10\text{mA}$	-	0.5	0.6	V
Total Capacitance	C_J	$f=1.0\text{MHz}$, $V_R=0\text{V}$	-	0.88	1.0	pF


ELECTRICAL CHARACTERISTICS CURVES





MMBD101/MMBD352/MMBD353/MMBD354/MMBD355

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2007

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.