


PARAMETERS		SYMBOL	MAX	MIN	TYP.	UNITS
POWER DISSIPATION	$P_d$	100	--			mW
FORWARD VOLTAGE	$V_f$	2.8	1.8	2.1		V
REVERSE VOLTAGE	$V_r$	5				V
EMISSION WAVELENGTH	$\lambda_p$			590		nm
AVE. FORWARD CURRENT	$I_{af}$	30	--			mA
LUMINOUS INTENSITY	$I_v$		5.0			mcad



CIRCUIT: SPDT  
CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NO. FOR REF. ONLY
  4. RATING: 12mA @24V
  5. FIXED CONTACT/MOVING CONTACT:  
COPPER ALLOY W/GOLD PLATE
  6. CONTACT BOUNCE: <5m SEC.
  7. CONTACT RESISTANCE: <50milli-OHMS

**E-SWITCH®**

C	11908	REVISED AND REDRAWN	2/5/02	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE	5500 STD BODY 3
SCALE	2:1
DATE	2/5/02
DR	CJB
DWG	R010020
REV	C

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED