



SPC4533W

N & P Pair Enhancement Mode MOSFET

DESCRIPTION

The SPC4533W is the N- and P-Channel enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology. This high density process is especially tailored to minimize on-state resistance and provide superior switching performance. These devices are particularly suited for low voltage applications such as notebook computer power management and other battery powered circuits where high-side switching, low in-line power loss, and resistance to transients are needed.



FEATURES

- ◆ N-Channel
 - 30V/10A,R_{D(S)}(ON)= 25mΩ@V_{GS}= 10V
 - 30V/8.0A,R_{D(S)}(ON)= 36mΩ@V_{GS}= 4.5V
- ◆ P-Channel
 - 30V/-6.0A,R_{D(S)}(ON)= 42mΩ@V_{GS}= -10V
 - 30V/-3.0A,R_{D(S)}(ON)= 78mΩ@V_{GS}= -4.5V
- ◆ Super high density cell design for extremely low RDS (ON)
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ SOP – 8P package design

APPLICATIONS

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- LCD Display inverter

PIN CONFIGURATION(SOP – 8P)



PART MARKING



A : Lot Code
B : Date Code

PIN DESCRIPTION



SPC4533W

N & P Pair Enhancement Mode MOSFET

Pin	Symbol	Description
1	S1	Source 1
2	G1	Gate 1
3	S2	Source 2
4	G2	Gate 2
5	D2	Drain 2
6	D2	Drain 2
7	D1	Drain 1
8	D1	Drain 1

ORDERING INFORMATION

Part Number	Package	Part Marking
SPC4533WS8RGB	SOP- 8P	SPC4533W

※ SPC4533WS8RGB : 13" Tape Reel ; Pb – Free ; Halogen - Free

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical		Unit
		N-Channel	P-Channel	
Drain-Source Voltage	V _{DSS}	30	-30	V
Gate –Source Voltage	V _{GSS}	±20	±20	V
Continuous Drain Current(T _J =150°C)	T _A =25°C	ID	10	A
	T _A =70°C		6	
Pulsed Drain Current	I _{DM}	20	-12	A
Power Dissipation	T _A =25°C	P _D	2.0	W
Operating Junction Temperature	T _J	-55/150		°C
Storage Temperature Range	T _{STG}	-55/150		°C
Thermal Resistance-Junction to Ambient	R _{θJA}	80	80	°C/W



SPC4533W

N & P Pair Enhancement Mode MOSFET

N CHANNEL ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V(BR)DSS	VGS=0V, ID=250uA	30			V
Gate Threshold Voltage	VGS(th)	VDS=VGS, ID=250uA	1.0		2.5	
Gate Leakage Current	IGSS	VDS=0V, VGS=±20V			±100	nA
Zero Gate Voltage Drain Current	IDSS	VDS=24V, VGS=0V			1	uA
		VDS=24V, VGS=0V TJ=55°C			5	
On-State Drain Current	ID(on)	VDS≥5V, VGS =10V	25			A
Drain-Source On-Resistance	RDS(on)	VGS= 10V, ID=10A		18	25	mΩ
		VGS=4.5V, ID=5.6A		25	36	
Forward Transconductance	gfs	VDS=15V, ID=10A		10		S
Diode Forward Voltage	VSD	IS=1A, VGS =0V			1.2	V
Dynamic						
Total Gate Charge	Qg	VDS=20V, VGS=4.5V ID= 10A		7.2		nC
Gate-Source Charge	Qgs			1.4		
Gate-Drain Charge	Qgd			2.2		
Input Capacitance	Ciss	VDS=15V, VGS=0V f=1MHz		570		pF
Output Capacitance	Coss			81		
Reverse Transfer Capacitance	Crss			65		
Turn-On Time	td(on)	VDD=12V, ID=5.0A, VGEN=10V, RG=3.3Ω		4.1		nS
	tr			9.8		
Turn-Off Time	td(off)			15.5		
	tf			6.1		



SPC4533W

N & P Pair Enhancement Mode MOSFET

P CHANNEL ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, ID=-250uA	-30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , ID=-250uA	-1.0		-2.5	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-24V, V _{GS} =0V			-1	uA
		V _{DS} =-24V, V _{GS} =0V T _J =55°C			-5	
On-State Drain Current	I _{D(on)}	V _{DS} ≤-5V, V _{GS} =-10V	-6			A
Drain-Source On-Resistance	R _{DSS(on)}	V _{GS} =-10V, ID=-6A		0.035	0.042	Ω
		V _{GS} =-4.5V, ID=-3A		0.065	0.078	
Forward Transconductance	g _{fs}	V _{DS} =-10.0V, ID=-6A		6		S
Diode Forward Voltage	V _{SD}	I _S =-6A, V _{GS} =0V			-1.2	V
Dynamic						
Total Gate Charge	Q _g	V _{DS} =-20V, V _{GS} =-4.5V ID=-6A		6.4		nC
Gate-Source Charge	Q _{gs}			2.7		
Gate-Drain Charge	Q _{gd}			3.1		
Input Capacitance	C _{iss}	V _{DS} =-24V, V _{GS} =0V f=1MHz		650		pF
Output Capacitance	C _{oss}			270		
Reverse Transfer Capacitance	C _{rss}			104		
Turn-On Time	t _{d(on)}	V _{DD} =-12V, ID=-5.0A, V _{GEN} =-10V R _G =3.3Ω		9		ns
	t _r			16		
Turn-Off Time	t _{d(off)}			21		
	t _f			22		



SPC4533W N & P Pair Enhancement Mode MOSFET

N CHANNEL TYPICAL CHARACTERISTICS




Fig. 1 Typical Output Characteristics




Fig. 2 On-Resistance vs. Gate Voltage




Fig. 3 Forward Characteristics of Diode




Fig. 4 Gate Charge Characteristics




Fig. 5 V_{GS} vs. Junction Temperature




Fig. 6 On-Resistance vs. Junction Temperature



SPC4533W

N & P Pair Enhancement Mode MOSFET

N CHANNEL TYPICAL CHARACTERISTICS




Fig. 7 Typical Capacitance Characteristics




Fig. 8 Maximum Safe Operation Area




Fig. 9 Effective Transient Thermal Impedance




Fig. 10 Switching Time Waveform




Fig. 11 Unclamped Inductive Waveform



SPC4533W

N & P Pair Enhancement Mode MOSFET

P CHAENL TYPICAL CHARACTERISTICS




Fig. 1 Typical Output Characteristics




Fig. 2 On-Resistance vs. Gate Voltage




Fig. 3 Forward characteristics of Diodes




Fig. 4 Gate Charge Characteristics




Fig. 5 Vgs vs. Junction Temperature




Fig. 6 On-Resistance vs Junction Temp



SPC4533W

N & P Pair Enhancement Mode MOSFET

P CHANNEL TYPICAL CHARACTERISTICS




Fig. 7 Typical Capacitance Characteristics




Fig. 8 Maximum Safe Operation Area




Fig. 9 Effective Transient Thermal Impedance




Fig. 10 Switching Time Waveform








Fig. 11 Unclamped Inductive Waveform



SPC4533W

N & P Pair Enhancement Mode MOSFET

SOP- 8 PACKAGE OUTLINE



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	—	0.25	0.004	—	0.010
A2	—	1.45	—	—	0.057	—
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	—	1.27	—	—	0.050	—
L	0.38	0.71	1.27	0.015	0.028	0.050
$\triangle y$	—	—	0.076	—	—	0.003
θ	0°	—	8°	0°	—	8°



SPC4533W

N & P Pair Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation

©2011 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

©<http://www.syncpower.com>