


STC

MOSFETS


DUAL N CHANNEL POWER MOSFETS

PACKAGE
6 PIN SIP



DEVICE TYPE	BV _{DSS} VOLTS	RDS (ON) @0.5 I _D OHMS	I _D CONTINUOUS OHMS	P _D WATTS	CHIP
SND600	600	0.6	11.0	125	IXTD15N60
SND500	500	0.4	14.0	125	IRFC450
SND460	600	0.25	20.0	125	IXTD21N50
SND410	400	0.2	20.0	125	IRFC360
SND400	400	0.3	17.0	125	IRFC350
SND310	300	.09	22.0	125	IXTD40N30
SND300	300	.1	17.0	125	IXTD35N30
SND200	200	0.09	30.0	125	IRFC250
SND100	100	0.06	30.0	125	IRFC150


TO-61
ISOLATED



DEVICE TYPE	BV _{DSS} VOLTS	RDS (ON) @0.5 I _D OHMS	I _D CONTINUOUS OHMS	P _D WATTS	CHIP
SNF80504	500	0.4	13.0	150	IRFC450
SNF80403	400	0.3	15.0	150	IRFC450
SNF80201	200	0.09	30.0	150	IRFC250
SNF80101	100	0.06	30.0	150	IRFC150

P CHANNEL POWER MOSFETS

PACKAGE
TO-61
ISOLATED



DEVICE TYPE	BV _{DSS} VOLTS	RDS (ON) @0.5 I _D OHMS	I _D CONTINUOUS OHMS	P _D WATTS	CHIP
SPF82208	-200	-6.5	0.8	10	IRFC9230
SPF82103	-100	-12.0	0.3	75	IRFC9130

Electrical Characteristics at 25°C unless otherwise noted.