



a time and place...
for everything

Wi-Sys Communications Inc.

WS2803 RF Switch

Applications:

- ◆ L-Band / S-Band
- ◆ 802.11 WiFi / 2.4 GHz ISM
- ◆ Test & Measurement Equipment



The WS2803 is a general-purpose, high performance, high isolation solid-state L-Band and S-Band RF coaxial switch. The high switching speed also allows for the user to send bursts of RF signal, making it suitable for testing RF detectors, power regulated amplifiers or any other devices operated under rapidly varying RF levels.

Technical Specifications

Electrical

- ◆ Voltage Supply: 4 to 15 VDC
- ◆ Frequency range: 100 MHz to 2.5 GHz
- ◆ Switch Speed: 100 ns typ. (600 ns max.)
- ◆ Impedance: 50 Ohms
- ◆ 1dB Compression point: 27 dBm @ 0.1 – 2GHz
- ◆ VSWR: 1.5 max (S_{11} and S_{22})
- ◆ I_{p3} : 44dBm @ 1900MHz
- ◆ Switch Control Voltage: 0 V to 5V max
 - V_{IL} : 1 V max
 - V_{IH} : 2.3 V min
- ◆ Insertion Loss: 2 dB Max. @ 0.1 to 1.0 GHz
2.5 dB Max. @ 1.0 to 2.5 GHz
- ◆ Isolation: 50 dB Max. @ 0.1 to 2.5 GHz

Mechanical

- ◆ Connectors: RF: SMA Female
- ◆ DC Voltage Supply: 2.1 mm Jack
- ◆ Operating Temp: -40C to +85C
- ◆ Mounting holes: 4.65mm (.180") dia.
- ◆ Dimensions: 73 mm x 39.5 mm x 25.5 mm
(2.85" x 1.55" x 1.0")
- ◆ Weight: 30g (2.4oz)

Wi-Sys Communications Inc.

31B Richardson Side Road
Ottawa, ON K2K 0A1 Canada
Tel 613.254.7386 Fax 613.254.7388
sales@wi-sys.com www.wi-sys.com